View NSN Online: https://aerobasegroup.tw/nsn/6520-01-176-7609

Product ID:BEAUTY-CAST INLAY INVESTMENT

MSDS Date:11/22/1991

FSC:6520

NIIN:01-176-7609

MSDS Number: BHBDQ === Responsible Party ===

Company Name: WHIP MIX CORP Address: 361 FARMINGTON AVE

City:LOUISVILLE

State:KY ZIP:40217 Country:US

Info Phone Num:502-637-1451

Emergency Phone Num:502-637-1451

Prepar

er's Name:DONNA RINGO

CAGE:FO376

=== Contractor Identification === Company Name:WHIP MIX CORP Address:361 FARMINGTON AVE

City:LOUISVILLE

State:KY ZIP:40217 Country:US

Phone:502-637-1451

CAGE:FO376

Company Name: WHIP-MIX CORP Address: 361 FARMINGTON AVE

Box:City:LOUISVILLE

State:KY ZIP:40217 Country:US

Phone:502-637-1451

CAGE:12164

======= Composition/Information on Ingredients ========

Ingred Name:SILICA DIOXIDE, CRYSTALLINE QUARTZ, SAND (SUSPECTED HUMAN CARCINOGEN BY IARC & ACG

| RTECS #:VV7330000 Other REC Limits:0.05 MG/CUM NIOSH OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.1 MG/M3 RDUST;9293 |
|--|
| Ingred Name:SILICA CRYSTALLINE, SILICA (CRISTOBALITE) (SUSPECTED HUMAN CARCINOGEN BY IARC) CAS:14464-46-1 RTECS #:VV7325000 Other REC Limits:0.05 MG/CUM NIOSH OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.05 MG/M3 RDUST9293 |
| Ingred Name:NUISANCE DUST OSHA PEL:5 MG/CUM (DUST) ACGIH TLV:5 MG/CUM (DUST) |
| Ingred Name:BARIUM (SOLUBLE COMPOUNDS) CAS:7440-39-3 RTECS #:CQ8370000 OSHA PEL :0.5 MG/CUM ACGIH TLV:0.5 MG/CUM |
| ====================================== |
| Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO Health Hazards Acute and Chronic:INHALATION: IRRITATION. SKIN/EYES: DRYNESS & IRRITATION. INGESTION: BARIUM SALT CAN BE FATAL. Explanation of Carcinogenicity:SEE INGREDIENTS Effects of Overexposure:INHALATION: LUNG DAMAGE, SILICOSIS. |
| ====================================== |
| First Aid:EYES: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES. |
| ====================================== |
| Unusual Fire/Explosion Hazard:THIS MATERIAL POSES NO FIRE OR EXPLOSION HAZARD. |
| ======== Accidental Release Measures ========= |
| Spill Release Procedures:VACUUM; AVOID CREATING DUST. AVOID WASHING DOWN DRAIN AS MATERIAL PLUGS DRAINS. |
| |
| |

IH) CAS:14808-60-7

| ====== Handling and Storage ============= |
|---|
| Handling and Storage Precautions:MINIMIZE DUST GENERATION AT ALL TIMES. MAY SOLIDIFY IF CONTACTED BY WATER. |
| ====== Exposure Controls/Personal Protection ======= |
| Respiratory Protection:USE NIOSH APPROVED RESPIRATOR TO AVOID EXPOSURE ABOVE RECOMMENDED LIMITS Work Hygienic Practices:WASH AFTER HANDLING. Supplemental Safety and Health |
| ========== Physical/Chemical Properties ========== |
| Spec Gravity:3 So Iubility in Water:SLIGHT Appearance and Odor:ODORLESS POWDER |
| ========= Stability and Reactivity Data ========== |
| Stability Indicator/Materials to Avoid:YES HYDROFLUORIC ACID Stability Condition to Avoid:MAY SOLIDIFY IF CONTACTED BY WATER |
| ======= Disposal Considerations ========== |
| Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. |

Disclaimer (provided with this information by the compiling agencies): This info rmation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.