

PACKAGING SERVICE CO., INC. -- BOILED LINSEED OIL -- 8010-00-244-8961

=====
Product Identification
=====

Product ID:BOILED LINSEED OIL

MSDS Date:11/01/1987

FSC:8010

NIIN:00-244-8961

MSDS Number: BHDCV

=== Responsible Party ===

Company Name:PACKAGING SERVICE CO., INC.

Address:4704 SHANK ROAD

Box:875

City:PEARLAND

State:TX

ZIP:77581

Country:US

Info Phone Num:(713) 485-1457

Emergency Phone Num:(713)

485-1457

Preparer's Name:SCIENTIFIC INFO SERVICES

CAGE:9V846

=== Contractor Identification ===

Company Name:PACKAGING SERVICES INC

Address:472 SHANK RD

Box:875

City:PEARLAND

State:TX

ZIP:77581

Country:US

Phone:713-485-1457

CAGE:9V846

=====
Composition/Information on Ingredients
=====

Ingred Name:BOILED LINSEED OIL

CAS:67746-08-1

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenic

ity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: POSSIBLY A MILD IRRITANT TO SKIN

Effects of Overexposure:SKIN: IRRITATION DEVELOPS SLOWLY AFTER CONTACT.
EYE: IRRITATION DEVELOPS IMMEDIATELY UPON CONTACT.

=====
===== First Aid Measures =====

First Aid:INGESTION: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. EYE: FLUSH WITH WATER FOR 15 MINUTES, GET MEDICAL ADVICE. SKIN: WASH WITH WATER AND SOAP.
GET MEDICAL ADVICE IF SYMPTOMS PERSIST.

=====
===== Fire Fighting Measures =====

Flash Point:200F/93C
Extinguishing Media:WATER FOG, SPRAY, FOAM, DRY POWDER, CARBON DIOXIDE
Fire Fighting Procedures:APPROACH FIRE FROM UPWIND SIDE. AVOID BREATHING SMOKE,FUMES,MIST,OR VAPORS.WATERMAY CAUSE FROTHING IF DIRECTED INTO CONTAINERS OF BURNING LIQ.
Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE FROM INTERNAL PRESSURE IF CONFINED TO FIRE AREA. COOL WITH WATER GET NEARBY PEOPLE OUT OF THE AREA.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILLS PICK UP WITH ABSORBENT MEDIA. STORE AS INDUSTRIAL WASTE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM OXIDIZERS OR MATERIALS BEARING A YELLOW DOT LABEL.
Other Precautions:AVOID CONTACT WITH SKIN, EYES, AND CLOTHING. IF CONTACT OCCURS REMOVE CONTAMINATED CLOTHING, LAUNDRY CLOTHING BEFORE REUSE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED
Ventilation:MECHANICAL OR LOCAL EXHAUST DESIRED
Protective Gloves:NEOPRENE RUBBER TYPE RECOMMENDED
Eye Protection:CHEMICAL GOGGLES WITH FULL FACE SHIELD
Other Protective Equipment:NONE
Work Hygienic Practices:WASH HANDS BEFORE EATING, DRINKING, OR SMOKING.
Supplemental Safety and Health
NK

=====
===== Physical/Chemical Properties =====

=====

Boiling Pt:B.P. Text:NA
Vapor Pres:NA
Vapor Density:NA
Spec Gravity:0.92
Evaporation Rate & Reference:NA
Solubility in Water:INSOLUBLE
Appearance and Odor:CLEAR YELLOW LIQUID W/DISTINCT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZER OR OXIDIZING MATERIALS
Hazardous Decomposition Products:FIRE,SMOKE,CARBON DIOXIDE/MONOXIDE,
POSSIBLY ACROLEIN.

===== Disposal Considerations =====

=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE,
AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional a
dvice to verify and
assume responsibility for the suitability of this information to their
particular situation.