

CHEMRAY COATINGS, CORP. -- ENAMEL, FLOOR AND DECK GRAY 16165 -- 8010-00-597-8231

===== Product Identification =====

Product ID:ENAMEL, FLOOR AND DECK GRAY 16165

MSDS Date:08/16/1989

FSC:8010

NIIN:00-597-8231

MSDS Number: BHFRD

=== Responsible Party ===

Company Name:CHEMRAY COATINGS, CORP.

Address:209 N. MICHIGAN AVE.

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1111

Emergen

cy Phone Num:800-924-9300 (CHEMTRAC)

CAGE:OBRN9

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

Company Name:CHEMRAY COATINGS CORP.

Address:209 N. MICHIGAN AVE.

Box:NA

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:800-924-9300

CAGE:OBRN9

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM SOLVENT,M.S. 66

CAS:8052-41-3

Fracti

on by Wt: 25%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:INHALATION: CAN CAUSE NAUSEA, HEADACHE,
DIZZINESS

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION
SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN: REMOVE
CONTAMINATED CLOTHING AND WAS
H THOROUGHLY WITH SOAP AND
WATER. INHALAT ION: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR,
CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL
PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:103F/40C
Lower Limits:.9
Upper Limits:7
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL
Fire Fighting Procedures:USE AIR-SUPPLIED BREATHING EQUIPMENT FOR
ENCLOSED CONTAINERS WITH WATER SPRAY. AVO
ID BREATHING VAPOR OR
FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER
SPRAY TO DISPERSE THE VAPORS FROM FIREFIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGN SOURCES. KEEP FROM HEAT,
SPARKS & OPEN FLAME. ADD ABSORBNT (SAND,EARTH,SAWDUST) TO SPILL.
VENTILATE AREA (OPEN WINDOWS,DOORS) IF LG SPILL, KEEP PRODUCT FROM
ENTERING SEWERS & WATER- COURSES BY DIKING. ADVISE AUTHOR

ITIES OF
SPILL.
Neutralizing Agent:NA

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES.
KEEP IN COOL, DRY, WELL-VENTILATED AREAS. AVOID DIRECT
SUNLIGHTAND EXTREME TEMPERATURES - HOT OR COLD.
Other Precautions:AVOID EYE, SKIN CONTACT, INHALATION, INGESTION OF
MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING
DUST.

===== Exposure Controls/Personal Protection =====
=====

Respiratory Protection:USE HYDROCARBON VAPOR CANNISTER OF SUPPLIED-AIR
RESPIRATOR IN CONFINED AREA.
Ventilation:LOCAL EXHAUST-FACE VELOCITY 60PPM SPECIAL-USE ONLY WITH
ADE-QUATE VENTILATN. MECHANICAL-USE EXPLOSION-PROOF EQUIPMENT.
Protective Gloves:CHEMICAL RESISTANT
Eye Protection:SPLASH GOGGLES OR FACE SHIELD
Other Protective Equipment:CHEMICAL RESISTANT APRON OR CLOTHING.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Bo
iling Pt:B.P. Text:308F/155C
Decomp Temp:Decomp Text:600F/316C
Vapor Pres:>10
Vapor Density:4.8
Spec Gravity:1.16
pH:NA
Solubility in Water:NEGLIGIBLE
Appearance and Odor:MOUSE GRAY LIQUID WITH KEROSENE ODOR
Percent Volatiles by Volume:51
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
CAN REACT WITH OXIDIZING MATERIAL WHEN HEATED TO
DECOMPOSITION.
Stability Condition to Avoid:HIGH TEMPERATURE
Hazardous De

composition Products:CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:ASSURE CONFORMITY WITH APPLICABLE DISPOSAL REGULATIONS. DISPOSE OF ABSORBED MATERIAL AT APPROVEDDISPOSAL SITE OR FACILITY. DISPOSE OF IN CONFOR- MITY WITH STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.