

ASAHIPEN AMERICAN INC. -- TT-S-711C DARK OAK -- 8010-00-165-8628

===== Product Identification =====

Product ID:TT-S-711C DARK OAK

MSDS Date:03/01/1990

FSC:8010

NIIN:00-165-8628

MSDS Number: BHMGL

=== Responsible Party ===

Company Name:ASAHIPEN AMERICAN INC.

Address:1126 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134-1197

Country:US

Info Phone Num:206-682-4603

Emergency Phone Num:303-573-1014 PO

ISON CENTER

Preparer's Name:DOUGLAS KIER

CAGE:DO047

=== Contractor Identification ===

Company Name:ASAHIPEN AMERICA INC.

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134-1197

Phone:303-573-1014 POISON CENTER

CAGE:DO047

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

(VAPOR PRESSURE 2.0 MM HG @ 68 F)

CAS:64475-85-0

RTECS #:PY8240000

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:MINERAL SPIRITS

CAS:68551-15-6

=====

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NOTICE: REPORTS HAVE ASSOCIATED

REPEATED & PROLONGED OCCUPATIONAL OVER-EXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Explanation of Carcinogenicity:NO

Effects

Effects of Overexposure:INHALE: NASAL & RESPIRATORY IRRITATION, DIZZINESS, WEAK, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUS & EVEN ASPHYXIATION. SKIN: MODERATE IRRITATION, DEFATTEMENT, DERMATITIS. EYE: RED, IRRITATION, TEARING, BLURRED VISION. SWALLOW: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING,DIARRHEA. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

===== First Aid Measures =====

First Aid:INHALE: REMOVE TO FRESH AIR. IF BREATH IS DIFFICULT, ADMINISTER

OXYGEN. IF BREATH HAS STOPPED GIVE CPR. KEEP PERSON WARM, QUIET & GET MEDICAL ATTENTION. EYE: WASH WITH WATER 15 MIN. CONSULT PHYSICIAN. SKIN: IF IRRITATION PERSISTS, WASH THOROUGHLY WITH SOAP & WATER, REMOVE & WASH CLOTHING BEFORE RE-USE. INGEST: DO NOT INDUCE VOMIT. GET MEDICAL ATTENTION. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:103 F/ 39 C

Lower Limits:1.0

Extinguishing

Media:USE FOAM, CO2, DRY CHEMICAL, WATER SPRAY OR FOG.

Fire Fighting Procedures:CLOSED CONTAINMENT MAY EXPLODE FROM EXTREME HEAT.

USE WATER FOR COOLING PURPOSES. AVOID SPREADING OF BURNING LIQUID. SELF-CONTAINED BREATHING APPARATUS IS NEEDED.

Unusual Fire/Explosion Hazard:DON'T APPLY TO HOT SURFACES. KEEP AWAY FROM HEAT, SPARK, ELECTRIC EQUIP & OPEN FLAMES. DO NOT STORE OR MIX WITH STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED.

===== Accidental Release Measures =====

=====

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. KEEP PEOPLE AWAY.  
RE-COVER FREE LIQ. ADD ABSORBENT (SAND, EARTH, ETC.) TO SPILL AREA.  
AVOID BREATHING VAPORS. VENT AREA. KEEP OUT OF SEWERS &  
WATERCOURSES BY DIKING OR IMPOUND. ADVISE AUTHORITIES IF PRODUCT  
HAS ENTERED.

===== Handling and Storage =====

Handling and Storage Precautions: DON'T HANDLE OR STORE NEAR HEAT,  
SPARKS, FLAME OR STRONG OXIDANTS. ADEQUATE VENTILATION REQUIRED.

NOSMOKING OR OPEN LIGHTS. DON'T TAKE INTERNALLY.

Other Precautions: REMOVE CONTAMINATED CLOTHING, LAUNDRY BEFORE RE-USE.  
WASH SKIN THOROUGHLY WITH SOAP & WATER AFTER CONTACT. GROUND  
CONTAINERS WHEN POURING & LIMIT FREE FALL TO MINIMIZE STATIC CHARGE  
BUILD-UP. EMPTY CONTAINERS MAY BE HAZARDOUS FROM RESIDUE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE ORGANIC VAPOR CANISTER OR SUPPLIED-AIR  
RESPIRATORY PROTECTION WHEN TLV IS EXCEEDED.

Ventilation: APPLICATION AREAS-PROVIDED WITH SUFFICIENT MECH VENTILATION  
W/EXPLOSION PROOF EQUIP TO MAINTAIN EXPOSURE LEVEL BELOW TLV

Protective Gloves: SOLVENT RESISTANT GLOVES

Eye Protection: SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment: PROTECTIVE CREAM WHERE SKIN CONTACT IS  
LIKELY. WEAR IMPERVIOUS CLOTHING & BOOTS TO PREVENT  
REPEATED/PROLONGED CONTACT

Work Hygienic Practices: WASH HANDS BEFORE EATING OR USING THE WASHROOM,  
SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

DO NOT TAKE INTERNALLY. AVOID PROLONGED CONTACT WITH SKIN OR BREATHING  
OR SPRAY MIST. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM  
CHILDREN. THIS PRODUCT CONTAINS NO LEAD PIGMENT. EMPTY CONTAINERS  
MAY BE HAZARDOUS FROM RESIDUES/VAPORS & ALL CAUTIONS ON THIS SHEET  
APPLY TO THEM.

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 314-383 F

Vapor Density: > AIR

pH: NA

Viscosity: 10"-25" 4FC

Evapor

ation Rate & Reference:SLOWER THAN AIR  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:THIN LIQUID, VARIOUS COLORS, MILD ODOR  
Percent Volatiles by Volume:65-69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:HIGH TEMPERATURE OR DIRECT HEATING.  
Hazardous Decomposition Products:MAY PRODUCE FUMES WHEN HEATED TO  
DECOMP. FUMES MAY CONTAIN CARBON MONOXID  
E/DIOXIDE, VARIOUS  
HYDROCARBONS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND  
LOCAL REGULATIONS. BEFORE ATTEMPTING CLEAN-UP, REFER TO HAZARD  
CAUTION INFORMATION IN OTHER SECTIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manne  
r whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.