View NSN Online: https://aerobasegroup.tw/nsn/8010-00-988-1458

PLASTI-KOTE CO., INC. -- AERODOL SPRAY PAINT TT-E-489-G BLUE 15095 -- 8010-00-988-1458

========== Product Identification ==========

Product ID:AERODOL SPRAY PAINT TT-E-489-G BLUE 15095
MSDS Date:01/08/1987
FSC:8010
NIIN:00-988-1458
MSDS Number: BHNBD
=== Responsible Party ===
Company Name:PLASTI-KOTE CO., INC.
Address:1000 LAKE ROAD
City:MEDINA
State:OH
ZIP:44256
Country:US
Info Phone Num:(216) 725-4511
Eme
rgency Phone Num:(216) 725-4511
CAGE:HO182
=== Contractor Identification ===
Company Name:PLASTI-KOTE CO., INC.
CAGE:HO182
Company Name:TEMPO PRODUCTS CO A PLASTI-KOTE CO INC
Address:1000 LAKE ROAD
Box:City:MEDINA
State:OH
ZIP:44256
Country:US
Phone:330-725-4511
CAGE:07708

========== Composition/Information on Ingredients ==========

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

========== Hazards Identification ==========

Routes of Entry: Inhalatio

n:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO
Health Hazards Acute and Chronic:INHAL: NASAL & RESPIR IRRI, DIZZ, WEAK, FATIGUE, NAUSEA, HEADACHES, UNCONS, ASPHXIATION. METHYLENE CHLORIDE-LOSS OF CONS & DEATH AS LOW AS 10,000 PPM NUMBNESS, RAPID HEART BEAT. EYES: SEV IRRI, RED, T EAR, BLURRED VISION, CONTACTS SHOULD NOTBE WORN. SKIN: PAINFUL IRRI. SWALLOW: GASTROIN IRRI, NAUSEA, VOMIT & DIARRHEA.
Explanation of Carcinogenicity:METHYLENE CHLORIDE A
PPEARS ON ABOVE
AGENCIES LISTS OF SUSPECTED CARCINOGENS.
Effects of Overexposure:SEE ABOVE. PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSDAM. SEVERE OVEREXPOSURE IN LAB ANIMALS HAS ALSO CAUSED LIVER ABNORMALITIES AND DAMAGE TO KIDNEYS, LUNG & SPLEEN. INTENT MISUSE BY DELIBERATE CONCEN & INHALE OFCONTENTS MAY BE HARMFUL OR FATAL. ALSO SKIN: IRRITATION, DEFATTING & DERMATITIS.
Medical Cond Aggravated by Exposure:CAN CAUSE ALLERGIC RESPIRATORY

REACTIONS AND/OR SKIN REACTIONS.

========== First Aid Measures ==========

First Aid:INHALE: REMOVE TO FRESH AIR. IF BREATH IS DIFF, ADMIN OXYGEN, IF STIPPED, GIVE CPR & SEEK MED HELP. EYES: FLUSH W/WTR 15 MINS. WHILE LIFTING LIDS. GET MED ATTNSWALLOWED: DO NOT INDUCE VOMIT (ASPIRATI ON OF MATERIAL INTO LUNGS CAN CAUSE CHEMPNEUMONITIES, CAN BE FATAL) KEEP PERSON WARM/QUIET, GET MED ATTN/POISON CONTROL CENTER. SKIN: WASH W/SOAP & WTR OR VARIOU
S HAND CLEANERS. LAUNDER
CLOTHING

========== Fire Fighting Measures ==========

Flash Point:NR
Lower Limits:1.0
Extinguishing Media:ALCOHOL, FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:WTR SPRAY MAY BE INEFFECT, USE TO COOL CLOSED CONT TO PREVENT PRESSURE BUILD-UP/AUTO-IGNITE/EXPLOSION. IF WTR USED FOG NOZZLE PREFER. SELF CONT BREATH APPARATUS
Unusual Fire/Explosion Hazard:CLOSED CONT MAY EXP &/OR AUTOIGNITE WHEN EXPOSED TO EXTREME HEAT. VAPORS ARE

HEAVIER THAN AIR, MAY TRAVEL
ALONG GROUND OR BY VENT & IGNITE AT LOCATIONS DISTANT

========== Accidental Release Measures ==========

Spill Release Procedures:ELMINATE ALL IGNITION SOURCES. EVACUATE AND VENT AREA. TURN OFF HEATING/AIR CONDITIONING TO PREVENTVAPOR CONTAMINATION. ABSORB LIQUID ON PAPER OR VERMICULITE. FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL & TRANSFER TO CLOSED CONTAINER.

========== Handling and Storage ==========
=====

Handling and Storage Precautions:DO NOT STORE IN AREAS ABOVE 120 F. IN DIRECT SUNLIGHT OR NEAR HEAT OR OPEN FLAMES. DO NOT PUNCTURE OR INCINERATE.
Other Precautions:NONE.

========== Exposure Controls/Personal Protection ==========

Respiratory Protection:TO AVOID BREATHING VAPORS OR SPRAY MIST, OPEN WINDOWS & DOORS OR USE OTHER MEANSTO ENSURE FRESH AIR ENTRY DURING APPLICATION & DRYING. WHERE VAPOR CONCENTRATIONIS GREATER THAN 100 PPM AN ORGANIC VAPOR TYPE
RESPIRATOR IS ADVISED.
Ventilation:PROVIDE SUFFICIENT MECH (GENERAL) &/OR LOCAL EXHAUST VENT TOMAINTAIN EXPOSURE BELOW TLV'S. DO NOT USE IN CONFINED AREA.
Protective Gloves:CHEMICAL RESISTANT (NEOPRENE).
Eye Protection:CHEMICAL SPLASH GOGGLES (OSHA REGULATED)
Other Protective Equipment:SOLVENT RESISTANT BOOTS, APRON, HEADGEAR AND/OR FACESHIELDS SHOULD BE WORN WHERE SPLASHING IS POSSIBLE.
Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM. AS WITH ALL CHEMICALS, MINIMI
ZE PERSONAL CONTACT AND/OR BREATHING OF
VAPORS.
Supplemental Safety and Health
NK.

========== Physical/Chemical Properties ==========

HCC:V3
Boiling Pt:B.P. Text:104-300 F
Melt/Freeze Pt:M.P/F.P Text:1500 E
Vapor Density:> AIR
Spec Gravity:< 1
Evaporation Rate & Reference:>1, PROPELLANT