

NILES CHEMICAL PAINT COMPANY -- N 1207A EARTH YELLOW CAMO TYPE IV -- 8010-01-130-3346
===== Product Identification =====

Product ID:N 1207A EARTH YELLOW CAMO TYPE IV
MSDS Date:10/11/1989
FSC:8010
NIIN:01-130-3346
Kit Part:Y
MSDS Number: BHNDN
=== Responsible Party ===
Company Name:NILES CHEMICAL PAINT COMPANY
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Info Phone Num:6
16-683-3377 (INFORMATION)
Emergency Phone Num:219-236-5856 (24 HOURS)
Preparer's Name:MIKE LICHATOWICH
CAGE:02388
=== Contractor Identification ===
Company Name:NILES CHEMICAL PAINT
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Phone:616-683-3377/219-236-5856
CAGE:02388

===== Composition/Information on Ingredients =====

Ingred Name:PM ACETATE
(VP 3.7 MM HG @ 20C)
CAS:108-65-6
RTECS #:AI8925000
Fraction by Wt: 17%

Ingred Name:POLYES

TER RESIN
Fraction by Wt: 16%

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 9%
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 7%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTE
CS #:ZE2100000
Fraction by Wt: 3%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CHROMIUM (III) OXIDE
CAS:1308-38-9
RTECS #:GB6475000
Fraction by Wt: 1%
OSHA PEL:0.5 MG/M3 (CR)
ACGIH TLV:0.5 MG/M3 (CR); 8990

Ingred Name:VOC. ORGANIC CMPD 4.33 LB/GAL LESS WATER & NPRS* (NK) G/L
LESS WATER VOC. (NK) LB/GAL SOLIDS (NK) G/L SOLIDS CALCU
RTECS #:9999999VO

===== Hazards Identification =====

Rout

es of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:HISTOLOGIC FIBROSIS OF LUNGS,
INCOHERENCE, CORNEAL VACUOLIZATION, ANOREXIA. TAR-GET ORGANS: CNS,
LUNGS, EYES, SKIN, RESPIRATORY SYS, GI TRACT, BLOOD, LIVER,
KIDNEYS.ALSO SEE BELOW
Explanation of Carcinogenicity:NOT LISTED
Effects of Overexposure:EYE: SEVERE IRRI, LACRIMATION, RED, BLURRED
VISION. SKIN: RED & IRRI, DEFATTING OF SKIN, DERMATITIS
. BREATH:
NASAL & RESPIRATORY IRRI, CNS DEPRESS (DIZZ, DROWS,WEAK, FATIGUE,
CONF) NAUSEA, HEAD, VERTI GO, UNCONSC, ASPHYX. INGES:
GASTROINTESIRRI, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA

===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR AT ONCE. IF BREATH STOPPED, CPR,
GET MED ATTN IMMEDIATELY. SKIN: IMMEDIATELY FLUSH WITH PLENTY OF WATER. REMOVE
CONTAMINATED CLOTHES & FLUSH SKIN WITH WATER. GET MED ATTN. LAUNDRY CLOTHES &
SHOES BEFORE REUSE. EYE: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER 15 MIN, LIFTING
LIDS. GET MED ATTN IMMEDIATELY. CONTACT LENS SHOULD NOT BE WORN.
INGESTION: DRINK 1/2 GLASSES WATER. DO NOT INDUCE VOMIT. GET MED
ATTN/POISON CONTROL IMMEDIATELY

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:20 F/ -6 C
Lower Limits:1.0
Upper Limits:10
Extinguishing Media:DRY CHEMICAL, FOAM, CO2
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS WITH FULL
FACEPIECE OPERATED POSITIVE
PRESSURE & FULL PROTECTIVE CLOTHES. WATER TO
COOL CLOSED CONTAINMENT PREVENT PRESSURE BUILDUP/EXPLOSION
Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED. VAPORS HEAVIER
THAN AIR, MAY TRAVEL ALONG GROUND TO IGNITE SOURCE. ISOLATE FROM
HEAT, ETC. OVEREXPOSURE TO DECOMPRESSION MAY CAUSE HEALTH HAZARDS

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. MINIMIZE BREATHING OF
VAPORS.AVOID SKIN CONTACT. ABSORB WITH INERT MATERIAL; CLAY,SOIL,

OR
COMMERCIALLY AVAIL ABSORBENT. SHOVEL RECLAIMED LIQ/ABSORBENT INTO
RECOVERY OR SALVAGE DRUMS FOR DISPOSAL. LG: DIKE, RECLAIM IN
DRUM,TANK,TRUCK

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMP AREAS OR
NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN
USEAVOID ROUGH HANDLING.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN
EMPTY. DO NOT WELD OR FLAME ORCUT ON
EMPTY DRUMS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROPRIATE PROPERLY FITTED RESPIRATOR
(NIOSH/MSHA) DURING & AFTER APPLICATION UNLESS AIR MONITOR DEMO
VAPOR/MIST LEVELS ARE BELOW APPLICABLE LIMITS. FOLLOW RESPIRATOR
MANUFACTURER'S DIRECTIONS FOR USE

Ventilation:SUFFICIENT VENT IN VOL/PATTERN TO KEEP AIR CONCEN BELOW
CURRENT APPL OSHA PERMISSIBLE LIMIT. REMOVE DECOMP PRODUCTS

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:CHEM GOGGLES/SAFETY GLASSES/FACE SHIELD

Other Protective Equipment:WEAR CHEMICAL RESISTANT CLOTHING AS NEEDED
TO PREVENT SKIN CONTACT. REMOVE CLOTHES THAT BECOME WET (FLAMMABLE
HAZARD)

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING
RESTROOM. WASH PROMPTLY WHEN SKIN BECOMES CONTAMINATED.

Supplemental Safety and Health

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION
TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. DURING E
MERGENCY

CONDITIONS, OVEREXP TO DECOMP PRODUCTS MAY CAUSE A HEALTH HAZAR D.
SYMPTOMS MAY NOT BE IMMEDIATELY APPA-RENT. OBTAIN MEDICAL
ATTENTION.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-302 F

Decomp Temp:Decomp Text:NE

Vapor Density:> AIR

Viscosity:70-85 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, ODOR OF SOLVENTS

Percent Volatiles by Volume:57.72

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDES

Stability Condition to Avoid: UNDER REASONABLE CONDITIONS OF STORAGE AND USE

Hazardous Decomposition Products: CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE

Conditions to Avoid Polymerization: HIGH TEMPERATURES, SHOCK FROM DROPPING

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.