View NSN Online: https://aerobasegroup.tw/nsn/6850-01-311-1180

Product ID:URESOLVE PLUS MSDS Date:09/01/1989 FSC:6850 NIIN:01-311-1180 MSDS Number: BHQRN === Responsible Party === Company Name: DYNALOY INC Address:7 GREAT MEADOW LN **City:EAST HANOVER** State:NJ ZIP:07936-1703 Country:US Info Phone Num:201-887-3678 Emergency Phone Num:201-887-3678 Preparer's Name: JAY W. PARTON CAGE :27905 === Contractor Identification === Company Name: DYNALOY INC Address:7 GREAT MEADOW LN **City:EAST HANOVER** State:NJ ZIP:07936-1703 Country:US Phone:201-887-9270/201-887-3678 FAX CAGE:27905 Company Name: DYNALOY, INC. Address:1910 SOUTH STATE AVE. Box:City:INDIANAPOLIS State:IN ZIP:46203 Country:US Phone:317-788-9925;703-527-3887 CAGE:27908

Ingred Name:2-METHOXYETHANOL (EGME) (SARA III) CAS:109-86-4 RTECS #:KL5775000 Fracti on by Wt: 60-80% OSHA PEL:S, 25 PPM ACGIH TLV:S, 5 PPM; 9192

Ingred Name:POTASSIUM HYDROXIDE (SARA III) CAS:1310-58-3 RTECS #:TT2100000 Fraction by Wt: 2-4% OSHA PEL:C, 2 MG/M3 ACGIH TLV:C 2 MG/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:OTHER COMPONENTS (TYPE NOT SPECIFIED)

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 2460 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity

:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: MODERATELY TOXIC. EYE AND SKIN IRRITATION. HEADACHE, DIZZINESS, DROWSINESS, FATIGUE, NAUSEA, VOMITING, TREMOR, CONFUSION, KIDNEY DAMAGE. CHRONIC: REPEATED OVEREXPOSURE MAY CAUSE INJURY TO BONE MARROW AND BLOOD CELLS, KIDNEY, LIVER, AND TESTES.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE, SKIN & RESPIRATORY TR

ACT IRRITATION,

HEADACHE, DIZZINESS, DROWSINESS, FATIGUE, NAUSEA, VOMITING, TREMOR, CONFUSION.

Medical Cond Aggravated by Exposure:BREATHING OF VAPOR AND/OR MIST MAY AGGRAVATE ASTHMA AND INFLAMMATORY OR FIBROTIC PULMONARY DISEASE.

First Aid:INHALATION:REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, OXYGEN MAY BE GIVEN BY QUALIFIED PERSONNEL. CALL A PHYSICIAN. EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUT ES, INCLUDING UNDER THE

EYELIDS. CALL A PHYSICIAN. SKIN:REMOVE CONTAMINATED CLOTHING AND FLUSH WITH WATER. INGESTION: GIVE 2 GLASSES OF WATER AND INDUCE VOMITING IF THE PATIENT IS CONSCIOUS. CALL A PHYSICIAN.

Flash Point Method:CC Flash Point:117F,47C Autoignition Temp:Autoignition Temp Text:545F Lower Limits:1.8 Upper Limits:14.0 Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG. Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:WEAR SUITABLE PROTECTIVE EQUIPMENT. SMALL SPILLS SHOULD BE FLUSHED WITH LARGE QUANTITIES OF WATER. LARGE SPILLS SHOULD BE COLLECTED FOR DISPOSAL. Neutralizing Agent:NONE SPE CIFIED BY MANUFACTURER.

Handling and Storage Precautions:DO NOT BREATH VAPOR. USE WITH ADEQUATE VENTILATION. DO NOT GET IN EYES, ON SKIN, OR CLOTHING. ACCIDENTAL CONTACT SHOULD BE WASHED AWAY IMMEDIATELY.
Other Precautions:KEEP AWAY FROM HEAT AND FLAME. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. CAUSES EYE IRRITATION. COMBUSTIBLE.

Respiratory Protection: USE NIOSH/MSHA APPROVED SUPPLIED AIR RESPIRATOR FOR HIGH CONCENTRATIONS.

Ventilation: MECHANICAL (GENERAL) ROOM VENTILATION AND LOCAL EXHAUST REQUIRED. USE EXPLOSION PROOF MOTOR.

Protective Gloves:NEOPRENE

Eye Protection:SAFETY GOGGLES

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER. IMPERMEABLE APRON.

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT

WEAR CONTAMINATED CLOTHING OR FOOTWEAR. Supplemental Safety and Health AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.

HCC:F4 Boiling Pt:B.P. Text:256F,124C Vapor Pres:6.2 Vapor Density:2.62 Spec Gravity:0.990 pH:12.8 Evaporation Rate & amp; Reference:0.62(N-BUTYL ACETATE=1) Solubility in Water:COMPLETE Appearance and Odor:BLUE TO GREEN BROWN LIQUID, SLIGHT PLEASANT ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

Waste Disposal Methods:INCINERATE IN A FURNACE WHERE PERMITTED UNDER APPROPRIATE FEDERAL, STATE AND LOCAL REGULATI ONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular s ituation.