View NSN Online: https://aerobasegroup.tw/nsn/8010-00-161-7419

Product ID:PRIMER, ZINC CHROMATE YELLOW ALKYD TYPE MSDS Date:09/11/1989 FSC:8010 NIIN:00-161-7419 MSDS Number: BJDJG === Responsible Party === Company Name: CHEMRAY COATINGS, CORP. Address:209 N. MICHIGAN AVE. Box:NA City:KENILWORTH State:NJ ZIP:07033 Country:US Info Phone Num:2 01-245-1111 Emergency Phone Num:201-245-1111 Preparer's Name: FRED ARMSTRONG CAGE:OBRN9 === Contractor Identification === Company Name: CHEMRAY COATING CORP Address:209 N MICHIGAN AVE Box:City:KENILWORTH State:NJ ZIP:07033 Country:US Phone:201-245-1111 CAGE:33832 Company Name: CHEMRAY COATINGS CORP. Address:209 N. MICHIGAN AVE. Box:NA City:KENILWORTH State:NJ ZIP:07033 Country:US Phone:800-924-9300 CAGE:OBRN9

Ingred Name:STODDAR

D SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 32% OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293

Ingred Name:ZINC CHROMATE CAS:50922-29-7 RTECS #:GB3295000 Fraction by Wt: 23% ACGIH TLV:0.01 MG/M3

Ingred Name:LEAD DRIER AS (PB) Fraction by Wt: 0.1% OSHA PEL:0.05 MG/M3 ACGIH TLV:0.15 MG/M3

Ingred Name:COLBALT DRIER AS (CO) Fraction by Wt: 0.03% OSHA PEL:0.01 MG/M3 ACGIH TLV:0.01 MG/M3

Ingred Name:VOC. ORGANIC CMPD 3.6 LB/GAL LESS WATER & NPRS* 432 G/L RTECS #:9999999VO

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED BY OVER INHALATION. Explanation of Carcinogenicity:CHROMATES ARE CARCINOGENS Effects of Overexposure:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED BY OVER INHALATION. Medical Cond Aggravated by Exposure:NONE GENERALLY KNOWN.

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CALL A PHYSICIAN. SKIN CONTACT: REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY WITH SOAP AND WATER. INH ALATION: IF OVERCOME BY VAPORS, REMOVETO FRESH AIR, CALL A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL A PHYSICIAN.

Flash Point Method

:SCC Flash Point:103F/40C Autoignition Temp:Autoignition Temp Text:473F Lower Limits:0.9 Upper Limits:7 Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL. Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL ENCLOSED CONTAINERS WITH WATER SPRAY.AVOID BREATHING VAPORS OR FUMES.
Unusual Fire/Explosion Hazard: IF LEAK OR SPILL HAS IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.
======================================
Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARK& OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST)TO SPILL. VENTILATE AREA (OPEN WINDOWS, DOORS) IF LARGE SPILL KEEP PRODUCT FROM ENTERING SEWER/WATER COURSES BY DIKING. ADVISE AUTHORITIES IF ENTERED. Neutralizing Agent:NA
======================================
 Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES, KEEP IN COOL, DRY, WELL VENTILAT ED AREAS. AVOID DIRECT SUNLIGHT AND EXTREME TEMPERATURES, HOT OR COLD. Other Precautions:AVOID EYE, SKIN CONTACT, INHALATION, INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.
======================================
 Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREA. Ventilation: LOCAL EXHAUST-FACE VELOCITY 60 FPM. SPECIAL USE ONLY WITH ADEQUATE VENTILATION. MECHANICAL U SE EXPLOSION PROOF EQUIPMNT. Protective Gloves: CHEMICAL RESISTANT Eye Protection: SPLASH GOGGLES OR FACE SHIELD Other Protective Equipment: USE CHEMICAL RESISTANT APRON OR CLOTHING Supplemental Safety and Health AVOID EYE, SKIN CONTACT, INHALATION, INGESTION OF MISTS, SPRAY OR VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.
======================================
Boiling Pt:B.P. Text:308F/155C

Boiling Pt:B.P. Text:308F/155C Melt/Freeze Pt:M.P/F.P Text:0F(-17.8C) Decomp Temp:Decomp Text:600 F/316C Vapor Pres: