

CALGON VESTAL LABS -- 1-STROKE VESPHENE, 6397-08 -- 6840-01-140-0860

===== Product Identification =====

Product ID:1-STROKE VESPHENE, 6397-08

MSDS Date:08/21/1989

FSC:6840

NIIN:01-140-0860

MSDS Number: BJJHV

=== Responsible Party ===

Company Name:CALGON VESTAL LABS

Address:5035 MANCHESTER AVE

City:ST LOUIS

State:MO

ZIP:63110

Country:US

Info Phone Num:314-535-1810

Emergency Phone Num:314-862-2000;8

00-424-9300(CHEMTREC)

Preparer's Name:R C JENTE

CAGE:0LKT5

=== Contractor Identification ===

Company Name:CALGON VESTAL LABORATORIES

Address:5035 MANCHESTER AVENUE

Box:City:ST LOUIS

State:MO

ZIP:63110

Country:US

Phone:800-424-9300 (CHEMTREC)

CAGE:0LKT5

===== Composition/Information on Ingredients =====

Ingred Name:2-PHENYLPHENOL (SARA III)

CAS:90-43-7

RTECS #:DV5775000

Fraction by Wt: 11.1%

Ingred Name:#0-BENZYL-P-CHLOROPHENATE

CAS:120-32-1

Fraction by Wt: 8.9%

Ingred Name

:P-TERTIARY AMYLPHENOL

CAS:80-46-6

Fraction by Wt: 2.3%

Ingred Name:HEXYLENE GLYCOL

CAS:107-41-5

RTECS #:SA0810000

Fraction by Wt: 29 ML/FT3 @ 1:256 FOR 6 HOURS. MIST OF USE-DILUTION MAY
IRRIT NASAL PASSAGES.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:SEE HEALTH HAZARDS.

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR
15 MINUTES.

GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION:
REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING. DRINK LG
QUANTITIES OF FLUID. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:>200F, >93C

Extinguishing Media:SUITABLE FOR SURROUNDING FIRE - WATER, CO*2, FOAM,
DRY CHEM

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT

=====

===== Accidental Release Measures =====

Spill Release Procedures:SPILLS MAY BE CLEANED UP W/FLOWING WATER. THIS
IS A CLEANING AND DISINFECTING PROD.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:PROD WILL WITHSTAND OCCASN ACCIDENTAL
FRZ W/O LOSS IN ITS NORM PERFORMANCE CHARAC. IT MUST BE THOROUGHLY
THAWED & AGITATED (ROLL DRUM) BEFORE USING.

Other Precautio

ns:READ AND OBSERVE LABELED USE INSTRUCTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE CONCERN .

Ventilation:NORMAL ROOM VENTILATION.

Protective Gloves:RUBBER GLOVES

Eye Protection:CHEMICAL WORKERS GOGGLES

Other Protective Equipment:EMERGENCY EYE WASH & DELUGE SHOWER

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:200F,93C

Spec Gravity:1.0769 @ 25C

pH:12.6

Solubility in Water:COMPLETE

Appearance and Odor:BROWN LIQUID, MILD & PLEASANT ODOR

Percent Volatiles by Volume:64

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:FORCED IGNI

TION OF DRIED RESIDUES MAY

PRODUCE CO, CO*2, SULFUR OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:WASTES SOLUTIONS MAY BE SEWERED, DISPOSAL MUST BE I/AW FEDERAL, STATE AND LOCAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants t

his information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.