

ACCUMETRIC INC -- 200 FLUID, 5000 CS -- 9150-00-664-3829

===== Product Identification =====

Product ID:200 FLUID, 5000 CS
MSDS Date:01/22/1991
FSC:9150
NIIN:00-664-3829
MSDS Number: BJNWT
=== Responsible Party ===
Company Name:ACCUMETRIC INC
Address:350 RING RD
Box:843
City:ELIZABETHTOWN
State:KY
ZIP:42701
Country:US
Emergency Phone Num:502-769-3385
CAGE:58149
=== Contractor Identification ===
Com
pany Name:ACCUMETRIC INC
Address:350 RING RD
Box:843
City:ELIZABETHTOWN
State:KY
ZIP:42701
Country:US
Phone:502-769-3385
CAGE:58149

===== Composition/Information on Ingredients =====

Ingred Name:SILICONE FLUID
CAS:63148-62-9
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/SKIN

: PROLONGED CONTACT CAN CAUSE
SLIGHT IRRITATION. GENERAL: LOW TOXICITY LEVEL ON CONTACT OR
INGESTION.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:IRRITATION OF EYES/SKIN/RESPIRATORY TRACT.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF SKIN AND
RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====
=====

First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.
GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION:
REMOVE TO FRESH AIR. INGESTION: MANUFACTURER REPORTS THAT NO FIRST
AIR SH OULD BE NEEDED FOR SMALL ORAL AMOUNTS ACCIDENTALLY INGESTED.

===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:>610F,>321C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting P

rocedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:MOP OR WIPE UP SPILL WITH ABSORBENT MATERIAL.

Neutralizing Agent:NONE

===== Handling and Stor
age =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED
AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT
IN USE. PROTECT FROM PHYSICAL DAMAGE.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION
EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS
PER CURRENT 29 CFR 1910.134

, INSTRUCTIONS/WARNINGS AND
NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS USUALLY ADEQUATE.

Protective Gloves:RUBBER OR PLASTIC GLOVES

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres: