

KOP-COAT, INC. -- MIL-P-15930C FORMULA 120 GREEN -- 8010-00-664-0018

===== Product Identification =====

Product ID:MIL-P-15930C FORMULA 120 GREEN

MSDS Date:11/01/1989

FSC:8010

NIIN:00-664-0018

MSDS Number: BJQDX

=== Responsible Party ===

Company Name:KOP-COAT, INC.

Address:436 SEVENTH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219

Country:US

Info Phone Num:800-547-2468/412-227-2700 OUT OF US

Emergency

Phone Num:800-548-0489/800-424-9300 CHEMTREC

CAGE:HO783

=== Contractor Identification ===

Company Name:KOP-COAT INC

Address:436 7TH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

Phone:800-553-5631, CHEMTREC 800-424-9300

CAGE:00297

Company Name:KOP-COAT, INC.

Address:436 SEVENTH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219

Country:US

Phone:800-547-2468

CAGE:HO783

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-

10-1  
RTECS #:SA9275000  
Fraction by Wt: 35-40%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/75 STEL  
ACGIH TLV:50 PPM/75 STEL; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 25-30%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ZINC CHROMATE  
CAS:13530-65-9  
RTECS #:GB3290000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:0.1 MG/M3 (CRO3)  
ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:TALC  
CAS:14807-96-6  
RTECS #:VV7720000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:2 MG/M3 TWA  
ACGIH TLV:2 MG/M3

Ingred Name:VINYL CHLORIDE (SARA III)  
CAS:75-01-4  
RTECS #:KU9625000  
Fraction by Wt: .1-.2%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:SEE 1910.1017  
ACGIH TLV:5 PPM, A1; 9293  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:TRICRESYL PHOSPHATE (EXPOSURE LIMITS ARE TRI-O-CRESYL  
PHOSPHATE)  
CAS:1330-

78-5  
RTECS #:TD0175000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:0.1 MG/M3 TWA  
ACGIH TLV:0.1 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:INGESTION:MAY CAUSE GASTROINTESTINAL  
DISTURBANCES. ASPIRATION INTO LUNG MAY CAUSE CHEMICAL PNEUMONITIS  
WHICH MAY BE FATAL. INHALE:CHRONIC EXPOSURE TO CERT  
AIN CHROMIUM  
COMPOUNDS HAS BEEN SHOWN TO INCR EASE LUNG CANCER INCIDENCE.  
PROLONGED/REPEATED INHALE OF HIGH CONCENTRATES MAY CAUSE CENTRAL  
NERVOUS SYSTEM DEPRESSION  
Explanation of Carcinogenicity:SUFF EVIDENCE OF RESPIRATORY  
CARCINOGENICITY IN MEN. INCREASED INCIDENCES OF LUNG CANCER AMOUNG  
WORKERS. (CHROMIUM VI)  
Effects of Overexposure:EYES:MAY CAUSE IRRITATION. SKIN:MAY CAUSE  
IRRITATION &/OR DEFATTING,BLISTERING,CRACKING &/OR DRYNESS. CONTACT  
W/CHROMATE DUST MAY CAU  
SE IRRITATION & POSSIBLE SENSITIZATION.  
INHALE:RESPIRATORY IRRITATI  
ON,HEADACHE,DIZZINESS,WEAKNESS,NAUSEA,INCOORDINATION & POSSIBLE  
COLLAPSE. INGESTION:GASTROINTESTNAL DISTURBANCES.  
Medical Cond Aggravated by Exposure:PERSONS W/PRE-EXISTING DISEASE IN  
OR A HISTORY OF AILMENTS INVOLVING EYES, SKIN, RESPIRATORY TRACT &  
CENTRAL NERVOUS SYSTEM ARE AT GREATER THAN NORMAL RISK OF DEVELOPING  
ADVERSE EFFECTS FROM EXPOSURE.

===== First Aid Measures =====  
=====

First Aid:EYE:IMMED FLUSH W/LG AMNTS OF WATER 15 MINS,GET MED.SKIN:WASH  
THORO W/SOAP & WATER.IF IRRIT OCCURS/PERSISTS,GET MED.WASH CONTAM  
CLOTHES BEFORE REUSE.INHALE:REMOVE FROM EXPOSURE.IF BREATH  
STOPPED/DIFF, ADMIN CPR/OXYGEN AS NEEDED.GET MED.INGEST:DO NOT  
INDUCE VOMIT.GIVE 1 GLASS OF MILK OR 1-2 OZ(30 TO 60G)ACTIVATED  
CHARCOAL IN WATER AS TOLERATED.IMMED GET MED.DO NOT GIVE ANYTHING  
IF PERSON IS UNCONSC

===== Fire Fighting Measures =====

=====

Flash Point Method:CC

Flash Point:45 F/7.2 C

Extinguishing Media:CO2, DRY CHEMICAL, WATER SPRAY, ALCOHOL OR  
UNIVERSAL TYPE FOAMS PER MFR'S RECOMMENDATIONS. WATER MAY BE  
INEFFECTIVE.

Fire Fighting Procedures:WEAR COMPLETE FIRE SERVICE PROTECTIVE EQUIP,  
INCLUDING FULL-FACE MSHA/NIOSH APPROVED SCBA. USE WATER TO COOL  
FIRE-EXPOSED CONTAINER/STRUCTURE/PROTECT PERSONNEL

Unusual Fire/Explosion Hazard:VAPOR FORM FLAMM/EXPLOS MIX IN AIR.VAPOR  
HEAVY,MAY TRAVEL(GROUND  
/SEWER)TO IGNITE SOURCE-FLASH.FIRE MAY EMIT  
IRRIT/TOXIC GAS &/OR FUME.CLOSE CONTAIN MAY EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:STOP SPILL IF NO RISK.ELIM ALL IGNITE  
SOURCES.VENT AREA.AVOID BREATHING VAPOR.AVOID CONTACT W/HOT  
LIQ/FUMES.TAKE UP CAREFULLY TO AVOID HEAT/SPARKS.USE AN INERT  
ABSORB TO COMPLETE CLEAN-UP.REPORT RELEA SE INTO ENVIR TO  
NRC(1-800-424-8802),1 LB OR MORE.

===== Handling and  
Storage =====

Handling and Storage Precautions:STORE IN AREAS/BLDG DESIGN TO COMPLY  
W/OSHA 1910.106. KEEP IN CLOSED, LABELED CONTAINER W/COOL,WELL  
SHADED,DRY VENT AREA.PROTECT FROM PHYSICAL DAMAGE

Other Precautions:KEEP CONTAINER CLOSED WHEN MATERIAL IS NOT IN  
USE.MAINTAIN GOOD HOUSEKEEPING.NOT FOR USE/STORAGE IN/AROUND  
HOME.GROUND/BOND DRUM.DO NOT USE PRESSURE TO EMPTY DRUMS.KEEP AWAY  
FROM HEAT & OPEN FLAME.SPR AY PAINT IN ACCORD W/OSHA 29CFR 1910.107

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALE  
EXPOSURES BELOW PEL(TLV), USE APPROVED UNITS AS PER CURRENT  
29CFR1910.134 & NIOSH/RESPIRATOR DECISION LOGIC-PUB. #87.108. IF  
WITHIN OSHA PROTECTION FACTOR, AIR PURIFYING OV/FILTER UNITS OK.

Ventilation:SUFF GENERAL/LOCAL EXHAUST VENT IN PATTERN/VOL TO CONTROL  
INHALE EXPOSURE BELOW LIMITS & BELOW FLAMM VAPOR CONCENTRATION

Protective Gloves:INDUSTRIAL RES

ISTANT FLEX TYPE GLOVES

Eye Protection:SAFETY GLASSES/SIDE-FACE SHIELDS/GOGGLES

Other Protective Equipment:WEAR INDUSTRIAL-TYPE WORK CLOTHES & SAFETY  
FOOTWEAR. PROTECTIVE GARMENTS:HEAD/NECK  
COVER,APRONS,JACKETS,PAINTS,COVERALLS

Work Hygienic Practices:OBSERVE GOOD HYGIENE & SAFETY PRACTICES WHEN  
HANDLING THIS PRODUCT. AVOID PROLONGED OR REPEATED BREATHING OF  
VAPORS.

Supplemental Safety and Health

NOTE TO PHYSICIAN:THERE IS NO SPECIFIC ANTIDOTE FOR EFFECTS FROM  
OVEREXPOSURE TO  
THIS MATERIAL. TREATMENT SHOULD BE DIRECTED AT THE  
CONTROL OF SYMPTOMS & THE CLINICAL CONDITION.

===== Physical/Chemical Properties =====

Vapor Density:>1

Spec Gravity:8.55 LBS/GAL

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREEN VISCOUS LIQUID WITH TYPICAL SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

HEAT, SPARKS & OPEN FLAME.

Hazardous Decomposition Products:CARBON MONOXI  
DE, CARBON DIOXIDE UPON  
THERMAL DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE &  
FEDERAL REGULATIONS. AVOID PROLONG/REPEATED BREATHING OF VAPORS,  
MIST, FUMES OR SKIN & EYE CONTACT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner what  
soever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.