View NSN Online: https://aerobasegroup.tw/nsn/1440-00-152-3172

Product ID:COATED ABRASIVE ALUMINUM OXIDE: 163,175,194 MSDS Date:04/30/1986 FSC:1440 NIIN:00-152-3172 Kit Part:Y MSDS Number: BJQMQ === Responsible Party === Company Name: WORLD ABRASIVES COMPANY, INC. Address:1866 EASTERN PARKWAY City:BROOKLYN State:NY ZIP:11233-4398 Country:US Info Phone Num:718-495-4300 Emergency Phone Num:718-495-4300 Preparer's Name: AL KITTLESON CAGE:0CLX1 === Contractor Identification === Company Name: EUR-PAC CORP. Address:112 PORTER ST Box:City:WATERBURY State:CT ZIP:06708 Country:US Phone:203-756-0102 / FAX 0103 CAGE:8B805 Company Name: WORLD ABRASIVES COMPANY, INC. Address:1866 EASTERN PARKWAY Box:City:BROOKLYN State:NY ZIP:11233-4398 Country:US Phone:718-495-4300 CAGE:0CLX1

====== Composition/Information on Ingredients ====

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS FORMS) (SARA III) CAS:1344-28-1 RTECS #:BD1200000 Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SILICA CAS:112945-52-5 RTECS #:VV7310000 Other REC Limits:NONE SPECIFIED OSHA PEL:6 MG/M3 TDUST ACGIH TLV:10 MG/M3 T DUST

Ingred Name:MAGNESIUM OXIDE CAS:1309-48-4 RTECS #:OM3850000 Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 PARTICULATE ACGIH TLV:10 MG/M3;TDUST; 9293

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE EXPOSURE MAY CAUSE BREATHING DIFFICULTY; SKIN, EYE, NASAL & RESPIRATORY IRRITATION. FLUORIDE SALTS CAN CAUSE GASTRI C PAIN, INTERNAL BLEEDING, TISSUE DAMAGE &

DEATH. CHRONIC EXPOSURE TO FLUORIDE COMPOUNDS HAS BEEN REPORTED TO CAUSE OSTEOCLOROSIS, MOTTLING OF TOOTH ENAMEL & DAMAGE TO SKIN, EYE AND MUCOUS MEMBRANES.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:ACUTE EXPOSURE MAY CAUSE BREATHING DIFFICULTY; SKIN, EYE, NASAL & RESPIRATORY IRRITATION. FLUORIDE SALTS CAN CAUSE GASTRIC PAIN, INTER

NAL BLEEDING, TISSUE DAMAGE & DEATH. CHRONIC EXPOSURE TO FLUORIDE COMPOUNDS HAS BEEN REPORTED TO CAUSE OSTEOCLOROSIS, MOTTLING OF TOOTH ENAMEL & DAMAGE TO SKIN, EYE AND MUCOUS MEMBRANES.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF EYE, SKIN AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.
======================================
First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL A
TTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION.
======================================
Flash Point:NONE Autoignition Temp:Autoignition Temp Text:NONE Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, OR OTHER MEDIA APPROVED FOR ORDINARY COMBUSTIBLE "CLASS A FIRE" MATERIALS. Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.
===== Accidental Release Measures ====================================
Spill Release Procedures:USE ORDINARY PRECAUTIONS FOR DUSTS AND PARTICULATES. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER. Other Precautions:NONE SPECIFIED BY MANUFACTURER.
======================================
Respiratory Protection: IF LIMITS ARE EXCEEDED DURING SAND ING OR
GRINDING, AN APPROVED NIOSH RESPIRATOR MUST BE USED. Ventilation:LOCAL EXHAUST HOOD WITH DUST COLLECTOR MUST BE USED TO CONTROL EXPOSURE TO DUST OR FUMES.
Protective Gloves:WORK GLOVES Eye Protection:SAFETY GLASSES/GOGGLES WHILE SANDING Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health THIS IS PART OF A KIT SU

PPLIED BY EUR-PAC INC.

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:1832F,1000C Solubility in Water:NEGLIGIBLE Appearance and Odor:GRANULAR, WHITE TO LIGHT BROWN ABRASIVE. NO ODOR Percent Volatiles by Volume:0

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:DURING MELTING AT ELEVATED TEMPERATURES, VARIOU S FLUORIDE COMPOUNDS MAYBE LIBERATED.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and di

sclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.