

IDEAL INDUSTRIES INC -- WIRE LUBE WIRE PULLING LUBRICANT,ALL"31" SERI

=====

MSDS Safety Information

=====

FSC: 9150  
NIIN: 00-804-1036  
MSDS Date: 07/29/1993  
MSDS Num: BJRPP  
Product ID: WIRE LUBE WIRE PULLING LUBRICANT,ALL"31" SERIES  
MFN: 01  
Responsible Party  
Cage: 30119  
Name: IDEAL INDUSTRIES INC  
Address: BECKER PL  
City: SYC  
AMORE IL 60178  
Info Phone Number: 815-895-5181  
Emergency Phone Number: 815-895-5181  
Preparer's Name: NONE  
Proprietary Ind: Y  
Review Ind: Y  
Published: Y

=====

Contractor Summary

=====

Cage: 7R834  
Name: CHESAPEAKE ASSOC. ENT.  
Address: 22 NEWPORT DR  
City: FOREST HILL MD 21050  
Phone: 410-838-0260  
Cage: 30119  
Name: IDEAL INDUSTRIES INC  
Address: BECKER PL  
City: SYCAMORE IL 60178  
Phone: 815-895-5181  
Cag  
e: 79542  
Name: LAWRENCE F D ELECTRIC CO THE  
Address: 5739 WEBSTER ST  
City: DAYTON OH 45414  
Phone: 513-890-1059

=====

Item Description Information

=====

Item Manager: S9G  
Item Name: LUBRICANT,WIRE  
Specification Number: NONE  
Type/Grade/Class: NONE  
Unit of Issue: GL  
UI Container Qty: 0  
Type of Container: PAIL

=====

Ingredients

=====

=====

Name: \*\*\* PROPRIETARY \*\*\*

-----

=====

## Health Hazards Data

=====

LD50 LC50 Mixture: ORAL LD50 (RAT) IS UNKNOWN.

Route Of Entry Inds - Inhalation: NO

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: ACUTE: NONE NORMALLY EXPECTED. UPON PROLONGED CONTACT, MAY CAUSE TEMPORARY EYE DISCOMFORT. MICA, SODIUM HYDROXIDE, AND SODIUM NITRITE

MAY BE HAZARDOUS IN LARGE DOSES. CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation Of Carcinogenicity: NONE.

Signs And Symptoms Of Overexposure: EYES: IRRITATION.

Medical Cond Aggravated By Exposure: PERSONS WITH PRE-EXISTING CARDIOVASCULAR OR BONE MARROW DISEASE SHOULD NOT USE THIS PRODUCT.

First Aid: EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. SKIN: WASH AREA WITH SOAP AND WATER. INGESTION: ADMINISTER

WATER OR MILK. GET MEDICAL ATTENTION.

=====

## Handling and Disposal

=====

Spill Release Procedures: WIPE UP, SHOVEL OR VACUUM SPILLED MATERIAL. CLEAN UP SPILL IMMEDIATELY AS THEY CAN BE DANGEROUSLY SLIPPERY.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: COMPLY WITH FEDERAL, STATE, AND LOCAL REGULATIONS FOR SOLID LANDFILL.

Handling And Storage Precautions: STORE AT TEMPERATURES BETWEEN 40-120F. AVOID FREEZING.

Other Precautions: KEEP AWAY FROM CHILDREN, INFANTS, AND PETS.

=====

## Fire and Explosion Hazard Information

=====

Flash Point Method: COC

Flash Point Text: NONE

Lower Limits: NONE

Upper Limits: NONE

Extinguishing Media: USE EXTINGUISHING MEDIA SUITABLE FOR SURROUNDING MATERIAL.

Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS AND FUL

L

PROTECTIVE CLOTHING. KEEP FIRE EXPOSED CONTAINERS COOL WITH WATER.

Unusual Fire/Explosion Hazard: NONE

=====

### Control Measures

=====

Respiratory Protection: IF TLV EXCEEDED, USE NIOSH RESPIRATOR.

Ventilation: USE MECHANICAL(GENERAL) VENTILATION IN CLOSED AREAS AND LOCAL EXHAUST WHERE TLV IS EXCEEDED.

Protective Gloves: USE NEOPRENE GLOVES.

Eye Protection: WEAR SAFETY GLASSES OR SPLASH GOGGLE

S.

Other Protective Equipment: EYE WASH STATION IN WORK AREA IS RECOMMENDED.

Work Hygienic Practices: WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING.

Supplemental Safety and Health: NONE

=====

### Physical/Chemical Properties

=====

HCC: V6

B.P. Text: 212F,100C

M.P/F.P Text: UNKNOWN

Decomp Text: UNKNOWN

Vapor Pres: UNKNOWN

Vapor Density: UNKNOWN

Spec Gravity: 0.8

PH: 6.5-8

Evaporation R

ate & Reference: UNKNOWN

Solubility in Water: MODERATE

Appearance and Odor: TAN, FOAMY PASTE. MILD ODOR.

Percent Volatiles by Volume: <90

Corrosion Rate: UNKNOWN

=====

### Reactivity Data

=====

Stability Indicator: YES

Stability Condition To Avoid: STORE AWAY FROM HEAT AND DIRECT SUNLIGHT.

Materials To Avoid: STRONG OXIDIZING AGENTS AND STRONG ACIDS.

Hazardous Decomposition Products: EXCESSIVE

HEAT AND BURNING MAY RELEASE OXIDES  
OF CARBON AND NITROGEN.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: WILL NOT OCCUR.

=====

Toxicological Information

=====

=====

Ecological Information

=====

=====

MSDS Transport  
Information

=====

=====

Regulatory Information

=====

=====

Other Information

=====

=====

Transportation Information

=====

Responsible Party Cage:

30119

Trans ID NO: 86233

Product ID: WIRE LUBE WIRE PULLING LUBRICANT,ALL"31" SERIES

MSDS Prepared Date: 07/29/1993

Review Date: 09/28/1994

MFN: 1

Net Unit Weight: 6.7 LB/PAIL

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: GL

Container QTY: 0

Type Of Container: PAIL

Additional Data: CONTRACTORS 1 GALLON PAIL SHALL BE PACKAGED SIX PER  
COMPARTMENTIZED FIBERBOARD BOX. BOX SHALL CONFOR M TO PPP-B-636, STYLE AND  
CLASS CONTRACTORS OPTION. MARK CANS AND BOXES IAW MIL-STD-290. BAR CODE IAW  
MI

L-STD-129.

=====

Detail DOT Information

=====

DOT PSN Code: ZZZ  
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

Detail IMO Information

=====

IMO PSN Code: ZZZ  
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

=====

=====

Detail IATA Information

=====

IATA PSN Code: ZZZ  
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

Detail AFI Information

=====

AFI PSN Code: ZZZ  
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

HAZCOM Label

=====

=====

Product ID: WIRE LUBE WIRE PULLING LUBRICANT,ALL"31" SERIES  
Cage: 30119  
Company Name: IDEAL INDUSTRIES INC  
Street: BECKER PL  
City: SYCAMORE IL  
Zipcode: 60178  
Health Emergency Phone: 815-895-5181  
Label Required IND: Y  
Date Of Label Review: 09/28/1994  
Status Code: C  
Label Date: 09/28/1994  
Origination Code: F  
Eye Protection IND: YES  
Skin Protection IND: YES  
Signal Word: CAUTION  
Respiratory Protection IND: YES  
Health Hazard: Slight  
Contact Hazard: Slight  
Fire

Hazard: None

Reactivity Hazard: None

Hazard And Precautions: NO HEALTH HAZARDS NORMALLY EXPECTED. UPON PROLONGED CONTACT, MAY CAUSE TEMPORARY EYE DISCOMFORT. MICA, SODIUM HYDROXIDE, AND SODIUM NITRITE MAY BE HAZARDOUS IN LARGE DOSES. STORE AT TEMPERATURES BETWEEN 40-120F. AVOID FREEZING. FIRST AID: EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. SKIN: WASH AREA WITH SOAP AND WATER. INGESTION: ADMINISTER WATER OR MILK. GET MEDICAL ATTENTION. TARGET ORGANS: UNKNOWN.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.