

U.S. OIL COMPANY, INC. -- 240580 FUEL OIL 1 -- 9140-00-247-4366

=====
Product Identification
=====

Product ID:240580 FUEL OIL 1
MSDS Date:03/01/1987
FSC:9140
NIIN:00-247-4366
MSDS Number: BJVZK
=== Responsible Party ===
Company Name:U.S. OIL COMPANY, INC.
Address:425 S. WASHINGTON STREET
Box:25
City:COMBINED LOCKS
State:WI
ZIP:54113
Info Phone Num:(414) 739-6100
Emergency Phone Num:(414) 739-6100

CAGE:FO781
=== Contractor Identification ===
Company Name:U S OIL CO INC
Address:558 CARTER CT
Box:City:KIMBERLY
State:WI
ZIP:54136
Country:US
Phone:920-735-8287
CAGE:9V710
Company Name:U.S. OIL COMPANY, INC.
Address:425 S. WASHINGTON STREET
Box:25
City:COMBINED LOCKS
State:WI
ZIP:54113
Phone:920-735-8298
CAGE:FO781

=====
Composition/Information on Ingredients
=====

Ingred Name:KEROSENE
CAS:8008-20-6
RTECS #:OA5500000
Fraction by Wt: >95%
Other REC Limits:100 MG/CUM NIOSH
OS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: REDNESS/TEARING/BLURRED VISION.
SKIN: IRRITATION. INHALATION: NASAL/RESPIRATORY
IRRITATION/DIZZINESS/WEAK/FATIGUE/NAUSEA/HEADACHE/UNCONSCIOUS/ASPHY
XIATION/BREATHING DIFFICULTY. INGESTION: MOUTH, ESOPHAGUS, GI
IRRITATION/NAUSEA/VOMITING/DIARRHEA/AS
PIRATION INTO LUNGS CAUSING
CHEMICAL PNEUMONITIS/FATAL/LUNG DAMAGE.
Explanation of Carcinogenicity:LABORATORY TESTS IN ANIMALS HAVE BEEN
SHOWN TO PRODUCE CANCER.
Effects of Overexposure:EYE: IRRITATION. SKIN: DEFATTING/DERMATITIS.
INHALATION: NASAL/RESPIRATORY
IRRITATION/DIZZINESS/WEAK/FATIGUE/NAUSEA/HEADACHE/UNCONSCIOUSNESS/A
SPHYXIATION/BREATHING DIFFICULTY. INGESTION: MOUTH/ESOPHAG US/GI
IRRITATION/NAUSEA/VOMITING/DIARRHEA/ASPIRATION INTO LUNGS MAY CAUSE
CHEMICAL P
NEUMONITIS, FATAL, & LUNG DAMAGE.

=====
===== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF
WATER. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT,
ADMINISTER OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL
RESPIRATION. I NGESTION: DON'T INDUCE VOMITING. KEEP WARM/QUIET.
GIVE 2 GLASSES OF WATER. NEVER GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CA
SES.

=====
===== Fire Fighting Measures =====

Flash Point:120F
Lower Limits:1.1%
Extinguishing Media:REGULAR FOAM, CO2, OR DRY CHEMICAL
Fire Fighting Procedures:WEAR SCBA/FULL FACEPIECE OPERATED IN
PRESSURE-DEMAND/OTHER POSITIVE PRESSURE MODE. WATER/FOAM CAUSES
FROTHING, IF SPRAYED INTO CONTAINERS OF HOT BURNING LIQUID.
Unusual Fire/Explosion Hazard:VAPORS ARE >AIR & MAY TRAVEL ALONG GROUND
OR BE MOVED BY VENTILATION & IGNITED BY OTHER SOURCE OF IGNITION

HEAT, PILOT LIGHTS, & OTHER FLAMES. COMBUSTIBLE.

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE IGNITION SOURCES. ABSORB ON PAPER/VERMICULITE/FLOOR ABSORBENT/SAND/CLAY/EARTH/OTHER ABSORBENT & TRANSFER TO HOOD OR SHOVEL INTO CONTAINER. EVACUATE AREA. STOP AT SOURCE, PUMP TO SALVAGE TANK, & DIKE TO PREVENT SPREADING. WEAR PROTECTIVE EQUIP.

===== Handling and Storage =====

Handling and Storage Precautions: NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM, BECAUSE PRODUCT RESIDUES CAN IGNITE EXPLOSIVELY. Other Precautions: AVOID STRONG OXIDIZING AGENTS & CONTACT W/SKIN & EYES. DON'T TRANSFER TO UNLABELED CONTAINER. USE OR STORE W/ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. IMPLEMENT ENGINEERING/ADMINISTRATIVE CONTROLS TO REDUCE EXPOSURE. OSHA PERMITS OTHER NIOSH/MSHA RES PIRATORS UNDER SPECIFIC CONDITIONS. Ventilation: PROVIDE SUFFICIENT MECHANICAL/LOCAL EXHAUST VENTILATION TO KEEP