

DEXTER ADHESIVES AND STRUCTURAL MATERIALS -- EPK (EPS) 608 PART B -- 8040-01-065-9956
===== Product Identification =====

Product ID:EPK (EPS) 608 PART B
MSDS Date:01/15/1991
FSC:8040
NIIN:01-065-9956
Kit Part:Y
MSDS Number: BJZJL
=== Responsible Party ===
Company Name:DEXTER ADHESIVES AND STRUCTURAL MATERIALS
Address:ONE DEXTER DRIVE
City:SEABROOK
State:NH
ZIP:03874
Country:US
Info Phone Num:603-4
74-5541
Emergency Phone Num:800-424-9300(CHEMTREC)/603-474-5541
Preparer's Name:KEN DECOSTA
CAGE:33564
=== Contractor Identification ===
Company Name:DEXTER CORP THE HYSOL DIV
Address:1 DEXTER DR
Box:City:SEABROOK
State:NH
ZIP:03874
Country:US
Phone:603-474-5541/FAX: 603-474-5545
CAGE:1JB33
Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS
Address:2850 WILLOW PASS ROAD
Box:312
City:BAY POINT
State:CA
ZIP:94565-3299
Country:US
Phone:202-483-7616
CAGE:33564

===== Composition/Inf

ormation on Ingredients =====

Ingred Name:SILICA, AMORPHOUS (FILLER PARTICLES ARE THOROUGHLY WETTED
BY VEHICLE SO AIRBORNE EXPOSURE DOES NOT OCCUR UNLESS CURED *
CAS:112945-52-5
RTECS #:VV7310000
OSHA PEL:20 MPPCF

Ingred Name:*MATERIAL IS SUBSEQUENTLY GROUND, MACHINED OR SANDED.)

Ingred Name:ETHYLENE GLYCOL (SARA III)
CAS:107-21-1
RTECS #:KW2975000
OSHA PEL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:2,4,6-TRI(DIMETHYLAMINOMETHYL) PHENO
L
CAS:90-72-2
RTECS #:SN3500000

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:MAY CAUSE SKIN IRRITATION AND POSSIBLE
ALLERGIC REACTIONS. PROLONGED AND REPEATED CONTACT MAY CAUSE
SENSITIZATION WHICH WILL RESULT IN ALLERGIC REACTIONS.
Explanation of Carcinogenicity:N/K *FAILURE TO OBSERVE CAUTION MAY
RESULT IN EXCESSIVE HEAT BUILD-UP WITH THE RELEASE OF TOXIC GASES.
Effec
ts of Overexposure:SKIN/RASH IRRITATION.

===== First Aid Measures =====

First Aid:FLUSH SKIN AND EYE CONTACT WITH PLENTY OF WATER. WASH SKIN
THOROUGHLY WITH SOAP AND WATER, RUBBING ALCOHOL OR HAND CLEANER. DO
NOT USE SOLVENTS. REMOVE SOILED CLOTHING AND WASH BEFORE REUSE. IF
IRRITA TION PERSISTS, SEE PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:315F,157C
Extinguishing Media

:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, WATER
SPRAY, FOAM OR FOG.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN
FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE
LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP AND TRANSFER TO METAL CONTAINER.
WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT
FLAMMABILITY CAUTIONS, OR USE DETERG
ENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL
INSTRUCTIONS.

Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation:LOCAL EXHAUST RECOMMENDED, MECHANICAL ACCEPTABLE.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER

Eye Protection:SAFETY GLASSES OR GOGGL
ES

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres:1

Evaporation Rate & Reference: