View NSN Online: https://aerobasegroup.com/nsn/6850-00-965-2331

Product ID:OMEGA 1024 212-19 MSDS Date:04/01/1990 FSC:6850 NIIN:00-965-2331 MSDS Number: BKBFF === Responsible Party === Company Name: OMEGA CHEMICAL CORP Address:6935 WEST 62ND STREET City:CHICAGO State:IL ZIP:60638 Country:US Info Phone Num:312-586-8000 Emergency Phone Num:312-586-8000 **Preparer's Name** :PAUL ZALANTIS CAGE:OB5U9 === Contractor Identification === Company Name: OMEGA CHEMICAL CORD; SUCCESSOR TO MSCI CAGE:OB5U9 Company Name: OMEGA CHEMICAL PROD GP, FINE ORGANICS CORP Address:6935 WEST 62ND STREET City:CHICAGO State:IL ZIP:60638 Country:US Phone:312-586-8000, 800-424-9300 CAGE:0B5U9

Ingred Name:PETROLEUM HYDROCARBON CAS:64741-44-2 RTECS #:LX3296000 Other REC Limits:NONE SPECIFIED ACGIH TLV:100 PPM

Health Hazards Acute and Chronic:ACUTE: HIGH CONCENTRATIONS IRRITATING TO EYES AND RESPIRATORY TRACT. HEADACHES, DIZZINESS, NAUSEA. CHRONIC: MAY CAUSE LOSS OF CONSCIOUSNESS, BURNING TO EYES, SKIN IRRITATION. INGESTION MAY BE FATAL.

First Aid:WASH AREAS OF CONTACT WITH GENEROUS AMOUNTS OF WARM WATER AND MILD SOAP. FOR EYES FLUSH THOROUGHLY WITH WATER AND SE EK MEDICAL

ATTENTION IMMEDIATELY. IF INHALED, REMOVE FROM EXPOSURE AND SEEK MEDICAL ATTENTION IF NECESSARY. IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

Flash Point Method:TCC Flash Point:135F,57C Extinguishing Media:CO2, FOAM, DRY CHEMICAL. Fire Fighting Procedures:TREAT AS HYDROCARBON FIRE. Unusual Fire/Explosion Hazard:NONE.

Spill Release Procedures: IF OUTDOORS, ADD SAND, EARTH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. KEEP PRODUCT OUT OF SEWERS AND WATER COURSES BY DIKING OR IMPOUNDING. INSIDE SPILLAGE, ELIMINATE ALL IGNITION SOURCES AND REMOVE WITH ABSORBENT MATERIAL.

Handling and Storage Precautions:REASONABLE CARE AND PRECAUTIONS WHEN HANDLING THIS MATERIAL ARE STRONGLY REOMMENDED. Other Precautions:REMOVE AND LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:CARTRIDGE TYPE FOR SOLVENTS. Ventilation:MECHANICAL SHOULD BE SUFFICIENT TO REDUCE LEVELS BELOW TLV. Protective Gloves:NEOPRENE Eye Protection:FACESHIELD, SAFETY GOGGLES. Other Protective Equipment:APRON AND/OR SPLASH GUARD. Supplemental Safety and Health

HCC:F4 Boiling Pt:B.P. Text:250F,121C Me It/Freeze Pt:M.P/F.P Text:-20F,-29C Vapor Density:< 1 Spec Gravity:0.86 Evaporation Rate & amp; Reference:< 1 (WATER=1) Solubility in Water:MISCIBLE Appearance and Odor:AMBER LIQUID, SOLVENT ODOR Percent Volatiles by Volume:< 10

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:OPEN SPARKS AND FLAMES. Hazardous Decomposition Products:PARTIAL COMBUSTION MAY PRODUCE CARBON MONOXI DE.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. DISPOSAL RECOMMENDATIONS APPLY TO THE ORIGINAL MATERIAL AND ITS CONTAINER; NOT ANY MATERIALS WHICH ARE A WASTE BY-PRODUCT OF THE USERS' OPERATION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United Sta

tes of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.