

DEXTER CORP THE PACKAGING PRODUCTS DIV -- EPK 0151 PART B -- 8040-00-145-0043  
===== Product Identification =====

Product ID:EPK 0151 PART B

MSDS Date:07/11/1989

FSC:8040

NIIN:00-145-0043

Kit Part:Y

MSDS Number: BKJFX

=== Responsible Party ===

Company Name:DEXTER CORP THE PACKAGING PRODUCTS DIV

Address:1-7 EAST WATER STREET

City:WAUKEGAN

State:IL

ZIP:60085-5614

Country:US

Info Phone Num:708-623-

4200

Emergency Phone Num:708-623-4200

Preparer's Name:DR. SHELDON CLARK

CAGE:04347

=== Contractor Identification ===

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Phone:716-372-6300/6309

CAGE:04347

Company Name:DEXTER CORP THE HYSOL DIV

Address:1 DEXTER DR

Box:City:SEABROOK

State:NH

ZIP:03874

Country:US

Phone:603-474-5541/FAX: 603-474-5545

CAGE:1JB33

Company Name:THE ROBERT MCKEOWN CO INC

CAGE:ROBER

=====

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SILICA, AMORPHOUS (FILLER PARTICLES ARE THOROUGHLY WETTED BY VEHICLE SO AIRBORNE EXPOSURE DOES NOT OCCUR UNLESS CURED \*

CAS:112945-52-5

RTECS #:VV7310000

Other REC Limits:NONE SPECIFIED

OSHA PEL:20 MPPCF

Ingred Name:\*MATERIAL IS SUBSEQUENTLY GROUND, MACHINED OR SANDED.

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

Ingred Name:TRIETHYLENETETRAMINE

CAS:112-24-3

RTECS #:YE6650000

Other REC Limits:NONE SPECIFIED

==

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MATERIAL IS CORROSIVE TO SKIN. MAY CAUSE CHEMICAL BURNS TO SKIN AND EYES. REPEAT CONTACT MAY CAUSE SENSITIZATION.

Explanation of Carcinogenicity:N/K BONDED. FAILURE TO OBSERVE CAUTION MAY RESULT IN EXCESSIVE HEAT BUILD-UP WITH THE RELEASE OF TOXIC GASES.

Effects of Overexp

posure:SKIN RASH, IRRITATION; POSSIBLE BURNS.

=====  
First Aid Measures  
=====

First Aid:FLUSH SKIN AND EYE CONTACT WITH PLENTY OF WATER. WASH SKIN THOROUGHLY WITH SOAP AND WATER, RUBBING ALCOHOL OR HAND CLEANER. DO NOT USE SOLVENTS. REMOVE SOILED CLOTHING AND WASH BEFORE RE- USE. IF IRRITATION PERSISTS, SEE PHYSICIAN.

=====  
Fire Fighting Measures  
=====

Flash Point:265F,129C

Extinguishing Media:DRY CHEMICAL OR

HALON FIRE EXTINGUISHER, WATER  
SPRAY, FOAM OR FOG.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN  
FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE  
LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP AND TRANSFER TO METAL CONTAINER.  
WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT  
FLAMMABILITY CAUTIONS, OR USE DETERGENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL  
INSTRUCTIONS.

Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED WITH GOOD INDUSTRIAL VENTILATION;  
ORGANIC RESPIRATOR.

Ventilation:LOCAL EXHAUST RECOMMENDED, MECHANICAL ACCEPTABLE.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER.

Eye Protection:SAFETY GLASSE  
S OR GOGGLES.

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:B2

Boiling Pt:B.P. Text:531F,277C

Vapor Pres:1

Spec Gravity:0.98

Evaporation Rate & Reference: