View NSN Online: https://aerobasegroup.com/nsn/8030-00-709-3327

ZPG -- ZPG-1815 RUST PREVENTIVE -- 8030-00-709-3327

============= Product Identification ==============

Product ID:ZPG-1815 RUST PREVENTIVE

MSDS Date:02/26/1990

FSC:8030

NIIN:00-709-3327

MSDS Number: BKJNK === Responsible Party ===

Company Name: ZPG

Address:26500 CAPITOL AVE.

City:REDFORD

State:MI ZIP:48239 Country:US

Info Phone Num:313-937-0710

Emergency Phone Num:313-937-0710

Preparer's Name:DR. S. BEICOS

CAGE:K O638

=== Contractor Identification ===

Company Name: ZEP MANUFACTURING COMPANY Address: 1310 SEABOARD INDUSTRIAL BLVD NW

Box:2015 City:ATLANTA State:GA

ZIP:30318 Country:US

Phone:877-428-9937

CAGE:27674

Company Name: ZPG

Address:26500 CAPITOL AVE.

City:REDFORD

State:MI ZIP:48239 Country:US

Phone:313-937-0710

CAGE:KO638

====== Composition/Information on Ingredients ========

Ingred Name: MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000 Fraction by Wt: >1% Other REC Limits: NONE SPECIFIED OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3/10 STEL;9192 Ingred Name:PETROLEUM DISTILLATES CAS:8002-05-9 RTECS #:SE7449000 Fraction by Wt: >1% Other REC Limits: NONE SPECIFIED ACGIH TLV:100 PPM =========== Hazards Identification ========================== Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SYMPTOMS RANGE FROM MILD DEPRESSION TO CONVULSIONS AND LOSS OF CONSCIOUSNESS, SKIN CONTACT CAUSES IRRITATION, DEFATTIN G AND DERMATITIS. INHALATION SYMPTOMS AS ABOVE. Medical Cond Aggravated by Exposure: SKIN, LIVER, KIDNEY AND C.N.S. DISORDERS. First Aid: INHALATION: REMOVE TO FRESH AIR, GIVE OXYGEN, CONTACT PHYSICIAN. EYES: FLUSH WITH WATER, CONTACT PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHING, WASH WITH WATER. INGESTION: DO NOT INDUCE VOMITING, CONT ACT PHYSICIAN; GIVE WHITE MINERAL OIL. ====== Fire Fighting Measures ========== Flash Point:101F,38C Autoignition Temp: Autoignition Temp Text: 800 F Lower Limits:0.0 **Upper Limits:6.0** Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER. Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS. REMOVE ALL SOURCES OF IGNITION. Unusual Fire/Explosion Hazard:PETROLEUM DISTILLATES ARE A FIRE AND EXPLOSION HAZARD. VAPORS CAN FLOW TO DISTANT IGNITION SOURCES. ======== Accidental Release Measures =============

Spill R

elease Procedures:REMOVE SOURCES OF IGNITION, PROVIDE ADEQUATE VENTILATION, ABSORB WITH VERMICULITE OR OTHER ABSORBENT.
======================================
Handling and Storage Precautions:STORE IN COOL, WELL-VENTILATED AREA AWAY FROM SOURCES OF IGNITION. Other Precautions:PREVENT SKIN CONTACT AND AVOID BREATHING VAPORS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE AIR PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE AT A TLV. USE S.C.B.A. AT >10 TIMES THE TLV. Ventilation:LOCAL EXHAUST RECOMMENDED. MAINTAIN ADEQUATE TRANSFER VELOCITY TO PREVENT EXPLOS CONC. ELIMINATE IGNITION SOURCES. Protective Gloves:BUNA-N-RUBBER GLOVES Eye Protection:GOGGLES OR FACE SHIELDS RECOMMENDED. Other Protective Equipment:APRON. Supplemental Safety and Health
======== Physical/Chemical Properties =========
HCC:F4 Boiling Pt:B.P. Text:>350F,>177C Vapor Pres: