

FENWAL INC. -- TRU-BOND 214 PART A -- 8040-00-947-5483

=====
Product Identification
=====

Product ID:TRU-BOND 214 PART A

MSDS Date:08/01/1988

FSC:8040

NIIN:00-947-5483

Kit Part:Y

MSDS Number: BKJSD

=== Responsible Party ===

Company Name:FENWAL INC.

Address:400 MAIN ST.

City:ASHLAND

State:MA

ZIP:01721

Country:US

Info Phone Num:508-881-2000

Emergency Phone Num:508-881-2000

CAGE:0KDPZ

=== Contractor

Identification ===

Company Name:FENWAL INC.

Address:400 MAIN ST

City:ASHLAND

State:MA

ZIP:01721

Country:US

Phone:617-881-2000

CAGE:0KDPZ

Company Name:KIDDE FENWAL INC

Address:400 MAIN ST

Box:City:ASHLAND

State:MA

ZIP:01721-2150

Country:US

Phone:508-881-2000

CAGE:0KDP7

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL GLYCIDYL ETHER (BGE)

CAS:2426-08-6

RTECS #:TX4200000

Fraction by Wt: 2.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:50 PPM

ACGIH TLV:25 PPM;

9293

Ingred Name:EPICHLOROHYDRIN (SARA III)

CAS:106-89-8

RTECS #:TX4900000

Fraction by Wt: *

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 5 PPM

ACGIH TLV:S, 2 PPM; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:SILVER (SARA III)

CAS:7440-22-4

RTECS #:VW3500000

Fraction by Wt: 71%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.01 MG/M3

ACGIH TLV:0.1 MG/M3; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:PROPRIETARY ORGANIC SOLVENTS

Fraction by Wt: TRACE

Other REC Limits:NONE SPECIFIED

ED

OSHA PEL:145 PPM

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:PROLONGED OR REPEATED CONTACT CAN CAUSE MILD SKIN IRRITATION. MILDLY IRRITATING TO EYES. SILVER DUST IS NONTOXIC, BUT CAN LEAD TO LIFE LONG DISFIGUREMENT BY DEPOSITING SILVER UNDER SKIN (ON TISSUES), WHICH DARKENS UPON EXPOSURE TO LIGHT. PIGMENTATION MAY FORM IN THE LUNGS OF INDIVIDUALS WHO HAVE INHALED SILVER DUST.

=====
First Aid Measures
=====

First Aid:GET MEDICAL ATTENTION IMMEDIATELY. INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NECESSARY. SKIN: WASH WITH SOAP & WATER. GET MEDICAL HELP IF IRRITATION PERSISTS. EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP IF IRRITATION PERSISTS.

=====
Fire Fighting Measures
=====

Flash Point:>400F,>204C

Extinguishing Media:CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS

INED BREATHING APPARATUS.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS AND REMOVE. RESIDUAL CAN BE REMOVED WITH NONFLAMMABLE SOLVENT. INCINERATE IN ACCORDANCE WITH LOCAL POLLUTION REGULATIONS AND ORDINANCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED ORGANIC VAPOR RESPIRATOR.
Ventilation:LOCAL & MECHANICAL EXHAUST.
Protective Gloves:IMPERVIOUS GLOVES.
Eye Protection:SPLASH-PROOF GOGGLES.
Other Protective Equipment:SAFETY SHOWER AND EYE WASH FACILITIES.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity:APPROX. 7.8
Solubility in Water:NOT DETERMINED
Appearance and Odor:SILVER COLORED PASTE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXID; ACETYLENE; AMMONIA; ETHANOL; OXALIC, TARTARIC, NITRIC ACIDS; ETHYLENEIMINE; BROMOAZIDE; HYDROGEN PEROXIDE.
Stability Condition to Avoid:STORAGE AT ELEVATED TEMPERATURES OVER LONG PERIODS OF TIME.
Hazardous Decomposition Products:CO, CO2
Conditions to Avoid Polymerization:EXCESSIVE EXOTHERMS WHEN CURED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.