

WORLD AUTOMOTIVE TRANSPORT SUPPLIES INC -- LUBRICATING OIL -- 9150-00-261-8146

===== Product Identification =====

Product ID:LUBRICATING OIL

MSDS Date:05/03/1987

FSC:9150

NIIN:00-261-8146

MSDS Number: BKLPY

=== Responsible Party ===

Company Name:WORLD AUTOMOTIVE TRANSPORT SUPPLIES INC

Address:918 PARK AVE SUITE 101

City:PITTSBURGH

State:PA

ZIP:15234-2120

Country:US

Info Phone Num:412-343-1335

Eme

rgency Phone Num:412-343-1335

CAGE:1EV56

=== Contractor Identification ===

Company Name:WORLD AUTOMOTIVE TRANSPORT SUPPLIES INC

Address:918 PARK AVE SUITE 101

Box:City:PITTSBURGH

State:PA

ZIP:15234-2120

Country:US

Phone:412-343-1335

CAGE:1EV56

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTILLATE

Other REC Limits:5MG/CUM AS OILMIST

Ingred Name:OTHER COMPONENTS (NOT SPECIFIED)

Other REC Limits:NONE SPECIFIED

===== Hazards Identi

fication =====

Health Hazards Acute and Chronic:ACUTE: IRRITATION OF EYES, SKIN,
RESPIRATORY TRACT; REDNESS OR DRYING OF SKIN. CHRONIC: DERMATITIS.
Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE
MILD SKIN IRRITATION.
Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

===== First Aid Measures =====

First Aid:CONTACT-IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER. CALL A
PHYSICIAN. WASH SKIN WITH SOAP AND
WATER.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:320F/160C
Lower Limits:1
Upper Limits:6
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO CO NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:CARBON MONOXIDE, SULFUR OXIDES.

=====
==== Accidental Release Measures =====

Spill Release Procedures:TAKE UP WITH NONCOMBUSTIBLE ABSORBANT
MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED, HAND & STORE
IN WELL VENTILATED AREA AWAY FROM HEAT, FLAME & STRONG OXIDANTS.
Other Precautions:AVOID BRTHG OIL MIST. REMOVE OIL SOAKED CLOTHING &
LAUNDRER PRIOR TO RE-USE. WASH SKIN THOROUGHLY WITH SOAP & WATER
AFTER HANDLING.

=

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR OIL
MIST/VAPOR IF ABOVE TLV/PEL OR SCBA IN AN ENCLOSED AREA.

Ventilation:LOCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES.

Protective Gloves:RUBBER

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING, EYE-WASH
FOUNTAIN.

Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYES. WASH
THOROUGHLY AFTER USE. DO NOT USE CONTAMIN
ATED CLOTHES.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:540F/282C

Vapor Pres:11

Spec Gravity:0.9

Evaporation Rate & Reference: