

PRATT AND LAMBERT INC -- LAC ACR RED 11136 ID794104 -- 8010-00-935-7063

=====
Product Identification
=====

Product ID:LAC ACR RED 11136 ID794104
MSDS Date:12/11/1990
FSC:8010
NIIN:00-935-7063
MSDS Number: BKSVC
=== Responsible Party ===
Company Name:PRATT AND LAMBERT INC
Address:16116 E 13TH ST
Box:2153
City:WICHITA
State:KS
ZIP:67201
Country:US
Info Phone Num:316-733-1361
Emergency Phone Num:873
-6000 DOT EMER 8002553924
Preparer's Name:W. A. ELLISON
CAGE:61196

=== Contractor Identification ===
Company Name:PRATT AND LAMBERT INC
Box:6027
City:CLEVELAND
State:OH
ZIP:44101-1027
Country:US
Phone:216-566-2902
CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:CYCLOHEXANONE (SARA III)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 20%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000

LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL BENZYL PHTHALATE (SARA III)

CAS:85-68-7

RTECS #:TH9990000

Fraction by Wt: < 5%

Other REC Limits:NONE SPECIFIED

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ing

red Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:LEAD CHROMATE (SARA 313)
CAS:7758-97-6
RTECS #:GB2975000
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:.05MG/M3/.1MG/M3CEIL
ACGIH TLV:0.0500 MG/M3

Ingred Name:VOC: 5.19 LB/GL LESS WATER & NPRS*; 623 G/L LESS WATER;
CALCULATED
*NEGLIGIBLY PHOTOCHEMICALLY REACTIVE MATERIALS
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 18.90 LB/GAL SOLIDS; 2268 G/L SOLIDS; CALCULATED
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:IRRITATION (GASTROINTEST, NOSE,
THROAT, EYE, SKIN). ASPIRATION
TO LUNGS: CHEMICAL PNEUMONITIS-CAN
BE FATAL. CENTRAL NERVOUS SYS DEPRESSION. SKIN: DEFATTING.
OVEREXPOS: LUNG CANCER. LIVER DAMAGE. SEVER E DAMAGE: BLOOD
FORMING, NERVOUS, URINARY & REPRODUCTIVE SYS. PERIPHERAL
NEUROPATHY. PERM BRAIN & NERVOUS SYS DAMAGE.
Explanation of Carcinogenicity:CHROMIUM & CERTAIN CHROMIUM COMPOUNDS,
LEAD CHROMATE, DI(2-ETHYLHEXYL)PHTHALATE, ARE LISTED AS
CARCINOGENS.
Effects of Overexposure:INGEST: NAUSEA/VOMITING. INHALE: HEADACHES,
DIZZINES

S, NAUSEA, CONFUSION. CHRONIC OVEREXPOSURE: NO APPETITE, METALLIC TASTE IN MOUTH, ANXIETY, CONSTIPATION, NAUSEA, WEAKNESS, INSOMNIA, HEADACHE, MUSCLE/JOINT PAIN, FINE TREMORS, NUMBNESS, DIZZINESS, HYPERACTIVITY & COLIC. METAL FUME FEVER:FLU-LIKE, FEVER, CHILLS, COUGH.

Medical Cond Aggravated by Exposure:PRE-EXISTING KIDNEY CONDITIONS MAY BE AGGRAVATED BY EXPOSURES TO LEAD. OVEREXPOS TO SOLVENTS ARE ASSOCIATED W/ PERMANENT BRAIN AND NERVE SYS DAMAGE. LAB STUDIES W/RAT

S INDICATE MIBK DAMAGE THE KIDNEYS

=====
===== First Aid Measures =====

First Aid:INGEST: DO NOT INDUCE VOMITING. CALL POISON CONTROL, EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY. INHALE: REMOVE TO FRESH AIR IMMEDIATELY. GIVE ARTIFICIAL RESPIRATION IF NEEDED. KEEP WARM & QUIET. GET IMMEDIATE MEDICAL AID. EYE: FLUSH THOROUGHLY WITH LARGE AMOUNTS OF WATER FOR 15 MIN. GET MEDICAL AID. SKIN: REMOVE CONTAMINATED CLOTHES WASH AFFECTED AREA WITH SOAP & WATER.
PERSISTANT IRRIT/MEDICAL AID.

=====
===== Fire Fighting Measures =====

Flash Point:1F,-17C

Lower Limits:.3

Upper Limits:13.0

Extinguishing Media:USE NFPA CLASS B(CO2, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM) FOR LIQUID FIRES. POLYMER FOAM PREFERRED FOR LARGE FIRES

Fire Fighting Procedures:USE SCBA. WATER MAY BE INEFFECTIVE, USE TO COOL CNTNRS(FOG NOZZLE PREFERABLE) TO PREVENT PRESSURE BUILD-UP&AUTO- IGNITION/EXPLOSION WHEN EXPOSED TO EXTREME HEAT

Unusual Fire/Explosion Hazard:EMERGENCY CONDITIONS:OVEREXPOSURE TO DECOMP PRODUCTS MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MEDICAL AID. VAPORS MAY CAUSE FLASH FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE IGNITION SOURCES. DIKE AND CONTAIN. REMOVE WITH INERT MATERIAL (SAND, EARTH, ETC). USE COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL. USE NON-SPARKING

TOOLS. PREVENT CONTAMINATION OF SEWERS, STREAMS AND GROUNDWATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. LARGE QUANTITY STORAGE: COMPLY WITH OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CONTAINERS CLOSED AFTER USE.

Other Precautions:DO NOT REUSE CONTAINERS FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:RESTRICTED AREA: NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR. SPRAYING:MECHANICAL PREFILTER MAY BE REQUIRED. CONFINED AREAS: NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR. EXCEEDED TLV AREA: NIOSH/MSHA APPROVED RESPIRATOR WITH PROTECT FACTOR.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME & PATTERN

DO NOT KEEP CONCENTRATIONS BELOW EXPOSURE LIMITS.

Protective Gloves:REPEAT/PROLONG USE: IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES

Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT, SEE OSHA STANDARDS FOR LEAD.

Work Hygienic Practices:DO NOT BREATHE SANDING DUST. WASH HANDS AND FACE BEFORE EATING OR DRINKING.

Supplemental Safety and Health

HAZARDOUS/TOXIC, POSSIBLE HAZARDOUS/TOXIC INGREDIENTS/WASTE. REFER TO OSHA 29CFR1910 FOR SAFETY/PROTECTIVE REQUIREMENTS. WE

LDING, BRAZING

OR TORCH CUTTING MATERIALS COATED WITH THIS PRODUCT MAY PRODUCE METAL OXIDES.

=====
Physical/Chemical Properties
=====

HCC:F2

Boiling Pt:B.P. Text:133 TO 314F

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Density:> AIR

Spec Gravity:1.0

pH:NA

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Solubility in Water:NA

Appearance and Odor:PAINT

Percent Volatiles by Volume:72

=====
Stability and Reactivity Data
=====

Stab

ility Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: AVOID HIGH TEMP->100F & IGNITION SOURCES.

Hazardous Decomposition Products: BURNING (INCL WELD/CUT) PRODUCES SMOKE, CARBON MONOXIDE, CARBON DIOXIDE. OXIDES: CHROMIUM AND LEAD MAY BE GENERATED.

===== Disposal Considerations =====

Waste Disposal Methods: FOLLOW FEDERAL, STATE & LOCAL REGULATIONS & LAWS. INCINERATE IN EPA PERMITTED FACILITY. DO NOT INCINERATE

CLOSED CONTAINERS. USE PRECAUTIONS FOR DISPOSAL OF HAZARDOUS/TOXIC MATERIALS-D001/D008. USE HAZARDOUS WASTE LANDFILL FOR USED ABSORBENTS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing thi

s

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.