

ASPEN PAINTS -- STAIN, OIL TYPE, WOOD INTERIOR, WALNUT -- 8010-00-597-8225

=====
Product Identification
=====

Product ID:STAIN, OIL TYPE, WOOD INTERIOR, WALNUT

MSDS Date:09/01/1991

FSC:8010

NIIN:00-597-8225

MSDS Number: BKZZM

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 S.W. SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603 (M-F, 8:30-5:00)

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:D. KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

Company Name:ASPEN PAINTS/ASAMIPEN AMERICA INC

Address:1128 SPOKANE STREET

Box:City:SEATTLE

State:WA

ZIP:98134-1187

Country:US

Phone:303-573-1014(MED ONLY)

CAGE:0AL09

=====
Composition/Information on Ingredients
=====

Ingred Nam

e:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

=====
===== Hazards Identification =====

LD50 LC50 Mixture:SEE INGREDIENTS
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: NASAL & RESPIRATORY
IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE,
POSSIBL
E UNCONSCIOUSNESS, ASPHYXIATION. MAY BE HARMFUL OR FATAL.
SKIN: PROLONGED & REPEATED CONTACT W/SKIN C AN CAUSE DEFATTING &
DRYING OF SKIN RESULTING IN IRRITATION & DERMATITIS. EYE: SEVERE
IRRITATION, REDNESS, TEARING *
Effects of Overexposure:* & BLURRED VISION. INGESTION: CAN CAUSE
GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA.
ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS
WHICH CAN BE FATAL. REPORTS HAVE ASS OCIATED REPEATED & PROLONGED
OCCUPATIONAL OVEREXPOSURE TO SOLVENT W/PERMANENT BRAIN & NERVOUS
SYSTEM DAMAGE.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM FROM FURTHER EXPOSURE & RESTORE
BREATHING IF REQUIRED. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES
WHILD HOLDING EYELIDS OPEN. SKIN: WASH CONTAMINATED SKIN W/MILD
SOAP & WATER . INGESTION: DO NOT INDUCE VOMITING. OBTAIN MEDICAL
ATTENTION IMMEDIATELY.

=====
===== Fire Fighting Meas
ures =====

Flash Point Method:TCC
Flash Point:112F,44C
Lower Limits:0.8
Upper Limits:5.0
Extinguishing Media:DRY CHEMICAL, CO2, FOAM AND WATER FOG.
Fire Fighting Procedures:DO NOT ENTER CONFINED FIRE SPACE W/O ADEQUATE
PROTECT CLOTH & APPROVED POSITIVE PRESS SCBA. EXCLUDE AIR. USE
WATER ONLY AS FOG. COOL FIRE EXPOSED CNTNR W/WATER.
Unusual Fire/Explosion Hazard:AVOID EXCESSIVE HEAT, OPEN FLAMES & ALL
IGNITION SOURCES.

=====
===== Accidental Release Measures

=====
Spill Release Procedures:REMOVE IGNITION SOURCES. VENT AREA. ABSORB
SPILL W/ABSORB MAT'L & PLACE IN CLOSED CNTNR. LARGE SPILL-DIKE AREA
TO PREVENT MAT'L FROM ENTERING WATER SYSTEMS. WEAR PROTECT
EQUIPMENT DURING CLEANUP. NOTI FY PROPER AUTHORITIES IF SPILL
EXCEEDS 220 LBS.

=====
Handling and Storage

Handling and Storage Precautions:COMBUSTIBLE LIQUID. STORE IN A COOL,
DRY, WELL-VENTILATED AREA, AWAY FROM HEAT &
IGNITION SOURCES. AVOID
PROLONGED OR REPEATED CONTACT W/SKIN.

Other Precautions:AVOID BREATHING SPRAY/MIST. LAUNDRER CONTAM CLOTHING
PRIOR TO REUSE. GROUND CONTAINERS WHEN POURING. LIMIT FREE FALL TO
MINIMIZE STATIC CHARGE BUILD-UP. EMPTY CONTAINERS MAY BE HZDS FROM
PRODUCT RESIDU E & VAPORS & ALL CAUTIONS APPLY TO THEM.

=====
Exposure Controls/Personal Protection

Respiratory Protection:A CANISTER-TYPE RESPIRATOR MUST BE WORN TO
PREVENT THE INHALATION
OF VAPORS OR SPRAY MISTS WHEN THE TLV/PEL IS
EXCEEDED.

Ventilation:GENERAL VENT IS REQUIRED DURING NORMAL USE. LOCAL VENT MAY
BE REQUIRED IN CERTAIN CASES TO KEEP EXPOS LEVEL BELOW LIMIT.

Protective Gloves:CHEM-RESIST NITRILE, NEOPRENE OR RUBBER.

Eye Protection:WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN
CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:USE GOOD PERSONAL HYGIENE.

Supplem

ental Safety and Health

DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM
CHILDREN.

=====
Physical/Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:301 TO 402F

Vapor Pres:>7.0 @ 38C

Vapor Density:4.8

Spec Gravity:0.87

Viscosity:10"-25"

Evaporation Rate & Reference:SLOWER THAN BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:THIN LIQUID, MILD ODOR.

Percent Volatiles by Volume:65-69

=====
Stability and Re

activity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE ARE PRODUCED ON COMBUSTION.

Conditions to Avoid Polymerization: AVOID EXCESSIVE HEAT, OPEN FLAME AND ALL IGNITION SOURCES.

===== Disposal Considerations =====

Waste Disposal Methods: TREAT AS HAZARDOUS WASTE IF NOT POSSIBLE TO RECLAIM. DISPOSE

OF AT A LICENSED WASTE DISPOSAL COMPANY OR

INCINERATE W/APPROVAL OF ENVIRONMENTAL AUTHORITY. ALL DISPOSAL PROCEDURES MUST COMPLY W/LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any

person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.