

DAVIS HOWLAND OIL CO. -- VM & P NAPHTHA -- 6810-00-244-7637

===== Product Identification =====

Product ID:VM & P NAPHTHA

MSDS Date:03/04/1986

FSC:6810

NIIN:00-244-7637

MSDS Number: BLCYQ

=== Responsible Party ===

Company Name:DAVIS HOWLAND OIL CO.

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Info Phone Num:716-473-6650

Emergency Phone Num:716-473-6650

Preparer's Name:DO

D-HMIS (DGSC-SSH)

CAGE:5A565

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA, LIGHT ALIPHATIC

CAS:64742-89-8

Fraction by Wt: 100.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:300 PPM

===== Hazards Identification =====

Routes of Entr

y: Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: ACUTE: MODERATE TO SEVERE IRRITATION OF EYES, SKIN, RESPIRATORY OR G.I. TRACTS; CNS EFFECTS LIKE HEADACHE, DIZZINESS, NAUSEA AND VOMITING. REDNESS OR BURNS OF EYES/SKIN POSSIBLE. CHRONIC: DRYING OF SKIN, DEFATTING OR DERMATITIS, DAMAGE TO LUNGS, EYES, LIVER OR KIDNEYS. .
Explanation of Carcinogenicity: DATA PER MSDS
Effects of Overexposure: MAY CAUSE IRRITATION OF EYES, SKIN, RESPIRATORY OR G.I. TRACTS; MAY CAUSE HEADACHE, DIZZINESS, NAUSEA, VOMITING OR GI TRACT DISTURBANCES POSSIBLE. BURNS OR REDNESS OF EYES/CRACKING OR DRYNESS OF SKIN.
Medical Cond Aggravated by Exposure: PERSONS WITH A HISTORY OF AILMENTS

===== First Aid Measures =====

First Aid: INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.
SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION: DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method: TCC
Flash Point: =10.C, 50.F
Lower Limits: 0.9
Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.
Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures: USE PROPER PERSONAL PROTECTION; REMOVE ALL IGNITION SOURCES. CONTAIN FREE MATERIAL IF POSSIBLE; USE SUITABLE INERT ABSORBENT MATERIAL

L AND RECOVER FOR PROPER DISPOSAL IN AN
APPROVED CONTAINER.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED
AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT
CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID
PROLONG OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES.
USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR AS REQUIRED
IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER,WORK
CLOTHING AND APRON AS REQUIRED.

Work

Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

MSDS PROVIDED PER REQUEST. DAVIS HOWLAND COULD NOT BE IDENTIFIED AS A
VENDOR, AND COULD NOT IDENTIFY THE PRODUCT. THUS MSDS COPIED FROM
ANOTHER NSN OF THIS SAME SPECIFICATION, TYPE, AND GRADE.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt.=115.6C, 240.F

Vapor Pressure:15

Vapor

Density:3.8

Spec Gravity:0.727-0.750

Evaporation Rate & Reference:9.2(ETHER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:ALIPHATIC HYDROCARBONS

Percent Volatiles by Volume:100.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:EXTREMELY HIGH TEMPERATURES

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND
OTHER UNIDENTIFIED COMPONENTS.

=====

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES.DISPOSAL MUST BE MADE
IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
d
isclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.