

SOUTH COAST TERMINALS INC -- SCT 9000H, FN202, L-9000-1 -- 9150-00-181-8097

=====  
Product Identification  
=====

Product ID:SCT 9000H, FN202, L-9000-1  
MSDS Date:03/25/1992  
FSC:9150  
NIIN:00-181-8097  
MSDS Number: BLFDQ  
=== Responsible Party ===  
Company Name:SOUTH COAST TERMINALS INC  
Address:7401 WALLISVILLE RD  
Box:15535  
City:HOUSTON  
State:TX  
ZIP:77020-3555  
Country:US  
Info Phone Num:713-672-2401, EXT  
301  
Emergency Phone Num:CHEMTREC: 800-424-9300  
CAGE:1L506  
=== Contractor Identification ===  
Company Name:SOUTH COAST TERMINALS, INC  
Address:7401 WALLISVILLE ROAD  
Box:15535  
City:HOUSTON  
State:TX  
ZIP:77020  
Country:US  
Phone:713-672-2401/800-424-9300(CHEMTREC)  
CAGE:1L506

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LUBRICATING OIL BASE STOCK  
Fraction by Wt: 80-90%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:5 MG/M3 OIL MIST  
ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:Z

INC DIALKYL DITHIOPHOSPHATE  
CAS:68457-79-4  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:ACCIDENTAL INGESTION OF THIS MATERIAL  
MAY CAUSE IRRITATION OF G/I TRACT. THIS MATERIAL MAY CAUSE EYE  
IRRITATION. THIS MATERIAL MAY CAUSE SKIN IRRITATION. EXPOSURE TO  
HEATED MIST OR VAPORS MAY CAUSE NOSE AND THROAT IRRITATION.

Explanation of Carcinogen

icity:MFR SAID "NOT APPLICABLE" IN ALL  
CARCINOGEN FIELDS.

Effects of Overexposure:ORAL: G/I IRRITATION. EYE: BURNING,TEARING,  
REDNESS. SKIN: PROLONGED OR REPEATED CONTACT MAY CAUSE BURNING,  
REDNESS, DERMATITIS. INHALATION: IRRITATION OF NOSE AND THROAT.

Medical Cond Aggravated by Exposure:SUPPLIER DID NOT ADDRESS THIS  
FIELD.

=====  
===== First Aid Measures =====

First Aid:IF INGESTED,DO NOT INDUCE VOMITING; CALL A PHYSICIAN. FOR  
DIRECT CONT

ACT,FLUSH EYE WITH CLEAN WATER. WASH SKIN WITH SOAP AND  
WATER. REMOVE CONTAMINATED CLOTHING. (LAUNDER BEFORE REUSE.) IF  
IRRITATION OF NOSE AND THROAT DEVELOP, MOVE AWAY FROM SOURCE OF  
EXPOSURE. MEDICAL OPINION IS DIVIDED FOR LARGE INGESTIONS. EMESIS  
OR LAVAGE IS RECOMMENDED FOR PETROLEUM PRODUCTS WITH HIGH TOXICITY.  
SEE SUPP DAT

=====  
===== Fire Fighting Measures =====

Flash Point:>392F,>200C

Extinguishing Media:EXTINGUISH WITH DRY CHEMICAL, CO\*2  
, WATER SPRAY,

FOAM AND SAND OR EARTH. WATER AND FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:RESPIRATORY PROTECTION AND EYE PROTECTION  
REQUIRED FOR FIRE FIGHTING PERSONNEL.

Unusual Fire/Explosion Hazard:NONE

=====  
===== Accidental Release Measures =====

Spill Release Procedures:TREAT AS OIL SPILL. CONTAIN AND REMOVE BY  
MECHANICAL MEANS.

Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

=====  
===== Handling and Storage =====

=====

Handling and Storage Precautions:SUPPLIER DID NOT ADDRESS THIS FIELD.  
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED.  
Ventilation:IF CURRENT VENTILATION DOES NOT MAINTAIN AIRBORNE  
CONCENTRATIONS BELOW ESTABLISHED EXPOSURE LIMITS, USE MECHANICAL  
VENT.  
Protective Gloves:CHEMICAL RESISTANT  
Eye Protection:SAFETY OR SPLASH GOGGLES  
Other Protective Equipment:NONE  
Work Hygienic Practices:SUPPLIER  
DID NOT ADDRESS THIS FIELD.  
Supplemental Safety and Health  
FIRST AID: IF ANY IRRITATION PERSISTS OR IS SEVERE, SEE A DOCTOR.

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:>500F,>260C  
Vapor Pres:1  
Spec Gravity:0.875  
pH:NEUTRL  
Evaporation Rate & Reference: