

NATIONAL REFRIGERANTS, INC -- NATIONAL REFRIGERANT II -- 6830-00-281-3036

=====
Product Identification
=====

Product ID:NATIONAL REFRIGERANT II
MSDS Date:06/01/1988
FSC:6830
NIIN:00-281-3036
MSDS Number: BLKXR
=== Responsible Party ===
Company Name:NATIONAL REFRIGERANTS, INC
Address:11401 ROOSEVELT BLVD.
City:PHILADELPHIA
State:PA
ZIP:19154
Country:US
Info Phone Num:609-455-4555
Emergency Phone Nu
m:609-455-4555/800-424-9300 CHEMTREC
Preparer's Name:T. NAPRAVA
CAGE:4J994
=== Contractor Identification ===
Company Name:NATIONAL REFRIGERANTS INC
Address:661 KENYON AVE
Box:City:BRIDGETON
State:NJ
ZIP:08302
Country:US
Phone:800-262-0012/215-698-6620
CAGE:4J994

=====
Composition/Information on Ingredients
=====

Ingred Name:TRICHLOROFLUOROMETHANE (CFC-11) (SARA III)
CAS:75-69-4
RTECS #:PB6125000
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000 PPM
ACGIH TLV:C, 1000 PPM; 9293
E

PA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ozone Depleting Chemical:1

===== Hazards Identification =====

LD50 LC50 Mixture:ORL:>3725MG/KG-RAT;LC50 RAT 26200PPM/4HR
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: VAPOR IS HEAVIER THAN AIR
AND CAN CAUSE SUFFOCATION BY REDUCING OXYGEN AVAILABLE FOR
BREATHING. BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE
AUSE
LIGHT-HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, & MAY LEAD TO
NARCOSIS, CARDIAC IRREGULARITIES, UNCONSCIOUSNESS OR DEATH. SKIN:
NOT A CORROSIVE OR IRRITANT;
Effects of Overexposure:HOWEVER, REPEATED OR PROLONGED LIQUID CONTACT
CAN CAUSE DEFATTING OF SKIN.
Medical Cond Aggravated by Exposure:SKIN DISEASE: PRODUCT CAN DISSOLVE
THE NATURAL OIL OF THE SKIN, THEREFORE DERMATITIS MAY BE EXPECTED
TO RESULT FROM REPEATED CONTACT. PRE-EXISTING SKIN DISORDERS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR, CALL PHYSICIAN. IF NOT
BREATHING, GIVE CPR, PREFERABLY MOUTH-TO-MOUTH. IF BREATHING IS
DIFFICULT, GIVE OXYGEN. DO NOT GIVE EPINEPHRINE OR SIMILAR DRUGS.
EYE: IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES W/PLENTY OF WATER
FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN. SKIN: CLEANSE AFTER USE.

===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:NONE
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS MAY BE
REQUIRED IF DRUMS RUPTURE AND CONTENTS ARE SPILLED UNDER FIRE
CONDITIONS.
Unusual Fire/Explosion Hazard:DRUMS MAY RUPTURE UNDER FIRE CONDITIONS.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. DO NOT FLUSH INTO SEWERS. DIKE
SPILL. COLLECT ON ABSORBENT MATERIAL & TRANSFER TO STEEL DRUMS FOR
RECOVERY OR DISPOSAL. COMPLY W/FEDERAL, STATE A

ND LOCAL REGULATIONS
OR REPORTING RELEASES.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A CLEAN, DRY AREA. DO NOT
HEAT ABOVE 125 F.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:UNDER NORMAL MANUFACTURING CONDITIONS, NO
RESPIRATORY PROTECTION IS REQUIRED WHEN USING THIS PRODUCT.
SELF-CONTAINED BREATHING APPARATUS (SCBA) IS REQUIRED IF A SPILL
OCCURS.

Ventilation

:NORMAL VENT IS GENERALLY ADEQUATE. USE LOCAL EXHAUST WHEN
LARGE AMTS RELEASED. USE MECHANICAL VENT IN LOW PLACES.

Protective Gloves:BUTYL GLOVES.

Eye Protection:CHEMICAL SPLASH GOGGLES

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:G3

Boiling Pt:B.P. Text:75.0F,23.9C

Vapor Pres:.7PSIG@77F

Vapor Density:4.9

pH:NEUTRL

Evaporation Rate & Reference:0.1 (CC14=1)

Solubility in Water:0.1% BY WT @ 77 F

Appearance and Odor:COLORLESS LIQU

ID; SLIGHT ETHERAL ODOR.

Percent Volatiles by Volume:100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

ALKALI OR ALKALINE EARTH METALS - POWDERED AL, ZN, BE, ETC.

Stability Condition to Avoid:AVOID OPEN FLAMES AND HIGH TEMPERATURES.

Hazardous Decomposition Products:HIGH TEMPS (OPEN FLAMES, GLOWING
SURFACES, ETC.) FORMING HYDROCHLORIC & HYDROFLUORIC ACIDS-POSSIBLE
CARBONYL HALIDES.

=====
Disposal Considera
=====

tions =====

Waste Disposal Methods:EPA HAZARDOUS WASTE NO. U121; F001; F002. COMPLY WITH FEDERAL, STATE AND LOCAL REGULATIONS. RECLAIM BY DISTILLATION OR REMOVE TO A PERMITTED WASTE DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.