

OCTAGON PROCESS INC. -- SILICONE BRAKE FLUID (DOT 5) -- 9150-01-102-9455

=====
Product Identification
=====

Product ID:SILICONE BRAKE FLUID (DOT 5)

MSDS Date:09/20/1991

FSC:9150

NIIN:01-102-9455

MSDS Number: BLLXG

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-945-9400

Emergency Phone Num:201-

945-9400, CHEMTREC:800-424-9300

CAGE:82925

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYDIMEHTYLSILOXANE

CAS:63148-62-9

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports o

f Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE:MILD IRRITATION. SKIN:MILD IRRITATION. INHALATION:IRRITATION OF MUCUS MEMBRANES AND RESPIRATORY TRACT. INGESTION:NAUSEA AND IRRITATION TO GASTROINTESTINAL TRACT. CHRONIC:CHEMICAL CONJUNCTIVITIS AND DERMATITIS.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:MILD EYE & SKIN IRRITATION., NAUSEA AND VOMITING.

Medical Cond Aggravated by Exposure:NONE KNOWN.

=====
===== First Aid Measures =====

First Aid:INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP & WATER. REMOVE AND LAUNDRER CONTAMINATED CLOTHING. EYE: FLUSH WITH PLENTY OF WATER FOR ATLEAST 15 MINUTES. GET MEDICAL AT TENTION. INHALATION: REMOVE TO FRESH AIR.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:218

F,103C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL. PROTECT FROM I GNITION. ABSORB

WITH SAND OR INERT MATERIAL. SWEEP OR SCOOP UP AND TRANSFER TO DISPOSAL DRUM.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM SPARKS AND OPEN FLAMES.

Other Precautions:DO NOT GET IN EYES, OR ON CLOTHING. KEEP AWAY FROM SPARKS AND OPEN FLAMES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:USE WI

TH ADEQUATE VENTILATION.

Protective Gloves:NEOPRENE/BUTYL RUBBER/POLYETHYLENE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EMERGENCY SHOWER AND EYE WASH STATION.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:482F,250C

Vapor Pres:1

Spec Gravity:0.967

Evaporation Rate & Reference: