

DAVIS HOWLAND OIL CORP. -- VVD-1078-40000 CST -- 9150-00-864-4973

===== Product Identification =====

Product ID:VVD-1078-40000 CST

MSDS Date:01/01/1987

FSC:9150

NIIN:00-864-4973

MSDS Number: BLWCC

=== Responsible Party ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Info Phone Num:716-473-6650

Emergency Phone Num:716-473-6650

Prepare

r's Name:DOD-HMIS (DGSC-SSH)

CAGE:5A565

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

===== Composition/Information on Ingredients =====

Ingred Name:"NOT HAZARDOUS"

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 ORAL (RAT) IS 20,000 MG/KG

Routes of Entry

: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and
Chronic:ACUTE-EYE/SKIN/INHALATION/INGESTION:UNKNOWN.
CHRONIC-UNKNOWN.
Effects of Overexposure:SEE HEALTH HAZARDS SECTION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:CALL A PHYSICIAN.INHALATION: REMOVE TO FRESH AIR.EYE:
IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT
LEAST 15 MINUTES.
SKIN:WASH WITH SOAP AND WATER.INGESTION:CALL PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC
Flash Point:>400F,>204C
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, SAND OR EARTH
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL
FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

=====
Accidental Release Measures =
=====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL
AND PUT IN A CONTAINER FOR DISPOSAL.
Neutralizing Agent:NONE GIVEN.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORAGE-KEEP CONTAINER CLOSED WHEN NOT
IN USE.
Other Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Ventilation:LOCAL EXHAUST
Protective Gloves:RUBBER
Eye Protection:SAFETY GLASSES - GOGGLES -

FACE SHIELD

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING, AND BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS COPIED FROM ANOTHER OF SAME SUPPLIER, SAME MATERIAL.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:NEGLIGIBLE

Spec Gravity:0.97

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in Water:

INSOLUBLE

Appearance and Odor:CLEAR LIQUID-ODORLESS

Percent Volatiles by Volume: