

DEXSIL CHEMICAL CORP -- CLOR-D-TECT 1000; AMPULE 4 (RED-GREEN)

=====  
MSDS Safety Information  
=====

FSC: 6850  
NIIN: 01-316-9398  
MSDS Date: 05/17/1995  
MSDS Num: BMHBH  
Product ID: CLOR-D-TECT 1000; AMPULE 4 (RED-GREEN)  
MFN: 04  
Kit Part: Y  
Responsible Party  
Cage: 65297  
Name: DEXSIL CHEMICAL CORP  
Address: 1 HAMDEN PARK DR  
IVE  
City: HAMDEN CT 06514-3150  
Info Phone Number: 203-288-3509  
Emergency Phone Number: 203-288-3509, CHEMTREC 800-424-9300  
Preparer's Name: UNKNOWN  
Proprietary Ind: Y  
Review Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: 65297  
Name: DEXSIL CORP  
Address: 1 HAMDEN PARK DR  
City: HAMDEN CT 06514-3150  
Phone: 203-288-3509

=====  
Item Description  
n Information  
=====

Item Manager: S9G  
Item Name: DETECTION KIT,CHLORINATED SOLVENTS  
Unit of Issue: BG  
Quantitative Expression: 00000000020EA  
UI Container Qty: 1  
Type of Container: BAG

=====  
Ingredients  
=====

Name: \*\*\* PROPRIETARY \*\*\*  
-----

=====  
Health Hazards Data  
=====

=====  
LD50 LC50 Mixture: UNKNOWN

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: MAY CAUSE IRRITATION. EXPOSURE TO THIS PRODUCT MAY HAVE  
SERIOUS ADVERSE HEALTH EFFECTS

Signs And Symptoms Of Overexposure: THIS PRODUCT CAN CAUSE SEVERE INJURY  
ESPECIALLY IF IMPROPERLY HANDLED.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYES- FLUSH

WITH LARGE AMOUNTS OF WATER 15 MINUTES. SEEK MEDICAL  
ATTENTION. SKIN- FLUSH WITH LARGE AMOUNTS OF WATER. USE SOAP AND WATER TO  
WASH AWAY ORGANIC COMPONENTS. INHALATION- REMOVE TO FRESH AIR .

=====  
Handling and Disposal

=====  
Spill Release Procedures: ABSORB IN SOLVENT ABSORBENT.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,  
STATE AND LOCAL ENVIRONMENTAL REGUL  
ATIONS.

Handling And Storage Precautions: STORE KIT IN A COOL, DRY PLACE. CHECK  
EXPIRATION DATE PRIOR TO PERFORMING TEST.

Other Precautions: THE USER IS RESPONSIBLE FOR DETERMINING THE PRECAUTIONS AND  
DANGER OF THESE CHEMICALS FOR THE PARTICULAR APPLICATION.

=====  
Fire and Explosion Hazard Information

=====  
Flash Point Text: 48.0F,8.9C

Extinguishing Media: DO NOT USE WATER ON A SODIUM FIRE. D  
RY CHEMICAL, FOAM,  
CARBON DIOXIDE.

Fire Fighting Procedures: DO NOT USE WATER. WEAR SCBA. AVOID BREATHING SODIUM  
OXIDE FUMES WHICH WILL FORM ON COMBUSTION.

Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER. AMPULES MAY  
BURST IN FIRE.

=====  
Control Measures

=====  
Respiratory Protection: DEPENDING ON USAGE, RESPIRATORS MUST BE USED TO AVOID  
CONTACT WITH MATERIAL OR BREATHING CHE

MICAL VAPORS/FUMES.

Ventilation: PERFORM TEST ONLY IN A WELL VENTILATED AREA.

Protective Gloves: ALWAYS WEAR RUBBER GLOVES.

Eye Protection: SAFETY GLASSES.

Other Protective Equipment: WEAR APPROPRIATE SAFETY EQUIPMENT WHEN PERFORMING TEST ON SITE.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health: KEY1:F3. THIS MSDS IS FOR AMPULE 4: CONTAINS 400 MG ETHANOL. SEE PN IND A, B, C, E AND F; SAME NSN FOR ADDITIONAL INFORMATION OF THE OTHER COMPONENTS OF THIS KIT.

=====  
Physical/Chemical Properties  
=====

HCC: R2

B.P. Text: 172F,78C

Vapor Pres: 44 MM HG

Spec Gravity: 0.79

Evaporation Rate & Reference: 2.7 (N-BUTYL ACETATE=1)

Solubility in Water: MISCIBLE

Appearance and Odor: RED-GREEN PLEASANT ODOR.

Percent Volatiles by Volume: 99  
=====

Reactivity Data  
=====

Stability Indicator: YES

Stability Condition To Avoid: DO NOT EXPOSE BROKEN SODIUM AMPULE TO MOISTURE.

Materials To Avoid: STRONG OXIDIZERS.

Hazardous Decomposition Products: OXIDES OF CARBON.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT  
=====

Toxicological Information  
=====

Ecological In  
formation  
=====

MSDS Transport Information  
=====

Regulatory Information  
=====

Other Information  
=====

=====  
Transportation Information  
=====

Responsible Party Cage: 65297

Trans ID NO: 124859

Product ID: CLOR-D-TECT 1000; AMPULE 4 (RED-GREEN)

MSDS Prepared Date: 05/17/1995

Review Date: 08/02/1995

MFN: 4

AF MMAC Code: NR

Multiple KIT Number: 0

Kit Part IND: Y

Review IND: Y

Unit Of Issue: BG

Container QTY: 1

Type Of Container: BAG

Additional Data: THIS ITEM IS SMALL QUANTITY. (400 MG ETHANOL). REF. EXCEPTIONS  
FOR SMALL QUA

NTITIES 49 CFR 173.4. TO TAL KIT SHIPPED AS: PSN-ALKALI METAL

DISPERSIONS; HAZARD CLASS-4.3; UN 1391; PACKING GROUP 1. SEE THIS NSN &  
PN IND A, B, C, E, AND F FOR ADDITIONAL INFORMATION.

=====  
Detail DOT Information  
=====

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
Detail IMO Information  
=====

IMO PSN Code: GPL

IMO Proper Shipping Name: ETHYL ALCOHOL

IMDG Page Number: 3219

UN Number: 1170

UN Hazard Class: 3.2

IMO Packaging Group: II

Subsidiary Risk Label: -

EMS Number: 3-06

MED First Aid Guide NUM: 305  
=====

=====  
Detail IATA Information  
=====

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====  
===

=====  
Detail AFI Information  
=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

HAZCOM Label  
=====

Product ID: CLOR-D-TECT 1000; AMPULE 4 (RED-GREEN)

Cage: 65297

Company Name: DEXSIL CORP

Street: 1 HAMDEN PARK DR

City: HAMDEN CT

Zipcode: 06514-3150

He

alth Emergency Phone: 203-288-3509, CHEMTREC 800-424-9300

Label Required IND: Y

Date Of Label Review: 08/02/1995

Status Code: C

MFG Label NO: UNKNOWN

Label Date: 08/02/1995

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Respiratory Protection IND: YES

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: MAY CAUSE IRRITATION. EXPOSURE TO THIS PRODUCT MAY HAVE  
SERIOUS ADVERSE HEALTH EFFECTS STO

RE KIT IN A COOL, DRY PLACE. CHECK

EXPIRATION DATE PRIOR TO PERFORMING TEST. FIRST AID: EYES- FLUSH WITH LARGE  
AMOUNTS OF WATER 15 MINUTES. SEEK MEDICAL ATTENTION. SKIN- FLUSH WITH LARGE  
AMOUNTS OF WATER. USE SOAP AND WATER TO WASH AWAY ORGANIC COMPONENTS.  
INHALATION- REMOVE TO FRESH AIR. TARGET ORGANS: SKIN.

=====  
Disclaimer (provided with this information by the compiling agencies): This  
information is formulated for use by elements

of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the Unit

ed States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.