

P O B INC. -- PERFECT SEAL NO. 4 ( OMC 317210 ) -- 5330-01-114-4198

===== Product Identification =====

Product ID:PERFECT SEAL NO. 4 ( OMC 317210 )

MSDS Date:05/20/1986

FSC:5330

NIIN:01-114-4198

MSDS Number: BMSRG

=== Responsible Party ===

Company Name:P O B INC.

Address:11100 KENWOOD ROAD

City:CINCINNATI

State:OH

ZIP:45242-1818

Country:US

Info Phone Num:513-793-6332

Emergency Phone Num:513-793-6332

Preparer's Name:WILLIAM ROHLFING

CAGE:MO957

=== Contractor Identification ===

Company Name:CONAIR AVIATION ASSOCIATES

Address:138 E RIO GRANDE AVE

Box:721

City:WILDWOOD

State:NJ

ZIP:08260-4527

Country:US

CAGE:2K255

Company Name:OUTBOARD MARINE CORP, JOHNSON MOTORS DIV

Address:200 SEA HORSE DRIVE

Box:City:WAUKEGAN

State:IL

ZIP:60085

Country:US

Phone:708-689-6200

CAGE:32195

Company Name:P O B INC.

Address:11100 KENWOOD ROAD

Box:City:CINCINNATI

State:OH

ZIP:45242-1818

Country:US

Phone:513-793-

6332  
CAGE:MO957  
Company Name:P.O.B. INC.  
Address:11100 KENWOOD ROAD  
Box:City:CINCINNATI  
State:OH  
ZIP:45242  
Country:US  
Phone:513-793-6332  
CAGE:2A214

===== Composition/Information on Ingredients =====

Ingred Name:CASTOR OIL  
CAS:8001-79-4  
Fraction by Wt: 13.3%  
Other REC Limits:NONE SPECIFIED

Ingred Name:SOYABEAN OIL  
CAS:68152-81-8  
Fraction by Wt: 41.3%  
Other REC Limits:NONE SPECIFIED

Ingred Name:CELITE  
CAS:7631-86-9  
Fraction by Wt: 15.2%  
Other REC Limits:NONE SPECIFIED

Ingred  
Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 24.1%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER  
CAS:107-98-2  
RTECS #:UB7700000  
Fraction by Wt: 4.8%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192

Ingred Name:CELITE T38  
CAS:1344-95-2  
Fraction by Wt: 1.0%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 T

DUST; 9192

Ingred Name:SW 10 FIBRA-FILL

CAS:65996-61-4

Fraction by Wt: 0.3%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT IS MILDLY IRRITATING. INHALED  
IN LARGE QUANTITY IT PRODUCES AN ANESTHETIC EFFECT.

Explanation of Carcinogenicity:THIS CHEMICAL IS NOT LISTED AS HAVING  
ANY EVIDEN

CE OF BEING CARCINOGENIC.

Effects of Overexposure:EYE:IRRITATION. SKIN:MILD

IRRITATION,DRYING,POSSIBLE DERMATITIS. INHALED:RESPIRATORY  
IRRITATION. INGESTED:NOT GIVEN BY MANUFACTURER (SUPPLIER).

Medical Cond Aggravated by Exposure:NONE GIVEN BY MANUFACTURER  
(SUPPLIER).

===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:REMOVE  
CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. WASH WITH SOAP &  
WATER.

INHALED:REMOVE TO FRESH AIR. CALL A PHYSICIAN.

INGESTED:NONE GIVEN BY MA NUFACTURER (SUPPLIER).

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:54.0F,12.2C

Lower Limits:3.24

Upper Limits:20.6

Extinguishing Media:USE CARBON DIOXIDE OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED  
CONTAINERS WITH WATER SPRAY.

Unusual Fire/Exp

losion Hazard:CANS WILL RUPTURE IN EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATION IGNITION SOURCE - USE A NON-SPARK  
SCOOP TO CLEAN UP MATERIAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:R  
ESPIRATORY ONLY IF TLV OF ANY COMPONENT IS  
EXCEEDED.

Ventilation:TO MAINTAIN EXPOSURE BELOW TLV

Protective Gloves:GLOVES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Work Hygienic Practices:NONE GIVEN BY MANUFACTURER (SUPPLIER).

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:105F,41C

Vapor Pres:68 MM

Vapor Density:2.5

Spec Gravity:1.03

Evaporation Rate & Reference:NOT READABLE

Solubil

ity in Water:0.86

Appearance and Odor:BROWN LIQUID, MILD ODOR

Percent Volatiles by Volume:29

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

HYDROFLUORIC ACID

Stability Condition to Avoid:KEEP FROM CONTACT WITH OXIDIZING MATERIAL

Hazardous Decomposition Products:CARBON MONOXIDE & CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:BURNING I/A/W LOCAL, STATE AND FEDERAL  
REG

ULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.