

BARON-BLAKESLEE -- SLIDEWIRE CLEANER (HEWLETT PACKARD P/N 508 -- 4931-00-406-1511

===== Product Identification =====

Product ID:SLIDEWIRE CLEANER (HEWLETT PACKARD P/N 508

MSDS Date:11/01/1987

FSC:4931

NIIN:00-406-1511

MSDS Number: BMSXC

=== Responsible Party ===

Company Name:BARON-BLAKESLEE

Address:2001 N. JANICE AVENUE

Box:93921

City:MELROSE PARK

State:IL

ZIP:60164

Country:US

Info Phone Num:312

-450-3900

Emergency Phone Num:312-450-3900

CAGE:25233

=== Contractor Identification ===

Company Name:BARON-BLAKESLEE

Address:2001 N. JANICE AVENUE

Box:93921

City:MELROSE PARK

State:IL

ZIP:60164

Country:US

Phone:312-450-3900

CAGE:25233

Company Name:HEWLETT-PACKARD CO, CORPORATE HQ

Address:3000 MINUTEMAN RD

Box:City:ANDOVER

State:MA

ZIP:01810-1032

Country:US

Phone:404-648-8754/FAX: 800-947-3299

CAGE:28480

===== Composition/Information on Ingredients =====

Ingred Name:1,1,2-TR

ICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA  
III)

CAS:76-13-1

RTECS #:KJ4000000

Fraction by Wt: 75%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000PPM/1250STEL

ACGIH TLV:1000PPM/1250STEL9192

Ozone Depleting Chemical:1

Ingred Name:DICHLORODIFLUOROMETHANE - PROPELLANT F-12 (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Fraction by Wt: 25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

=====

===== Hazards Identification =====

LD50 LC50 Mixture:LD 50 ORAL RAT >400,000 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT IS PRIMARILY A CENTRAL NERVOUS  
SYSTEM DEPRESSANT AND CAN CAUSE IRRITATION OF RESPIRATORY TRACT,  
DIZZINESS,NAUSEA,HEADACHE, LOSS OF COORDINATION AND EQUILIBRIUM,  
UNCONSCIOUSNESS AND EVEN DEATH IN A CONFINED OR POORLY VENTILATED  
ARE

A.PROLONGED/REPEATED SKIN CONTACT CAN CAUSE IRRITATION AND  
DERMITITIS.

Explanation of Carcinogenicity:PRODUCT IS NOT LISTED AS A CARCINOGEN BY  
IARC, NTP OR OSHA.

Effects of Overexposure:EYE OR SKIN CONTACT: IRRITANT, DEFATTING.  
INHALED:LOW LEVEL (2500PPM FOR 0.5-1 HR) HEADACHE, DIZZINESS,  
NAUSEA, LOSS OF CONCENTRATION. HIGH LEVELS: OUSNESS OR DEATH.  
LIQUID CAN CAUSE DEFATTING OF TI SSUE. INHALED:HIGH LEVEL:  
INTOXICATION,CNS DEPRESSION, CARDIAC EFFECTS, EVEN DEATH.

INGESTED: SIMILAT TO INHALED.  
Medical Cond Aggravated by Exposure:NO INFORMATION GIVEN ON MSDS BY  
SUPPLIER.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:REMOVE  
CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. WASH WITH SOAP &  
WATER. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING AS NEEDED.  
INGESTED:IMMEDIA TELY INDUCE VOMITING. (NOTHING BY MOUTHIF  
UNCONSCIOUS.) GET IMMEDIATE MEDICAL CARE. IF  
ANY IRRITATION  
PERSISTS OR IS SEVERE, SEE A DOCTOR.

===== Fire Fighting Measures =====

Flash Point:NON-FLAMMABLE  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED  
CONTAINERS WITH WATER SPRAY.  
Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE! EXPOSURE TO  
TEMPERATURES OVER 130 F M  
AY RESULT IN RUPTURE OF THE CONTAINER.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AND VENTILATE AREA. DIKE AREA TO  
CONTAIN SPILL. PREVENT CONTAMINATION OF GROUND AND SURFACE WATERS.  
RECOVER OR COLLECT ON ABSORBENT MATERIAL AND TRANSFER TO STEEL  
DRUMS FOR RECOVERY OR DISPOS AL. DO NOT FLUSH TO SEWER. THOROUGHLY  
WET VAC AREA  
Neutralizing Agent:NONE

===== Handling and Storage =====

Hand  
ling and Storage Precautions:STORE BELOW 130 F. CONTENTS UNDER  
PRESSURE. DO NOT PUNCTURE OR INCINERATE. DEPRESSURIZE BEFORE  
DISPOSAL. DO NOT USE IN POORLY VENTILATED AREAS.  
Other Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID  
CONTAMINATION OF WATER SUPPLIES. VAPORS ARE HEAVIER THAN AIR AND  
WILL ACCUMULATE IN LOW AREAS. DO NOT STORE IN OPEN, UNLABELED OR  
MIS-LABELED CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protect

ion:RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE  
NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR OR SELF CONTAINED  
BREATHING APPARATUS IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29 CFR  
1910.134 FOR REGULATIONS PERTAINING TO RESPIRATOR USE.  
Ventilation:PROVIDE LOCAL EXHAUST AT FILLING ZONES AND OTHER OPERATING  
SPACES WHERE LEAKAGE IS PROBABLE. MECHANICAL FOR OTHER.  
Protective Gloves:LINED BUTYL RUBBER, PVA OR NEOPRENE  
Eye Protection:SPLASH GOGGLES  
Other Protective Equipment:EYE WASH ST  
ATION AND SAFETY SHOWER. USE  
IMPERVIOUS CLOTHING IF THERE IS DANGER OF REPEATED OR PROLONGED  
CONTACT.  
Work Hygienic Practices:NO INFORMATION GIVEN ON MSDS BY SUPPLIER.  
Supplemental Safety and Health  
AVOID PROLONGED OR REPEATED BREATHING OF VAPORS. USE ONLY WITH ADEQUATE  
VENTILATION. AVOID CONTACT WITH SKIN OR EYES. DO NOT TAKE  
INTERNALLY. DO NOT EAT DRINK OR SMOKE IN WORK AREAS. USE  
RESPIRATORY P ROTECTION AT HIGH EXPOSURE LEVELS OR WHEN ENTERING  
CONFINED AREAS. DO NOT PU  
NCTURE OR INCINERATE CONTAINER.

===== Physical/Chemical Properties =====

HCC:V2  
Boiling Pt:B.P. Text:117F,47C  
Melt/Freeze Pt:M.P/F.P Text:-31F,-35C  
Decomp Temp:Decomp Text:250F,121C  
Vapor Pres:5.5 PSIA  
Vapor Density:6.5  
Spec Gravity:1.57  
pH:NEUTRL  
Evaporation Rate & Reference:2.0  
Solubility in Water:0.1%  
Appearance and Odor:CLEAR COLORLESS LIQUID,ETHEREL AND FAINT SWEETISH  
ODOR  
Percent Volatiles by Volume:100

===== Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS AND ALKALIS, REACTIVE METALS (ESPECIALLY POWDERED), STRONG  
OXIDIZING AGENTS  
Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES , WELDING,  
CIGARETTES  
Hazardous Decomposition Products:HYDROCHLORIC ACID, HYDROFLUORIC ACID,  
PHOSGENE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W ALL FEDERAL, STATE AND LOCAL  
REGULATIONS. MANUFACTURER SUGGESTS THAT R

ECOVERED LIQUIDS MUST BE

REPROCESSED, INCINERATED OR TREATED BY A PERMITTED HAZARDOUS WASTE MANAGEMENT FACILITY. TRE AT MATERIAL CONTAMINATED BY PRODUCT AS ABOVE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any per

son utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.