

SOUTH COAST TERMINALS, INC -- SCT MULTIPURPOSE ATF, DEXRON II D-22823, FN --  
9150-00-657-4959

===== Product Identification =====

Product ID:SCT MULTIPURPOSE ATF, DEXRON II D-22823, FN

MSDS Date:04/30/1986

FSC:9150

NIIN:00-657-4959

MSDS Number: BMTMZ

=== Responsible Party ===

Company Name:SOUTH COAST TERMINALS, INC

Address:7401 WALLISVILLE ROAD

Box:15535

City:HOUSTON

State:TX

ZIP:77020-3555

Countr

y:US

Info Phone Num:713-672-2401

Emergency Phone Num:713-672-2401 EX 301

CAGE:1L506

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:4N760

Company Name:SOUTH COAST TERMINALS, INC

Address:7401 WALLISVILLE ROAD

Box:15535

City:HOUSTON

State:TX

ZIP:77020

Country:US

Phone:713-672-2401/800-424-9300(CHEMTREC)

CAGE:1L506

===== Composition/Information on Ing

redients =====

Ingred Name:LUBRICATING OIL BASE STOCK (CAS NO. 64741-97-5 OR  
64742-54-7 OR 64742-65-0)

CAS:64741-97-5

Fraction by Wt: 90.48%

OSHA PEL:5 MG/M3(AS OIL MIST)

ACGIH TLV:5 MG/M3(AS OIL MIST)

Ingred Name:ZINC SALT OF DIALKYL DITHIOPHOSPHORIC ACID (ZINC DIALKYL  
DITHIOPHOSPHATE)

CAS:68457-79-4

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:C.I. SOLVENT RED 164

Fraction by Wt: 0.02%

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:XYLENE

S (O-,M-,P- ISOMERS) (SARA III) \*

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: TRACE

OSHA PEL:100 PPM/150 STEL \*

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: SKIN,EYE, & RESPIRATORY

IRR

ITANT. CHRONIC:DERMATITIS.

Explanation of Carcinogenicity:NOT RELAVENT

Effects of Overexposure:SKIN/EYES:MAY CAUSE IRRITATION MANIFESTED BY

BURNING & REDNESS AS WELL AS DERMATITIS FOR SKIN ON PROLONGED OR

REPEATED CONTACT AND TEARING FOR EYES W/ DIRECT CONTACT;

INHAL:HEATED MIST OR VAPORS MAY C AUSE IRRITATION TO NOSE & THROAT.

INGEST:MAY CAUSE IRRITATION OF THE DISESTIVE TRACT.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN OR RESPIRATORY

ALIMENTS.

=====

==== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP & WATER, REMOVE CONTAMINATED CLOTHING.  
EYES:FLUSH W/ CLEAN WATER. INHAL:IF IRRITATION OF NOSE OR THROAT DEVELOPS, MOVE FROM EXPOSURE SOURCE. INGEST: DO NOT INDUCE VOMITING, CALL PHY SICIAN IMMEDIATELY. MEDICAL OPINION ISDEVIDED FOR LARGE INGEST. EMESIS OR LAVAGE HAS BEEN RECOMMENDED FOR THOSE PETROLEUM PRODUCTS WITH A HIGH ORALTOXICITY.

==== Fire Fighting Measures =====  
=====

Flash Point:>220F,>104C  
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER FOG, SAND OR EARTH. WATER OR FOAM MAY CAUSE FROTHING.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:NONE SPECIFIED

==== Accidental Release Measures =====

Spill Release Procedures:TREAT AS AN OIL SPILL. CONTAIN & REMOVE BY MECHANICAL MEANS.  
Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

==== Handling and Storage =====

Handling and Storage Precautions:NO INFORMATION GIVEN ON MSDS BY SUPPLIER  
Other Precautions:NONE

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED  
Ventilation:IF CURRENT VENTILATION PRACTICES DONOT MAINTAIN AIRBORNE CONCENTRATIONS BELOW PE L/TLV, MECHANICAL VENTILATION IS RECOMM.  
Protective Gloves:CHEMICAL RESISTANT  
Eye Protection:SAFETY GOGGLES OR SPLASH GOGGLES.  
Other Protective Equipment:NONE  
Work Hygienic Practices:NO INFORMATION GIVEN ON MSDS BY SUPPLIER  
Supplemental Safety and Health

==== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:500F/260C  
Vapor Pres:1.  
Spec Gravity:0.875 @ 60F  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:NEGLIGIBLE  
Appearance and

Odor:DARK AMBER LIQUID WITH MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT MAY CAUSE THERMAL DECOMPOSITION.

Hazardous Decomposition Products:IN THE PRESENCE OF AIR, THERMAL  
DECOMPOSITION MAY YIELD MAJOR AMTS OF OXIDES OF CARBON & MINOR AMTS  
OF OXIDES OF S,N,P,Z

===== Disposal Considerations =====

Waste Disposal Metho

ds:DISPOSE OF I/A/W APPLICABLE,FEDERAL,STATE OR  
LOCAL REGULATIONS. ENCLOSED-CONTROLLED INCINERATION IS RECOMMENDED  
UNLESS DIRECTED OTHERWISE BY APPLICABLE ORDINANCES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any per

son utilizing this

document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.