

CLAYTON CHEMICAL -- XR AERIAL DEVELOPER REPLENISHER,PART C -- 6750-00-151-6035

===== Product Identification =====

Product ID:XR AERIAL DEVELOPER REPLENISHER,PART C

MSDS Date:08/02/1991

FSC:6750

NIIN:00-151-6035

Kit Part:Y

MSDS Number: BMXFS

=== Responsible Party ===

Company Name:CLAYTON CHEMICAL

Address:13310 FIGUEROA STREET

City:LOS ANGELES

State:CA

ZIP:90061

Country:US

Info Phone Num:213-538-953

0

Emergency Phone Num:213-538-9530

CAGE:61803

=== Contractor Identification ===

Company Name:CLAYTON CHEMICAL CO.

Address:13310 S. FIGUEROA STREET

Box:City:LOS ANGELES

State:CA

ZIP:90061

Country:US

Phone:310-538-9530/800-424-9300(CHEMTREC)

CAGE:61803

===== Composition/Information on Ingredients =====

Ingred Name:2-METHOXYETHANOL (EGME) (SARA III)

CAS:109-86-4

RTECS #:KL5775000

Fraction by Wt: 30-35%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 25 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:CHOLINE BISULFATE
CAS:28427-24-9
Fraction by Wt: 25-30%
Other REC Limits:NONE SPECIFIED

Ingred Name:HYDROQUINONE (SARA III)
CAS:123-31-9
RTECS #:MX3500000
Fraction by Wt: 10-12%
Other REC Limits:NONE SPECIFIED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute a

nd Chronic:ACUTE: EYE AND SKIN IRRITATION.

ALLERGIC SKIN REACTION. CHRONIC: REPEATED CONTACT CAN CAUSE SKIN
SENSITIZATION AND ALLERGIC DERMATITIS. CHRONIC OVEREXPOSURE CAN
CAUSE ANEMIA AND DISCOLORATION AND CORN EAL OPACITY OF THE EYES.

Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT
IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYES/SKIN: IRRITATION AND BURNING. INHALATION:
NORMALLY NO PROBLEM, BUT INHALATION OF MIST COULD CAU
SE RESPIRATORY

IRRITATION. INGESTION: MAY CAUSE IRRITATION OF MUCOUS MEMBRANES OR
DIGESTIVE TRACT.

Medical Cond Aggravated by Exposure:NONE NOTED.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.IF
IRRITATION PERSISTS,SEE DOCTOR. SKIN:WASH WITH WATER WHILE REMOVING
CONTAMINATED CLOTHING AND SHOES.IF IRRITATION PERSISTS,SEE DOCTOR.
INHALA TION:REMOVE VICTIM TO FRESH AIR. INGESTION:DO NOT I

NDUCE
VOMITING.SEE DOCTOR IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:>160F,>71C
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.
Fire Fighting Procedures:EVACUATE PERSONNEL TO A SAFE AREA. KEEP PERSONNEL REMOVED AND UPWIND OF FIRE. WEAR SELF-CONTAINED BREATHING APPARATUS. AVOID HIGH TEMPERATURE.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PERSONNEL.ELIMINATE IGNITION SOURCES.VENTILATE AREA.WEAR PROTECTIVE CLOTHING AND EQUIPMENT.NEUTRALIZE WITH SODIUM CARBONATE.ABSORB IN INERT MATERIAL AND PLACE IN APPROPRIATE DISPOSAL CONTAINER AND COVER.
Neutralizing Agent:SODIUM CARBONATE.

===== Handling and Storage =====

Handling and
Storage Precautions:STORE IN WELL VENTILATED AREA. KEEP IN TIGHTLY CLOSED CONTAINERS. DO NOT STORE WITH STRONG ALKALINES.
Other Precautions:DO NOT STORE OR CONSUME FOOD, DRINK OR TOBACCO IN AREA WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCERN.
Ventilation:MECHANICAL (GENERAL) VENTILATION.
Protective Gloves:PVC GLOVES.
Eye Protection:CHEMICAL SAFETY GOGGLES.
Other Protective Equipment:EYE BATH.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
KEY1:C3. THIS IS PART C OF A 3-PART KIT. FOR PARTS A & B, SEE PNI A & F, SAME NSN.

===== Physical/Chemical Properties =====

HCC:C3
Boiling Pt:B.P. Text:212F,100C
Vapor Pres:AS WATER
Vapor Density:AS WATER

ER
Spec Gravity:1.119
pH:4.65
Evaporation Rate & Reference:SAME AS WATER
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR, AMBER LIQUID. ODOR OF AMINE WITH SLIGHTLY
SULFUR DIOXIDE.
Percent Volatiles by Volume:AS WTR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ALKALINE.
Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION
Hazardous Decomposition Products:SULFUR DIOXIDE, CARBO
N MONOXIDE,
CARBON DIOXIDE, INCOMPLETELY BURNED CARBON PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER. FOR
LIQUID, DISPOSE IN PERMITTED TREATMENT SYSTEM. FOR SOLID, DISPOSE
IN PERMITTED LANDFILL. DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL,
STATE AND LOCAL REGULA TIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by el
ements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.