

CHEMRAY COATING CORP -- STAIN, OIL SEMI-TRANSPARENT WOOD, EXT DK RE --
8010-00-926-9129

=====
===== Product Identification =====

Product ID:STAIN, OIL SEMI-TRANSPARENT WOOD, EXT DK RE

MSDS Date:01/10/1989

FSC:8010

NIIN:00-926-9129

MSDS Number: BNCGR

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-

1111

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

=====
===== Composition/Information on Ingredients =====

Ingred Name:RULE 66 MINERAL SPIRITS

Fraction by Wt: 70%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC: 5.36 LBS/GAL OR 643 GRAMS/LITER.

RTECS #:9999999VO

Ot

her REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:(ACIGH) (OSHA) 100 PPM (590 MG/M3) FOR
8 HOUR WORK DAY. HIGH VAPOR CONCENTRATIONS (OVER 1000 PPM) ARE
IRRITATING TO THE EYE & RESPIRATORY TRACT. MAY CAUSE HEADACHES &
DIZZINESS. PROLONG SKIN CONTACT I RRITATES.

=====
===== First Aid Measures =====

First Aid:EYE C
ONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION
SUBSIDES. IF IRRITATION PERSISTES CALL A PHYSICIAN. SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY WITH SOAP AND
WATER. INH ALATION: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR,
CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:103F,39C
Lower Limits:.9
Upper Limits:7
Extinguishing Media:CA
RBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL.
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT IN
CONFINED AREAS. FOR ENCLOSED AREAS, WATER SPRAY, AVOID BREATHING
VAPOR OR FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER
SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. KEEP FROM
HEAT/SPARK/OPEN FLAME. ADD ABSORBENT (SAND,
EARTH, SAWDUST) TO
SPILL. VENT AREA (OPEN WINDOW/DOOR). LRG SPILL: KEEP PRODUCT FROM
ENTERING SEWER & WATERCOURSE BY DIKI NG. ADVISE AUTHORITIES IF
PRODUCT HAS ENTERED.

=====
===== Handling and Storage =====

Handling and Storage Precautions:PROPER SHIPPING NAME--PAINT. HAZARDOUS
CLASSIFICATION--COMBUSTIBLE LIQUID ID NO UN1263.
Other Precautions:REPORTS HAVE ASSOCIATED REPEATED & PROLONGED
OCCUPATION OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN

& NERVOUS

SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING CONTENT MAY BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINE AREA.

Ventilation:LOCAL EXHAUST: FACE VELOCITY 60 FPM. MECHANICAL (GENERAL): USE EXPLOSION PROOF EQUIP. SPECIAL: USE ONLY W/ADEQUATE VENT.

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:SPLA

SH GOGGLES OR FACE SHIELD.

Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR OTHER CLOTHING TO AVOID REPEATED SKIN CONTACT.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE AND KEEP CONTAINER CLOSED WHEN NOT IN USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:308F,153C

Melt/Freeze Pt:M.P/F.P Text: