View NSN Online: https://aerobasegroup.tw/nsn/9140-00-286-5294

Product ID:NO.2 FUEL OIL MSDS Date:01/01/1987 FSC:9140 NIIN:00-286-5294 MSDS Number: BPBWY === Responsible Party === Company Name: APEX OIL CO Address:8182 MARYLAND AVE City:ST. LOUIS State:MO ZIP:63105-3506 Country:US Info Phone Num:314-889-9600 Emergency Phone Num:314-889-9600/800-424-9300(CHEMTREC) CAGE:8P125 === Contractor Identification === Company Name: APEX OIL CO Address:8182 MARYLAND AVE Box:City:ST. LOUIS State:MO ZIP:63105-3506 Country:US Phone:800-424-9300/314-889-9600 CAGE:8P125 Ingred Name:NO.2 FUEL OIL(COMPLEX MIXTURE OF PARAFINIC, OLEFINIC, NAPHTHENIC HC + FUSED POLYCYCLIC HC (C10 & HI) AS BENZENE SOLUBLES.) CAS:68476-30-2 RTECS #:LS8930000 Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYCYCL

IC HYDROCARBONS, CAS# 8007-45-2. Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 RAT = 14500MG/KG(NIOSH RTECS 85-86) Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:MIST/VAPOR MAY CAUSE RESP TRACT IRRIT, CNS DEPRESS. INGEST: IRRIT, CNS DEPRESS, COMA, DEATH. SKIN:DERM,DIRECT CONTACT MAY CAUSE EXTREME IRRIT W/SEV **ERE ERYTHEMS** & EDEME W/BLISTERING & OPEN SORES. EYE: IRRIT IS POSSIBLE BUT ANIMAL STUDIES INDICATE IT UNLIKELY.CHRONIC:RENAL FAILURE, DEGENERATIVE CHANGES OF LIVER/KIDNEY Explanation of Carcinogenicity:NONE OF THE INGREDIENTS ARE LISTED AS CARCINOGENS BY IARC, NTP, OR OSHA. AMES TESTS DID NOT INDICATE MUTAGENIC ACTIVITY. Effects of Overexposure:INHAL:GIDDINESS,HEAD,DIZZ,NAU,VOMIT,INCOORDINATION,NAR COSIS,STUPOR,COMA,UNCONSC,WT LOSS,ANEMIA,WEAKNESS,NERVOUSNESS,RENAL

FAILURE, PAINS IN LIMBS, PERIPHERAL NUMBNESS, PARESTHESIAS. INGEST: IRRIT GIDDINES S, VERTIGO, HEADACHE, ANESTHETIC STUPOR, CNS DEPRESS, COMA, DEATH. SKIN: DRYING, CRACKING, DERM, NARCOSIS, RASH OF PIMPLES & SPOTS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MFG.

- First Aid:INHAL:REMOVE TO FRESH AIR.STOP BREATH GIVE ARTIF RESP.KEEP WARM/REST. INGEST:DO NOT INDUCE VOMIT.IF INGEST>1MG/KG REMOVE BY GASTRIC LAVAGE B
- Y QUALIF MED PERSONNEL.IF VOMIT KEEP HEAD LOWER THAN HIPS TO PREVENT PULM ASPIRATION.STOP VOMIT GIVE 30-60ML FLEET'S PHOSPHO-SODA DILUTED 1:4 W/WATER. SKIN:REMOVE CONTAMIN CLOTH.WIPE OFF EXCESS W/DRY CLOTH.WASH W/SOAP OR MILD DETERGENT & LG AMTS WATER 15-20MIN

Flash Point Method:TCC Flash Point:100F,38C Autoignition Temp:Autoignition Temp Text:>500F Lower Limits:0.6 Upper Limits:7.5 Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, FOR LARGER FIRES USE WATER SPRAY, FOG OR FOAM. Fire Fighting Procedures:USE SUPPLIED-AIR BREATHING EQPMT FOR ENCLOSED AREAS.COOL EXPOSED CONTAINERS W/WATER SPRAY.CONTINUE WATER SPRAY TIL ENTIRE CONTAINER CONTENTS ARE COOL.(SEE SUPP) Unusual Fire/Explosion Hazard:DO NOT MIX/STORE W/STRONG OXIDANTS NOR STORE/POUR NEAR IGN SOURCES.DO NOT PRESS/CUT/HEAT/WELD/EXPOSE EMTPY CNTNRS TO IGN SOURCES.VAP HEAVY & TRAVEL & FLASHBACK.

Spill Release Procedures:SUT OFF IGN SOURCES.ISOLATE HAZ AREA & RESTRICK ENTRYL.SM:TAKE UP W/SAND/OTHER ABSORBENT MATL.PLACE INTO CONTNRS.LG:DIKE FAR AHEAS TO PREVENT ENTRANCE INTO WATER COURSES &/OR GROUND WATER.OBSERVE LOC/ STATE/FED GOVRT SPILL & WATER QUALITY REGS.

Neutralizing Agent:NONE SPECIFIED BY MFG.

Handling and Storage Precautions: AVOID EXCESSIVE INHALATIO N OR SKIN

CONTACT. ISOLATE FROM SOURCES OF IGNITION. Other Precautions:NONE SPECIFIED BY MFG.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: MASK W/ORGANIC VAPOR CARTRIDGE IS RECOMMENDED. USE POSITIVE PRESSURE AIR-SUPPLIED ON SCBA IN THE EVENT OF A LARGE SPILL.

Ventilation:LOC EXHAUST:INDOORS USE LAB HOOD.OUTDOORS WORK UPWIND.MECH (GEN) RECOMMENDED FOR USE IN ENCLOSED/SEMIENCLOSED WORK AREA.

Protective Gloves:NEOPRENE, PVC.

Eye Protec

tion:SPLASH GOGGLES,SAF GLASSES W/SIDESHIELDS

Other Protective Equipment: EMPLOYEE MUST WEAR APPROPRIATE IMPERVIOUS CLOTHING & EQPMT TO PREVENT REPEATED/PROLONGED SKIN CONTACT W/THIS SUBSTANCE.

Work Hygienic Practices:WASH HANDS AFTER HANDLING & PRIOR TO EAT/SMOKE/DRINK.LAUNDER CONTAMIN CLOTHING PRIOR TO REUSE.DO NOT SMOKE IN WORK AREA.

Supplemental Safety and Health

W/DRAW IMMED IN CASE OF RISING SOUND FROM VENTING SAFETY DEVICE OR ANY DISCOLORATION OF STORAGE TANK DUE TO FIR

E(SUBJECT TO FIRE CHIEF'S DIRECTIONS). 1STAID EYE:FLUSH IMMED W/COPIOUS AMTS OF WATER LIF TING EYELIDS 15-20MINS.IN ALL CASES GETMED ATTN.

HCC:F4 Boiling Pt:B.P. Text:350F,177C Vapor Pres:1MM @68F Vapor Density:>5 Spec Gravity:0.9 Evaporation Rate & amp; Reference:>10, N-BUTYL ACETATE=1 Solubility in Water:INSOLUBLE. Appearance and Odor:BROWN, SLIGHTLY VISCOUS LIQUID. Percent Volatiles by Volume:>50

Stability Indicator/Materials to Avoid:YES
MAY REACT WHEN EXPOSED TO OXIDIZING MATERIALS.
Stability Condition to Avoid:MAY BE IGNITED BY HEAT/SPARKS/FLAME.VAP
MAY TRAVEL TO IGNITION SOURCES & FLASHBACK.VAP EXPLO HAZ
INDOORS/OUTDOORS/SEWERS
Hazardous Decomposition Products:THERM DECOMP MAY RELEASE VARIOUS
HYDROCARBONS & HDROCARBON DERIVATIVES INCLUDING C02, WATER, ORGANIC ACIDS, & ALDEHYDES.

====== Disposal Conside

Waste Disposal Methods:UNDER EPA RCRA IF PRODUCT BECOMES A WASTE MATL INTENDED FOR DISOSAL & HAS FLASH POINT