

ILFORD PHOTO CORP -- P-22 FIXER FX 22.15 PART A -- 6750-01-313-1956

===== Product Identification =====

Product ID:P-22 FIXER FX 22.15 PART A

MSDS Date:10/28/1988

FSC:6750

NIIN:01-313-1956

Kit Part:Y

MSDS Number: BPCFW

=== Responsible Party ===

Company Name:ILFORD PHOTO CORP

Address:33 LEWIS RD

City:BINGHAMPTON

State:NY

ZIP:13905

Country:US

Info Phone Num:800-421-1100/201-265-6000

Emergency Phone N

um:800-842-9660

CAGE:0LT87

=== Contractor Identification ===

Company Name:ILFORD IMAGING USA INC

Address:33 LEWIS RD

Box:City:BINGHAMTON

State:NY

ZIP:13905

Country:US

Phone:607-766-3153/ FAX 201-225-3514

CAGE:0LT87

===== Composition/Information on Ingredients =====

Ingred Name:AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000

Fraction by Wt: 40 - 50%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SULFIDE

CAS:37199-66-9

RTECS #:TT5950000

Fraction by Wt: 12 - 15%

O

ther REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT ESTABLISHED.  
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:POTASSIUM BISULFITE  
CAS:7773-03-7  
Fraction by Wt: 2 - 5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:TETRASODIUM ETHYLENE DIAMINE TETRAACETATE  
CAS:64-02-8  
RTECS #:AH5075000  
Fraction by Wt: 1 - 3%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 35 - 50%  
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE- EYE/SKIN:IRRITATION.  
INHALATION:LOW HAZARD FOR RECOMMENDED HANDLING. ORAL:MAY CAUSE  
STOMACH UPSET AND IRRITATION. CHRONIC-NONE KNOWN OR EXPECTED.  
Effects of Overexposure:CAUSES EYE AND SKIN IRRITATION. INHALATION HAS  
LOW HAZARD. ORALLY MAY CAUSE STOMACH UPSET AND IRRITATION.  
Medical Cond Aggravated by Exposure:INDIVIDUALS WITH  
SENSITIVE SKIN MAY  
BE MORE ADVERSELY AFFECTED.

===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES:IMMEDIATELY  
FLUSH WITH PLENTY OF WATER. SKIN:FLUSH WITH PLENTY OF SOAP AND  
WATER. INHALATION:REMOVE TO FRESH AIR. INGESTION:IF CONSCIOUS,  
DRINK 2-3 GLAS SES OF WATER. INDUCE VOMITING. SEEK MEDICAL  
ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONE  
Extingu

ishing Media:AS APPROPRIATE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND  
PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:MAY PRODUCE HAZARDOUS DECOMPOSITION  
PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH SMALL SPILLS TO A NON-ACID SEWER WITH  
LARGE AMOUNTS OF WATER IF REGULATIONS ALLOW.

===== Handling and Storage =====

Handling and Stora

ge Precautions:STORAGE- STORE IN COOL PLACE. KEEP  
CONTAINER TIGHTLY CLOSED AND AWAY FROM ACIDS.

Other Precautions:AVOID BREATHING VAPORS OR MISTS. DO NOT GET IN EYES,  
ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE  
EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. KEEP OUT  
OF REACH OF C HILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WITH GOOD VENTILATION.

Ventilation:GOOD GENERAL VENTI  
LATION SHOULD BE SUFFICIENT.

Protective Gloves:RUBBER OR PLASTIC RECOMMENDED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND  
IMPERVIOUS CLOTHING

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND  
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR  
FOOTWEAR.

Supplemental Safety and Health

THIS PRODUCT IS A KIT CONSISTING OF: DEVELOPER PART A AND PART B (PIN A  
AND B); FIXER PART A AND B (PIN C AND D); BLEA  
CH PART A AND B (PIN  
E AND F); AND BLEACH NEUTRALIZER PART A AND B (PIN G AND H).

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:AS WATER

Vapor Density:AS WATER

Spec Gravity:1.388

pH:6.8

Evaporation Rate & Reference:1 (WATER=1)

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR, COLORLESS LIQUID, SLIGHT AMMONIA ODOR

Percent Volatiles by Volume:42

===== Stability and Reactivity Data =====

====

Stability Indicator/Materials to Avoid: YES  
ACIDS  
Stability Condition to Avoid: FIRE, EXCESSIVE HEAT  
Hazardous Decomposition Products: OXIDES OF SULFUR

===== Disposal Considerations =====

Waste Disposal Methods: DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT  
TO FEDERAL, STATE OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United  
States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.