

LHB INDUSTRIES -- SO SURE ALUMINUM 17178 14-160

=====

MSDS Safety Information

=====

FSC: 8010

NIIN: 00-721-9751

MSDS Date: 04/16/1992

MSDS Num: BPFZG

Product ID: SO SURE ALUMINUM 17178 14-160

MFN: 03

Responsible Party

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 631

34

Info Phone Number: 314-522-3141

Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141

Preparer's Name: RUDOLF OPPENHEIM

Review Ind: Y

Published: Y

=====

Preparer Co. when other than Responsible Party Co.

=====

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 63134

=====

Contractor Summary

=====

=====

Cage: 0FTT5

Name: LHB INDUSTRIES

Address: 8833 FLEISCHER PLACE

City: ST. LOUIS MO 63134

Phone: 314-522-3141

=====

Item Description Information

=====

Item Manager: GSA

Item Name: ENAMEL

Specification Number: A-A-665D

Unit of Issue: PT

UI Container Qty: 0

=====

Ingredients

=====

=====

Cas: 8030-30-6
RTECS #: DE3030000
Name: VM&P NAPHTHA
% Wt: 5.28
Other REC Limits: NONE SPECIFIED
OSHA PEL: 300 PPM
ACGIH TLV: 300 PPM

Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE (SARA III)
% Wt: 26.62
Other REC Limits: NONE SPECIFIED
OSHA PEL: 200 PPM/150 STEL
ACGIH TLV: 50 PPM; 9293
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 67-64-1
RTECS #: AL3150000
Name: ACETONE (SARA III)
% Wt: 30.97
Other REC L
imits: NONE SPECIFIED
OSHA PEL: 1000PPM
ACGIH TLV: 750PPM/1000STEL;9293
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 74-98-6
RTECS #: TX2275000
Name: PROPANE
% Wt: 16.72
Other REC Limits: NONE SPECIFIED
OSHA PEL: 1000 PPM
ACGIH TLV: 1000 PPM

Cas: 75-28-5
RTECS #: TZ4300000
Name: ISOBUTANE
% Wt: 4.11
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 800 PPM

Cas: 106-97-8
RTECS #: E

J4200000

Name: N-BUTANE

% Wt: 6.58

Other REC Limits: NONE SPECIFIED

OSHA PEL: 800 PPM

ACGIH TLV: 800 PPM

RTECS #: 9999999VO

Name: VOC: 671 G/L

Other REC Limits: NONE SPECIFIED

=====

Health Hazards Data

=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: CONCENTRATING & INHALIN

G MAY BE HARMFUL/FATAL.

REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS: PERMANENT
BRAIN & NERVOUS SYS DAMAGE. IN CONFINED AREAS VAPOR IN HIGH CONC ARE
ANESTHETIC. IR RIT TO SKIN & RESP TRACT. LIGHT HEADEDNESS, STAGGERING,
GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.

Signs And Symptions Of Overexposure: IRRITATION TO EYES, THROAT AND RESPIRATORY
TRACT. MAY CAUSE HEADACHES, NAUSEA AND VOMITING.

Medical Cond Aggravated By Exposure: RESPIRATORY AI
LEMENTS.

First Aid: FOR CONTACT WITH SKIN OR CLOTHES, WASH WITH SOAP & WATER; WASH
CLOTHES BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES
& CONTACT PHYSICIAN/OPHTHAMOLOGIST IMMEDIATELY. IF SWALLOWED , DO NOT
INDUCE VOMITING. GET IMMEDIATEMEDICAL AID. IF INHALED, REMOVE TO FRESH AIR
AND GIVE ARTIFICIAL RESPIRATION IF NECESSARY AND GET MED AID. NEVER GIVE
ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

=====

Handling
and Disposal

=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.
MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE & LOCAL
REGULATIONS. DO NOT PUNCTURE, INCINERATE OR STORE ABOVE 120F. EXPOSURE TO
HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING. DISCARD EMPTY CAN IN T
RASH PICK-UP. DON'T PLACE IN HOME TRASHCOMPACTOR.

Handling

And Storage Precautions: KEEP OUT OF REACH OF CHILDREN!
CAUTION-CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120F. AVOID BREATHING
SPRAY, MIST OR VAPOR.
Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION.
READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL
MISUSE BY DELIBERATELY CONCENTRATING & INHALING OR SWALLOWING CONTENTS
MAY BE HARMFUL OR FATAL.

=====

Fire and Explosion Hazard In
formation

=====

Flash Point Text: NR
Autoignition Temp Text: 874 F
Lower Limits: 1.8
Upper Limits: 9.5
Extinguishing Media: CO2, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. AVOID
SPREADING ANY BURNING LIQUID WITH WATER SPRAY.
Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO KEEP FIRE EXPOSED
CONTAINER COOL. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST
BURSTING, RUPTURING, VENTING OF CONTNRS.
Unusual Fire/Explosion Hazard: DON'T
T SPRAY NEAR OPEN FLAME. AT ELEVATED
TEMPERATURES (OVER 120F) CONTAINERS MAY VENT RUPTURE OR BURST. AEROSOL
CONTAINERS; DO NOT EXPOSE TO TEMPS ABOVE 120F.

=====

Control Measures

=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.
Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT
POINT OF MIST OR SPRAY RELEASE.
Protective Gloves: TO
PROTECT SKIN.
Eye Protection: CHEMICAL SPLASH GOGGLES.
Other Protective Equipment: IMPERVIOUS CLOTHING TO PROTECT SKIN. EYE WASH
STATION.
Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK OR SMOKE
WHILE USING PRODUCT.

=====

Physical/Chemical Properties

=====

HCC: V3
Vapor Pres: 60 @ 68F
Vapor Density: >1.5
Spec Gravity: 0.848 (WATER=1)
Solubility in Water: INSOLUBLE
App

earance and Odor: ALUMINUM / PAINT
=====

Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: EXTREME HEAT.
Hazardous Decomposition Products: CARBON MONOXIDE, AND POSSIBLE HYDROGEN
CHLORIDE.
Hazardous Polymerization Indicator: NO
=====

Toxicological Information
=====

Ecological Information
=====

MSDS Transport Information
=====

Regulatory Information
=====

Other Information
=====

Transportation Information
=====

Responsible Party Cage: 0FTT5
Trans ID NO: 83198
Product ID: SO SURE ALUMINUM 17178 14-160
MSDS Prepared Date: 04/16/1992
Review Date: 09/08/1992
MFN: 3
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: PT
Container QTY: 0
=====

Detail DOT Information
=====

=====
DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30KGGROSS
Vessel Stow Req: A
=====

Detail IMO Information
=====
IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?
IMDG Page Number: SEE 9022
UN Number: 19
50
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13
=====

Detail IATA Information
=====
IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG
Max Quant Cargo: 150KG
Packaging Note Car
go: 203
=====

Detail AFI Information
=====
AFI PSN Code: ALS
AFI Proper Shipping Name: AEROSOLS, NONFLAMMABLE, N.O.S.
AFI PSN Modifier: CONTAINING SUBSTANCES IN CLASS 8, PACKING GROUP I OR II
AFI Hazard Class: FORB
Back Pack Reference: FORBIDDEN
=====

HAZCOM Label
=====
Product ID: SO SURE ALUMINU

M 17178 14-160
Cage: 0FTT5
Company Name: LHB INDUSTRIES
Street: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
Zipcode: 63134
Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141
Label Required IND: Y
Date Of Label Review: 12/16/1998
Status Code: C
Label Date: 12/16/1998
Origination Code: G

Hazard And Precautions: CONCENTRATING & INHALING MAY BE HARMFUL/FATAL.
REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS: PERMANENT
BRAIN & NERVOUS SYS DAMAGE. IN CONFINED AREAS VAPOR
IN HIGH CONC ARE
ANESTHETIC. IR RIT TO SKIN & RESP TRACT. LIGHT HEADEDNESS, STAGGERING,
GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. IRRITATION TO
EYES, THROAT AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA AN D
VOMITING.

=====

Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America i
n no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice
to verify
and assume responsibility for the suitability of this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other government situation.