View NSN Online: https://aerobasegroup.com/nsn/6850-00-965-2331 MAGNAFLUX CORPORATION -- CLEANING COMPOUND SOLVENT/SOLUBLE GREASE 6850-00-965-2331 Product ID:CLEANING COMPOUND SOLVENT/SOLUBLE GREASE MSDS Date:11/20/1992 FSC:6850 NIIN:00-965-2331 MSDS Number: BPJGK

Company Name: MAGNAFLUX CORPORATION Address:7300 W LAWRENCE AVE City:CHICAGO

State:IL

ZIP:60656-3504 Country:US

Info Phone Num:312-867-

=== Responsible Party ===

0008

Emergency Phone Num:312-867-8000

Preparer's Name: DGSC-SSH

CAGE:37676

=== Contractor Identification ===

Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL ZIP:60025 Country:US

Phone:847-657-5300/

CAGE:37676

======= Composition/Information on Ingredients ========

Ingred Name: ALIPHATIC HYDROCARBONS Other REC Limits: NONE SPECIFIED ACGIH TLV:200 PPM

**LD50** 

LC50 Mixture:NOT KNOWN Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE IRRITATION, SKIN IRRITATION, IRRITATION/POSSIBLE DAMAGE TO MUCOUS MEMBRANES. Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA. Effects of Overexposure:EYE, SKIN IRRITATION. DAMAGE TO THROAT IF SWALLOWED. Medical Cond Aggravated by Exposure:INDIVID UALS WITH PRE-EXISTING SKIN CONDITIONS MAY BE AT INCREASED RISK FROM EXPOSURE.
======================================
First Aid:SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH FOR 15 MINUTES WITH WATER-CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING-CALL PHYSICIAN. REMOVE TO FRESH AIR-GIVE OXYGEN IF BREATHING IS IMPAIRED.
======================================
Flash Point Method:TCC Flash Point:160F,71C Lower Limits:NO T KNOWN Upper Limits:NOT KNOWN Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, WATER, FOAM Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.  ===================================
Spill Release Procedures:DAM UP WITH SANDBAGS-SOAK UP ABSORBENT MATERIAL. PUMP INTO SEALABLE CONTAINERS.
======================================
Handling and Storage Precautions:STORE IN SEALED CONTAINERS BETWEEN 30-120F. Other Precautions:NONE KNOWN.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:ORGANIC VAPOR CANISTER IF VAPOR ABOVE TLV OF 200 PPM Ventilation:LOCAL Protective Gloves:RECOMMENDED Eye Protection:CHEMICAL GOGGLES Other Pr

otective Equipment:EMERGENCY EYEWASH AND SHOWER
Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT
AND BEFORE EATING DRINKING OR SMOKING.
Supplemental Safety and Health

======== Physical/Chemical Properties ==========

HCC:V4

Boiling Pt:B.P. Text:355F,179C

Vapor Pres:1 Spec Gravity:0.87

Evaporation Rate & Dr. Reference: