View NSN Online: https://aerobasegroup.tw/nsn/9340-01-323-0527

MINNESOTA MINING/ADH COATINGS/SEALERS -- SCOTCHPLY SP377CU1 LOW ENERGY CURE COMPOSITE PREPREG -- 9340-01-323-0527

============= Product Identification ==================

Product ID:SCOTCHPLY SP377CU1 LOW ENERGY CURE COMPOSITE PREPREG

MSDS Date:01/01/1990

FSC:9340

NIIN:01-323-0527

MSDS Number: BPSZG === Responsible Party ===

Company Name: MINNESOTA MINING/ADH COATINGS/SEALERS

Address:3M CTR City:ST PAUL State:MN ZIP:551

Country:US

44-1000

Emergency Phone Num:612-733-1110

CAGE:76381

=== Contractor Identification ===

Company Name: 3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR Box:City:SAINT PAUL

State:MN

ZIP:55144-1000 Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name: MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000 Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

====== Composition/Inf

Ingred Name:GLASS FABRIC Fraction by Wt: 55-70% Ingred Name:2,2-BIS(4-(2,3-EPOXYPROPYLOXY)PHENYL)PROPANE, BISPHENOL A DIGLYCIDYL ETHER, EPON 828, EPOXIDE A CAS:1675-54-3 RTECS #:TX3800000 Fraction by Wt: 15-25% Ingred Name:CURATIVES FOR EPOXY RESIN - TRADE SECRET Fraction by Wt: 10-20%	ormation on Ingredients ========
DIGLYCIDYL ETHER, EPON 828, EPOXIDE A CAS:1675-54-3 RTECS #:TX3800000 Fraction by Wt: 15-25% Ingred Name:CURATIVES FOR EPOXY RESIN - TRADE SECRET Fraction by Wt: 10-20% ===================================	<u>u</u>
Fraction by Wt: 10-20% ===================================	CAS:1675-54-3 RTECS #:TX3800000
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC :NO OSHA:NO Health Hazards Acute and Chronic:EYES: DUST FROM CUTTING/GRINDING/SANDING OF CURED PRODUCT MAY CAUSE IRRITATION. SKIN: ALLERGIES. INHALATION: IRRITATION OF RESPIRATORY SYSTEM. Explanation of Carcinogenicity:NONE Effects of Overexposure:SKIN: DUST FROM CUTTING, GRINDING, OR SANDING OF CURED PRODUCT MAY CAUSE IRRITATION.	<u>u</u>
Reports of Carcinogenicity:NTP:NO IARC :NO OSHA:NO Health Hazards Acute and Chronic:EYES: DUST FROM CUTTING/GRINDING/SANDING OF CURED PRODUCT MAY CAUSE IRRITATION. SKIN: ALLERGIES. INHALATION: IRRITATION OF RESPIRATORY SYSTEM. Explanation of Carcinogenicity:NONE Effects of Overexposure:SKIN: DUST FROM CUTTING, GRINDING, OR SANDING OF CURED PRODUCT MAY CAUSE IRRITATION. ===================================	======================================
CUTTING/GRINDING/SANDING OF CURED PRODUCT MAY CAUSE IRRITATION. SKIN: ALLERGIES. INHALATION: IRRITATION OF RESPIRATORY SYSTEM. Explanation of Carcinogenicity:NONE Effects of Overexposure:SKIN: DUST FROM CUTTING, GRINDING, OR SANDING OF CURED PRODUCT MAY CAUSE IRRITATION. ===================================	Reports of Carcinogenicity:NTP:NO IARC
OF CURED PRODUCT MAY CAUSE IRRITATION. ===================================	Health Hazards Acute and Chronic:EYES: DUST FROM CUTTING/GRINDING/SANDING OF CURED PRODUCT MAY CAUSE IRRITATION. SKIN: ALLERGIES. INHALATION: IRRITATION OF RESPIRATORY SYSTEM.
First Aid:EYES: IMMEDATELY FLUSH W/PLENTY OF WATER. SKIN: THOROUGHLY WASH AFFECT ED AREA W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES. ==================================	·
WASH AFFECT ED AREA W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES. ==================================	======================================
INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES. ==================================	
Extinguishing Media:CO2, FOAM, DRY CHEMICAL Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. ===================================	
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. ===================================	======================================
Spill Release Procedures:OBSERVE PRECAUTIONS. COLLECT SPILLED MATERIAL. PLACE IN A CLOSED CONTAINERS.	
PLACE IN A CLOSED CONTAINERS.	========= Accidental Release Measures ===========
======================================	
	======================================

and Storage ===========
Handling and Storage Precautions:FOR INDUSTRIAL/PROFESSIONAL USE. AVOID CONTACT W/EYES, SKIN, INHALATION OF VAPORS. USE SUFFICIENT VENTILATION. KEEP FROM CHILDREN. Other Precautions:USE WATER AS LUBRICANT ON MACHINING TOOLS TO ELIMINATE DUST/IMPROVE MACHINABILITY OF CURED PARTS. STORE AT 72F OR BELOW TO MAINTAIN SHELF LIFE. ALLOW TO THOROUGHLY WARM TO ROOM TEMP. DON'T OPEN PROTEC TIVE CONTAINER BEFORE AMBIENT CONDITION.
====== Ex posure Controls/Personal Protection ========
Respiratory Protection:WEAR DUST MASK TO AVOID DUST EXPOSURE. Ventilation:SUFFICIENT TO REMOVE VAPORS/PREVENT VAPOR BUILDUP. VENT CURING EQUIPMENT TO OUTDOORS/SUITABLE EMISSION CONTROL DEVICE. Eye Protection:SAFETY GLASSES OR GOGGLES Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health
========= Physical/Chemical Properties ==========
Spec Gravity:1.5-2 Solubility in Water:INSOLUBLE Appearance and Odor:BLACK TAPE, NO ODOR. Percent Volatiles by Volume:0.5-2%
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO, CO2

======= Disposal Considerations ===========

Waste Disposal Methods: UNCURED: INCINERATE AFTER MIXING W/FLAMMABLE MATERIAL IN INDUSTRIAL/COMMERCIAL FACILITY. CURED: DISPOSE OF IN SANITARY LANDFILL ACCORDING TO STATE, L OCAL, OR FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this infor

mation to their particular situation.