

NONFLUID OIL CORP -- VV-G-671F GRAPHITE GREASE -- 9150-01-320-2636

===== Product Identification =====

Product ID:VV-G-671F GRAPHITE GREASE

MSDS Date:01/10/1992

FSC:9150

NIIN:01-320-2636

MSDS Number: BPXBK

=== Responsible Party ===

Company Name:NONFLUID OIL CORP

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Info Phone Num:201-344-3451

Emergency Phone Num:201-344-3451

CAGE:7

6736

=== Contractor Identification ===

Company Name:NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Phone:201-344-3451/800-424-9300(CHEMTREC)

CAGE:76736

===== Composition/Information on Ingredients =====

Ingred Name:HYDROTREATED HEAVY NAPHTHENIC DISTILLATE, PETROLEUM

CAS:64742-52-5

RTECS #:PY8035000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

===== Ha

zards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT  
TENDS TO REMOVE SKIN OILS AND MAY CAUSE SKIN IRRITATION. EXPOSURE  
TO FUMES OR MISTS MAY CAUSE MUCOUS MEMBRANE IRRITATION.  
Effects of Overexposure:EYES/SKIN: IRRITATION. INHALATION: NOSE, THROAT  
AND UPPER RESPIRATORY SYSTEM IRRITATION. INGESTION: NO SYMPTOMS  
NOTED.

Medical Cond Aggravated by Exposure:NONE.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER. SKIN: WIPE OFF AND WASH  
WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION:  
GIVE WATER. DO NOT INDUCE VOMITING. SEE DOCTOR. --IF PRODUCT IS  
INJECTED UND ER THE SKIN, SEE DOCTOR IMMEDIATELY REGARDLESS OF  
APPEARANCE OR SIZE. THIS IS A SERIOUS MEDICAL EMERGENCY--

===== Fire Fighting Measures ====  
=====

Flash Point Method:COC  
Flash Point:>360F,>182C  
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL OR WATER FOG  
CAREFULLY TO PREVENT FROTHING.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED  
CONTAINERS WITH WATER SPRAY.  
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE  
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Rel  
ease Measures =====

Spill Release Procedures:SCRAPE UP GREASE. WASH REMAINDER WITH SUITABLE  
PETROLEUM SOLVENT. ABSORB IN INERT MATERIAL AND PLACE IN APPROPRIATE  
DISPOSAL CONTAINER AND COVER. WASH AREA WITH SOAP AND WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED,  
LOW FIRE RISK AREA. PROTECT FROM HEAT, OPEN FLAMES AND INCOMPATIBLE  
MATERIALS. KEEP CONTAINERS CLOSED.

Other

Precautions:AVOID REPEATED CONTACT WITH SKIN. AVOID CONTACT WITH EYES AND INHALATION OF FUMES, VAPORS OR MISTS. DO NOT INGEST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED.

Ventilation:GENERAL (MECHANICAL) VENTILATION. USE LOCAL EXHAUST IF MISTING.

Protective Gloves:NITRILE, PVA.

Eye Protection:SAFETY GLASSES, IF MISTING.

Other Protective Equipment:OIL RESISTANT APRON.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. LAUNDER

CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NONE.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F,>288C

Melt/Freeze Pt:M.P/F.P Text:200F,93C

Vapor Pres:10

Spec Gravity:0.91

Evaporation Rate & Reference: