

RICOH CO LTD -- 4120 TONER -- 6850-01-026-7239

=====
Product Identification
=====

Product ID:4120 TONER
MSDS Date:01/05/1987
FSC:6850
NIIN:01-026-7239
Kit Part:Y
MSDS Number: BQDNH
=== Responsible Party ===
Company Name:RICOH CO LTD
Address:1-3-6 NAKAMAGOME OTA-KU
City:TOKYO
Country:JA
Info Phone Num:201-882-5231 IN USA
Emergency Phone Num:201-882-5231 IN USA
CAGE:S0407
=== Contractor Identificat
ion ===
Company Name:RICOH CO LTD
Address:1-3-6 NAKAMAGOME OTA-KU
Box:City:TOKYO
Country:JA
Phone:03-777-8111JAPAN; 0559-21-2251
CAGE:S0407
Company Name:SAVIN CORP.
Address:9 WEST BROAD STREET
Box:12070
City:STAMFORD
State:CT
ZIP:06904-2270
Country:US
Phone:203-967-5000
CAGE:29382

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPARAFFINIC HYDROCARBON SOLVENT (HYDROTREATED HEAVY
NAPHTHA)
CAS:64742-48-9
Fraction by Wt: 90%
Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM (NAPHTHA)
ACGIH TLV:400 PPM (NAPHTHA)

Ingred Name:ACRYLIC RESIN
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9293

=====
===== Hazards Identification =====

LD50 LC50 Mixture:TLV IS 300 PPM
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSH
A:NO

Health Hazards Acute and Chronic:ACUTE AND CHRONIC- HEALTH STUDIES HAVE BEEN SHOWN THAT MANY PETROLEUM HYDROCARBONS AND LUBRICANTS POSE POTENTIAL HUMAN HEALTH RISKS WHICH MAY VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUID, VAPOR, MIST/FUME SHOULD BE MINIMIZED. VAPORS MAY CAUSE HEADACHES, DIZZINESS & IRRITATE EYES & RESPIRATORY TRACT.

Effects of Overexposure:HIGH VAPOR CONCENTRATIONS (GREATER THAN APPROXIMATELY 1000 PPM) ARE IRRITATING TO THE EYES AND THE RESPIRATORY TRACT, MAY CAUSE HEADACHES AND DIZZINESS, ARE ANESTHETIC, AND MAY HAVE OTHER CENTRAL NERVOUS SYSTEM EFFECTS.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THIS MATERIAL.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:WASH WITH SOAP & WATER.EYE:FLUSH WITH WATER FOR 15 MINUTES,HOLDING EYELIDS OPEN.INHALED:REMOVE TO FRESH AIR & PROVIDE

OXYGEN/CPR IF NEEDED.

ORAL:DO NOT INDUCE VOMITING.GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:126F,52C

Lower Limits:0.7

Upper Limits:6.5

Extinguishing Media:WATER SPRAY, CO2, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS SUCH AS CARBON MONOXIDE AND CARBON DIOXIDE

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE THE AREA. CONTAIN THE SPILL. PICK UP LARGE SPILL WITH NON-SPARKING TOOLS; SMALL SPILLS/RESIDUE WITH INERT ABSORB

ENT MATERIAL. PLACE IN CONTAINERS. PREVENT ENTERING WATERWAYS/SEWERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL,VENTILATED AREA,IN TIGHTLY CLOSED CONTAINERS,AWAY FROM HEAT,FLAMES & OXIDIZERS.

Other Precautions:"EMPTY" CONTAINERS MAY RETAIN RESIDUE AND CAN BE DANGEROUS.DO NOT PRESSURIZE,CUT,WELD,BRAZE,SOLDER,DRILL,GRIND OR EXPOSE SUCH CONTAINERS TO HEAT,FLAME,SPARKS.THEY MAY EXPLODE AND CAU

SE INJURY/ DEATH.A VOID REPEATED/PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHERE ADEQUATE VENTILATION CONDITIONS EXIST. IF AIRBORNE CONCENTRATION EXCEEDS TLV, A NIOSH-APPROVED MIST RESPIRATOR IS RECOMMENDED.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:IMPERVIOUS AS NEEDED

Eye Protection:GOGGLES AND FACE SH

FIELD IF NEEDED

Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

KEY1: F4. THE KIT CONTAINS EIGHT 1 QT BOTTLES DISPERSANT AND TWO 600 CC BOTTLES OF TONER. THIS MSDS IS FOR THE TONER.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:=18

O.C, 356.F

Vapor Pres:5

Spec Gravity:0.75

Evaporation Rate & Reference:0.3 (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK LIQUID. FAINT PETROLEUM HYDROCARBON ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS SUCH AS LIQUID CHLORINE AND CONCENTRATED OXYGEN.

Stability Condition to Avoid:EXCESSIVE HEAT, SPARKS, FLAME AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products

ts:CARBON MONOXIDE AND CARBON DIOXIDE AND

OTHER DECOMPOSITION PRODUCTS IN CASE OF INCOMPLETE COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no

o manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.