View NSN Online: https://aerobasegroup.tw/nsn/1730-01-182-0364

Product ID:ETHER MSDS Date:05/01/1991 FSC:1730 NIIN:01-182-0364 **MSDS Number: BQFFF** === Responsible Party === Company Name: QUICK START PRODUCTS LTD Address:HWY 251 S City:ROCHELLE State:IL ZIP:61068 Country:US Info Phone Num:815-562-5414 Emergency Phone Num:815-562-5414 CAGE:78280 === Contractor Identification === Company Name: QUICK START PRODUCTS LTD Address: HIGHWAY 251 SOUTH Box:City:ROCHELLE State:IL ZIP:61068 Country:US Phone:815-562-5414 CAGE:78280 Ingred Name: ETHYL ETHER (SARA III) CAS:60-29-7 RTECS #:KI5775000 Fraction by Wt: 91% Other REC Limits:NONE RECOMMENDED OSHA PEL:400 PPM/500 STEL ACGIH TLV:400PPM/500STEL; 9293 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS Ingred Name: ETHYLENE (SARA III) CAS:74-85-1 RTECS #:KU5340000 Fr

action by Wt: 6.5% Other REC Limits:NONE RECOMMENDED ACGIH TLV:ASPHYXIANT; 9293

Ingred Name:ETHYL ALCOHOL (ETHANOL) CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 2.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9293

Ingred Name:2,6-DI-TERT-BUTYL-P-CRESOL CAS:128-37-0 RTECS #:GO7875000 Fraction by Wt: .001% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3; 9293

LD50 LC50 Mixt ure:TLV=400PPM;STEL=500PPM ETHER,RTEC 92-4 Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES:MAY CAUSE CONJUCTIVITIS.INHAL:RESPIRATORY IRRITATION,HEADACHE,DIZZINESS,ANOREXIA,NAUSEA,SLEEPINESS. Explanation of Carcinogenicity:HMIS FOUND A MONOGRAPH ON DIETHYL ETHER IN RTECS 92-4,SHOWING DNA MUTATION IN E.COLI. Effects of Overexposure:MFG STATES THAT CASUAL EXPOSURE SHOULD HAVE NO ADVERS

Е

EFFECTS.INHAL:HEADACHE,DIZZINESS,ANOREXIA,NAUSEA,VOMITING,SLEEPINES S.

Medical Cond Aggravated by Exposure:NONE REPORTED BY MANUFACTURER.

First Aid:INGEST:IF CONSCIOUS,GIVE MILK OR WATER.DON'T GIVE ANYTHING ACIDIC(EG.JUICE).CALL PHYSICIAN.INDUCE VOMITING ONLY! IF ADVISED BY TREATING PHYSICIAN.INHAL:REMOVE TO FRESH AIR.RESTORE BREATHING BY MOUTH-T O-MOUTH RESPIRATION(PREFERRABLY).CALL PHYSICIAN.EYES:FLUSH WITH WATER FOR 15 MINUTES.DO NOT RUB EYES!SKIN:REMOVE CONTAMINATED CLOTHING.FLUSH WITH WATER.CALL PHYSICIAN.

Flash Point Method:COC Flash Point:-49F,-45C Lower Limits:1.9 **Upper Limits:48** Extinguishing Media: DRY CHEMICAL, FOAM, CARBON DIOXIDE. Fire Fighting Procedures: WATER IS INEFFECTIVE IN FIGHTING A FIRE, BUT MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. USE A SCBA IN POSITIVE PRESSURE MODE.FLUSH AWAY SPILLS NOT IGNITED. Unusual Fire/Explosion Hazard: VAPORS TRAVEL AND ARE A FLASH-BACK HAZARD.RUNOFF TO SEWERS ARE FIRE/EXPLOSION HAZARD.FIRE PRODUCES SMOKE AND HAZARDOUS DECOMPOSITION PRODUCTS. Spill Release Procedures: REMOVE SOURCES OF IGNITION. VENTILATE. FLUSH LARGE SPILLS WITH WATER; AVOID RUNOFF TO SEWERS. ADSORB SMALL SPILLS WITH AN INERT MATERIAL; PLACE IN AN APPROPRIATE CONTAINER FOR DISPOSAL, OR ALLOW TO EVAPORAT E (USING GOOD VENTILATION). Handling and Storage Precautions: STORE BELOW 175F.KEEP AWAY FROM SOURCES OF COMBUSTION AND COMBUSTIBLE MATERIALS.PREVENT DAMAGE TO CONTAINERS.KEEP AWAY FROM RESIDENTIAL STRUCTURES. Other Precautions: NO SMOKING IN STORAGE AREAS. Respiratory Protection: USE A NIOSH/MSHA APPROVED RESPIRATOR WHEN HIGH CONCENTRATIONS ARE PRESE NT. Ventilation:NATURAL VENTIALTION IS PREFERRED.ENGINEERING CONTROLS MUST BE EXPLOSION PROOF IF USED. Protective Gloves: FOR PROLONGED USE-NITRILE Eye Protection: GOGGLES MEETING ANSI 287.1 Other Protective Equipment: IF SKIN CONTACT IS ANTICIPATED USE NITRILE COATED CLOTHING. Work Hygienic Practices: USE PRUDENT HYGENIC AND SANITARY PRACTICES. Supplemental Safety and Health NONE.

HCC:V3 Boiling Pt:B.P. Text:94.0F,34.4C Vapor Pres:7.3ATM Vapor Density:2.6 Spec Gravity:.695 Evaporation Rate & amp; Reference:6.9 Solubility in Water:MODERATE Appearance and Odor:AEROSOL;COLORLESS;ETHER-LIKE ODOR(SWEET-PUNGENT) Percent Volatiles by Volume:>98

Stability Indicator/Materials to Avoid:YES OXIDIZERS,CHEMICALS THAT UNDERGO SPONTANEOUS COMBUSTION. Stability Condition to Avoid:TEMPERATURES ABOVE 175F,FLAMES,SOURCES OF IGNITION.EXPLOSIVE PEROXIDES FORM AS PRODUCT AGES/CONCENTRATES. Hazardous Decomposition Products:CARBON MONOXIDE,VARIOUS ALDEHYDES.

Waste Disposal Methods:1-ALLOW SMALL AMOUNTS TO EVAPORATE.2-USE CONTENTS COMPLETELY, THEN DISPOSE OF IN NORMAL TRASH; DO NOT PUNCTURE OR INCINERATE CANS.FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of t he Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.