

CROSSFIELD PRODUCTS CORP -- DEX-O-TEX AJ-44 DRESSING,PART B -- 5610-00-852-1901

=====
Product Identification
=====

Product ID:DEX-O-TEX AJ-44 DRESSING,PART B

MSDS Date:08/09/1989

FSC:5610

NIIN:00-852-1901

MSDS Number: BQWLV

=== Responsible Party ===

Company Name:CROSSFIELD PRODUCTS CORP

Address:3000 E. HARCOURT ST

City:COMPTON

State:CA

ZIP:90221-5504

Country:US

Info Phone Num:213-636-0561

Emergenc

y Phone Num:213-636-0561

CAGE:60782

=== Contractor Identification ===

Company Name:CROSSFIELD PRODUCTS CORP.

Address:3000 EAST HARCOURT ST.

Box:City:COMPTON

State:CA

ZIP:90221

Country:US

Phone:310-886-9100

CAGE:60782

=====
Composition/Information on Ingredients
=====

Ingred Name:PROPYLENE (PROPENE) (SARA III)

CAS:115-07-1

RTECS #:UC6740000

Fraction by Wt: 1.9%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:ASPHIXIANT; 9293

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ857

5000
Fraction by Wt: 1.4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:PHENYLMERCURIC ACETATE (SARA III)
CAS:62-38-4
RTECS #:OV6475000
Fraction by Wt: 0.1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG HG/M3;CEIL;S
ACGIH TLV:0.01 MG HG/M3; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:AMMONIA (SARA III)
CAS:7664-41-7
RTECS #:BO0875000
Fraction by Wt: 0.06%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:25 PPM/35 STEL;
9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ACGIH TLV=25PPM 2-BUTOXY ETHANOL
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN/EYES:IRRITANT.INHAL:CAUSE
GASTROINTESTINAL DISTURBANCES(RTECS 92-4).
Explanation of Carcinogenicity:2-BUTOXY ETHANOL HAS BEEN INVESTIGATED
BY RTECS 92-4 AS A TUMORIGEN AND REPROD
UCTIVE EFFECTOR.
Effects of Overexposure:INHAL:NAUSEA,VOMITING.
Medical Cond Aggravated by Exposure:MANUFACTURER STATES NONE.

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR.EYES:FLUSH WITH WATER FOR 15
MINUTES;GET MEDICAL ATTENTION.SKIN:REMOVE CONTAMINATED
CLOTHING;WASH WITH SOAP AND WATER.INGEST:DO NOT INDUCE VOMITING!!IF
CONSCIOUS,GIVE 2 PINTS OF WATER.GET MEDICAL ATTENTION.

===== Fire Fighting Measures

Flash Point:>300F,>149C
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL.
Fire Fighting Procedures:NO SPECIAL REQUIREMENTS.
Unusual Fire/Explosion Hazard:MATERIEL MAY SPLATTER IF HEATED ABOVE
212F.

===== Accidental Release Measures =====

Spill Release Procedures:ADSORB ONTO PEARLITE OR BORAX.PLACE IN AN
APPROPRIATE CONTAINER FOR DISPOSAL.CLEAN UP AREA WITH WATER.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING;PRODUCT WILL
COAGULATE.AVOID PROLONGED OR REPEATED INHALATION OF MISTS OR
VAPORS.

Other Precautions:WASH THOROUGHLY AFTER USING.PROVIDE PROPER
VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED IN NORMAL SERVICE.

Ventilation:CONFINED AREAS SHOULD BE VENTILATED EITHER BY LOCAL OR
GENERAL MECHANICAL EXHAUST.

Protective Gloves:RUBBER OR CHEMICAL
LY RESISTANT.

Eye Protection:CHEMICAL GOGGLES.

Other Protective Equipment:CLOTHING TO AVOID SKIN CONTACT.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET
CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK
AREA.

Supplemental Safety and Health

KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text: