Product ID:BRAKE PART CLEANER MSDS Date:07/04/1993 FSC:6850 NIIN:01-158-3928 MSDS Number: BRJLD === Responsible Party === Company Name: QPL CORP (WAS OMNITECH INTERNATIONAL) Address:800 N ACADIA RD **City:THIBODAUX** State:LA ZIP:70301 Country:US Info Phone Num:504-394-8440FAX 504-393-770 0 Emergency Phone Num:504-446-2003 CAGE: JO788 === Contractor Identification === Company Name: QPL CORP Address:40 IDLE BAY DR Box:City:CENTERPORT State:NY ZIP:11721-1138 Country:US Phone:516-754-0371 CAGE:0RHE6 Company Name: QPL CORP (WAS OMNITECH INTERNATIONAL) Address:800 NORTH ACADIA RD City:THIBODAUX State:LA ZIP:70301 Country:US Phone:504-449-8440/504-394-8440 CAGE: JO788 Company Name: QPL INC, FORMERLY OMNITECH INTERNATIONAL, INC. Address:800 N. ACADIA ROAD Box:City:THIBODAUX State:LA ZIP:7030

1 Country:US Phone:504-394-8440 CAGE:0AD61 Company Name: UNI-KEM INTERNATIONAL Address:1001 HARIMAW COURT EAST Box:City:METAIRIE State:LA ZIP:70001 Country:US Phone:504-835-7600/FAX:504-835-7608 CAGE:4S446 Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III) CAS:71-55-6 RTECS #:KJ2975000 Fraction by Wt: 75% Other REC Limits:NONE RECOMMENDED OSHA PEL:350 PPM/450 STEL ACGIH TLV:350 PPM/450STEL;9293 EPA Rpt Qty:1000 LB S DOT Rpt Qty:1000 LBS **Ozone Depleting Chemical:1** Ingred Name: PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III) CAS:127-18-4 RTECS #:KX3850000 Fraction by Wt: 25% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:25PPM/100,A3 STEL;94 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:CARBON DIOXIDE (PROPELLANT) CAS:124-38-9 RTECS #:FF6400000 Other REC Limits:NONE RECOMMENDED OSHA PEL:5000 PPM ACGIH TLV:5000PPM/30000STEL;93

===========

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: MAY CAUSE EYE & SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CENTRAL NERVOUS SYSTEM DEPRESSANT. LOSS OF CONSCIOUSNESS AND EVEN DEATH CAN OCCUR AT HIGH LEVELS OF EXPOSURE. SWALLOWING MAY CAUSE GI TRACT IRRITATION AND LEADTO ASPIRATION OF VOMIT WHICH CAN BE FATAL. Explanation of Carcinogenicity:NO INGREDIENT IS LISTED AS A CARCINOGEN BY NTP, IARC OR OSHA Effects of Overexposure: INHALED: COUGHING, WHEEZING, SHORTNESS OF BREATH, DIZZINESS, DROWSINESS, NAUSEA, VOMITING, HEADACHE. EYES: REDNESS, TEARING, BURNING SENSATION. SKIN: RASH, ITCHING, DRYING. INGESTED: NAUSEA, VOMITING, DIZZINESS, DROWSINESS, HEADACHE. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. 

First Aid:INHALATION: REMOVE TO FRESH A IR. IF NOT BREATHING, GIVE CPR.

IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. EYE: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL AT TENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER PROMPTLY. INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE LOTS OF WATER. GET IMMEDIATE MEDICAL ATTENTION.

Flash Point Method:TCC
Flash Point:>200F,>93C
Lower Lim
its:7.5
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. EXPOSURE TO FIRE MAY

CAUSE CAN TO EXPLODE.

Spill Release Pr

ocedures:ALLOW PROPELLENTS TO BOIL AND EVAPORATE. MAINTAIN GOOD VENTILATION. IF LIQUID SPILLS, ABSORB WITH DRY ABSORBENT AND PLACE IN A CONTAINER FOR LATER DISPOSAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED LOCATION, AWAY FROM ANY AREA WHERE THE FIRE HAZARD MAY BE ACUTE.
KEEP CONTAINERS CLOSED WHEN NOT IN USE.
Other Precautions:REA
D AND FOLLOW DIRECTIONS ON LABEL. DO NOT REUSE

CONTAINERS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE NORMALLY REQUIRED. IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR, OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.13 4.

Ventilation:LOCAL EXHAUST RECOMMENDED TO CONTROL VAPORS BELOW 50% OF TLV.

Protective Gloves:NITRILE, BUTYL, OR NEOPRENE RECO

**MMENDED** 

Eye Protection: USE SAFETY GLASSES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.APRON AND WORK CLOTHING TO MINIMIZE EXPOSURE. EYE WASH STATION & SAFETY SHOWER RECOMMENDE

Work Hygienic Practices: WASH THOROUGHLY AFTER USE AND BEFORE EATING, SMOKING OR USING TOILET FACILITIES. DO NOT BREATH VAPORS OR MIST. Supplemental Safety and Health

TARGET ORGANS ARE SKIN, CNS, CVS, AND EYES. VAPORS WILL COLLECT IN LOW AREAS.

================== Physical/Chemical Properties

\_\_\_\_\_

HCC:V2 Boiling Pt:B.P. Text:>200F,>93C Vapor Pres:>1 Spec Gravity:1.3 (WATER=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:AEROSOL PRESSURIZED SPRAY Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

## HYDROGEN CHLORIDE, HYFROFLUORIC ACID FUMES

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and discla

ims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.