

FARWEST PAINT MFG CO -- ANTI-SWEAT COATING COMPOUND WHITE 37778 -- 8010-00-965-2507
===== Product Identification =====

Product ID:ANTI-SWEAT COATING COMPOUND WHITE 37778

MSDS Date:04/01/1992

FSC:8010

NIIN:00-965-2507

MSDS Number: BRKJT

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-941-1619

Preparer's Name:NORMA HABEEB

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS 350

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 18.51%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:P

ARAFFINS (INC.NAPHTHENES)
CAS:64742-47-8
Fraction by Wt: 3.32%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:70 PPM

Ingred Name:AROMATICS
CAS:64742-95-6
Fraction by Wt: 6.45%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:70 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: THIS MATERIAL MAY CAUSE
IRRITATION, SENSITIZATION, OR D
EFATTING OF SKIN UPON PROLONGED OR
REPEATED CONTACT. INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR SPRAY
MISTS CAN RESULT IN HEADACHE, DIZZIN ESS, NAUSEA & LOSS OF
CONSCIOUSNESS. EYES: THIS MATERIAL MAY BE AN EYE IRRITANT.
Effects of Overexposure:SOME REPORTS HAVE ASSOCIATED REPEATED AND
PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT
BRAIN & NERVOUS SYSTEM DAMAGE.
Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH
SAFE HANDLING INSTRUCTIO
NS.

===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH WITH SOAP & WATER. EYES: FLUSH WITH LARGE
QUANTITIES OF WATER FOR 15 MINUTES & GET MEDICAL ATTENTION.
INGESTION: DO NOT INDUCE VOMITING, KEEP PERSON WARM, QUIET & GET
MEDICAL ATTEN TION. ASPIRATION OF MATERIAL INTO LUNGSCAN CAUSE
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. INHALATION: REMOVE TO
FRESH AIR IMMEDIATELY. IF RESPIRATORY SYMPTOMS DEVELOP, GET MEDICAL
ATTENTION
AT ONCE.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG. USE ANY CLASS B
EXTINGUISHING AGENT. WATER USED ONLY TO COOL CONTAINERS.
Fire Fighting Procedures:FIREFIGHTERS & OTHERS EXPOSED TO VAPORS OR
PRODUCTS OF COMBUSTION SHOULD WEAR SCBA. EVACUATE AREA OF
UNPROTECTED PERSONNEL. WEAR PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN
AIR & M

AY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED
CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENT AREA.
ABSORB SPILL WITH AN ABSORBENT MATERIAL SUCH AS SAWDUST, OR SAND,
ETC & PLACE INTO CLOSED CONTAINER. IF LARGE SPILL, DIKE AREA TO
PREVENT FROM ENTERING ALL WATERWAYS. WEAR PROTECTIVE CLOTHING
DURING CLEANUP.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED OR REPEATED INHALATION
OF HEATED VAPORS OR SPRAY MISTS. KEEP AWAY FROM HEAT OR OPEN FLAME.
THIS MATERIAL MAY CAUSE SENSITIZATION.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR CLOTHING. DO NOT ALLOW
CONTAMINATED CLOTHING TO CONTACT SKIN. DO NOT WELD ON FULL OR EMPTY
CONTAINERS. KEEP CONTAINERS CLOSED, WHEN NOT IN USE, & PROPERLY
LABELED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER-TYPE RESPIRATOR MUST BE WORN TO
PREVENT THE INHALATION OF VAPORS OR SPRAY MISTS WHEN THE TLV OR PEL
IS EXCEEDED.

Ventilation:GENERAL VENT IS REQUIRED DURING NORMAL USE. LOCAL VENT
REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOSURE BELOW LIMITS.

Protective Gloves:CHEMICAL RESIS, NITRILE, NEOPRENE,RUBBER

Eye Protection:CHEMICAL GOGGLES OR FACE SHIELD

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN
CONTACT

. EYE WASH STATION & SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:157 TO 300F

Vapor Pres:7 @ 20C

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH ST

STRONG OXIDANTS, ACIDS, BASES & EPOXY HARDENERS
UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid: HEAT, SPARKS, & OPEN FLAMES. IF PRODUCT
CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS WILL GENERATE
HYDROGEN GAS.

Hazardous Decomposition Products: INCOMPLETE COMBUSTION CAN YIELD CARBON
MONOXIDE & TOXIC VAPORS.

===== Disposal Considerations =====

Waste Disposal Methods: MATERIAL/CONTAINERS TREATED AS HAZARDOUS WASTE
BASED ON CHARACTER OF
IGNITABILITY DEFINED UNDER FEDERAL RCRA
REGULATIONS (40 CFR 261). DISPOSAL OF MATERIAL/CONTAINERS REQUIRES
COMPLY WITH APPLICABLE LABEL, PACK, RECORD, STANDARDS. GROUND EQUIP
PREVENT SPARK

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability
for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.