

HENTZEN COATINGS, INC -- 383 BROWN ZENTHANE P/N 08606TUZ-GD -- 8010-01-229-7545
===== Product Identification =====

Product ID:383 BROWN ZENTHANE P/N 08606TUZ-GD

MSDS Date:04/26/1993

FSC:8010

NIIN:01-229-7545

MSDS Number: BRKLF

=== Responsible Party ===

Company Name:HENTZEN COATINGS, INC

Address:6937 W MILL ROAD

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Info Phone Num:414-353-4200

Emergency Pho

ne Num:414-353-4200/800-424-9300 CHEMTREC

Preparer's Name:JANE FREEMAN

CAGE:09225

=== Contractor Identification ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Phone:414-353-4200

CAGE:09225

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOAMYL KETONE (SOLVENT)

CAS:110-12-3

RTECS #:MP3850000

Fraction by Wt: 24.302%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM;

9293

Ingred Name:BLACK IRON OXIDE (PIGMENT) (EXPOSURE LIMITS ARE FOR IRON OXIDE FUME)

CAS:1317-61-9

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

Ingred Name:RED IRON OXIDE (PIGMENT) (EXPOSURE LIMITS ARE FOR IRON OXIDE FUME)

CAS:1309-37-1

RTECS #:NO7400000

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:SILICA (PIGMENT)

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 20-30

%

Other REC Limits:NONE SPECIFIED

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE

CAS:28182-81-2

RTECS #:NQ9170000

Fraction by Wt: 20-30%

Other REC Limits:.5 PPM/STEL 1 MG/M3

Ingred Name:TRIVALENT CHROME (INSOLUBLE) (SARA III)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: 5.116%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.5 MG/M3

ACGIH TLV:0.5 MG/M3

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:AROMATIC HYDROCARBON (MIXTURE OF C8'S T

O C10'S)
CAS:64742-95-6
Fraction by Wt: 1.198%
Other REC Limits:MFR LIMIT: 100 PPM

Ingred Name:BUTYL ACETATE (SOLVENT)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 1.198%
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM
ACGIH TLV:150 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:HEXAMETHYLENE DIISOCYANATE MONOMER
CAS:822-06-0
RTECS #:MO1740000
Fraction by Wt: 0.048%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.005 PPM
ACGIH TLV:0.005 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred N
ame:VM&P NAPHTHA (SOLVENT)
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 4.959%
Other REC Limits:NONE SPECIFIED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:XYLENE (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 1.950%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/STEL 150 PPM
ACGIH TLV:100 PPM/STEL 150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC: 3.485 LBS/GAL; 417.152 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Haz

ards Identification =====

Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES

Health Hazards Acute and Chronic:ACUTE; IRRITATION TO SKIN, EYES, & RESPIRATORY TRACT (WATERING EYES, DRY THROAT, COUGHING, HEADACHE, TIGHT CHEST, BURNING SENSATION). HEADACHE, DIZZINESS, NAUSEA MAY BE EXPERIENCED BY SOME AS A RESULT OF EXPOSURE TO SOLVENTS.

Explanation of Carcinogenicity:IARC HAS LISTED SILICA AS A PROBABLE HUMAN CARCINOGEN.

Effects of Overexposure:CHRONIC: REPEATED & PROLONGED OCCUPATIONAL

OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE, LIVER, & KIDNEY DAMAGE. RESPIRATORY SENSITIZATION (ASTHMA LIKE SYMPTOMS), SKIN SENSITIZATION (RASH, ITCHING, HIVES, SWELLING OF THE EXTREMITIES). DERMATITIS.

Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY AILMENTS; CHEMICAL SENSITIZATION.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP

WARM & QUIET. NOTIFY PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH RUNNING WATER FOR AT LEAST 15 MIN, LIFTING EYELIDS. TAKE TO PHYSICIAN. SKIN: WASH AFFECTED AREAS WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. WASH BEFORE REUSE. CONSULT PHYSICIAN IF IRRITATION DEVELOPS/PERSISTS. INGESTION: CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:54.0F,12.2C

Auto

ignition Temp:Autoignition Temp Text:450.0F

Lower Limits:0.9

Upper Limits:8.2

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT WITH SELF-CONTAINED BREATHING APPARATUS. DURING FIRE, IRRITATING/HIGHLY TOXIC GASES & SMOKE PRESENT FROM DECOMP/COMBUSTION PRODUCTS.

Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD.KEEP FROM HEAT/IGNIT SOURCE.CLSD CNTNR MAY EXPLODE W/HEAT,BURST W/WATER CONTAMINATN. DONT APPLY TO HOT SRFCS.NEVER CUT

,WELD NEAR DRUM-EXPLOSIVE.

===== Accidental Release Measures =====

Spill Release Procedures:EVAC NON-ESSENTL PEOPLE.REMOVE IGNIT SOURCE.VENT.AVOID BREATHING.COVER SPILL W/INERT ABSORB.POUR LIQ DECONTAM OVER SPILLAGE-ALLOW 10 MIN REACT TIME.COLLECT MAT'L IN OPEN CNTNR ADD DECONTAM SOLUTION.CO VER LOOSELY.WASH DOWN AREA W/DECONTAM,FLUSH W/H2O.

Neutralizing Agent:0-10%AMMONIUM HYDROXIDE,2-5%DETERGENT & WATER.SOLUTN:TEGRITOL 20%TMN-10,80%WATER

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F OR BELOW 32F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP FROM SPARKS & OPEN FLAME.

Other Precautions:KEEP CNTNR CLOSED. IF MOISTURE ENTERS, DONT RESEAL. DONT INGEST. GROUND CNTNRS WHEN POURING. AVOID LIQ FREE FALL >FEW INCHES. USE W/VENT & RESP EQUIP. EMPTIED CNTNRS MAY RETAIN HZD RESIDUE. FOLLOW PRE CAUTIONS. AVOID EYE, SKIN, CLOTH CONTACT

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AIRLINE RESPIRATOR UNLESS AIR SAMPLING SHOWS EXPOSURE TO BE BELOW PEL. THEN, EITHER CHEMICAL CARTRIDGE RESPIRATORS OR AIRLINE RESPIRATORS REQUIRED. USE SAME PRECAUTIONS DURING MIXING OR ANY OPERAT IONS WHERE PAINT FUMES WOULD BE PRESENT.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST TO KEEP BELOW PEL/TLV DURING MIXING, APPLICATION, CURING & REMOVE DECOMP PROD (WE LD,CUT).

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:SAFETY EYEWEAR W/SPLASH GUARD & SIDESHLD

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO KEEP SKIN CONTACT AT A MINIMUM.

Work Hygienic Practices:WASH HANDS AND ANY EXPOSED SKIN THOROUGHLY BEFORE EATING OR SMOKING. SMOKE IN DESIGNATED AREAS ONLY.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:244 TO 418F

Decomp Temp:Decomp Text:400F,204C

Va

por Pres:15.00
Vapor Density:> AIR
Spec Gravity:1.22
Viscosity:65-68 KU
Evaporation Rate & Reference:FASTER THAN BUTYL ACETATE
Solubility in Water:REACTS WITH WATER
Appearance and Odor:OPAQUE LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:51.55

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
ONCE MATERIAL HAS BEEN EXPOSED TO ANY OF THE ABOVE OR ATMOSPHERIC
MOISTURE DONT SEAL CNTNR AS CO2 COULD BLDUP IN CNTNR.

Stability Co
ndition to Avoid:CONTAMINATION WITH WATER, EPOXY CATALYSTS,
ALCOHOLS, GLYCOL ETHERS, BASES, METAL COMPLEXES OR OTHER ACTIVE
MATERIALS.

Hazardous Decomposition Products:CO2, CO, OXIDES OF NITROGEN, TRACES OF
HYDROGEN CYANIDE, HEXAMETHYLENE DIISOCYANATE.

Conditions to Avoid Polymerization:SEE ABOVE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. DECONTAMINATE CONTAINERS
PRIOR TO DISPOSAL.

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.