View NSN Online: https://aerobasegroup.com/nsn/9150-00-190-0919

## NONFLUID OIL CORP/NFO TECHNOLOGIES, INC -- VV-G-671F -- 9150-00-190-0919

Product ID:VV-G-671F MSDS Date:01/10/1992

FSC:9150

NIIN:00-190-0919

MSDS Number: BRNJP === Responsible Party ===

Company Name: NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009 Country:US

Info Phone Num:201-344 3451 Emergency Phone Num:201-344 -3451/800-424-9300(CHEMTREC)

CAGE:76736

=== Contractor Identification ===

Company Name: NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Phone:201-344-3451/800-424-9300(CHEMTREC)

CAGE:76736

Company Name: SUMMIT LUBRICANTS INC

Address:4080 PEARL STREET

Box:966

City:BATAVIA

State:NY ZIP:14020 Country:US

Phone:716-344-4301/716-685-1576

CAGE:0R0E6

======= Composition/Information on Ingredients ========

Ingred Name: HYDROTREATED

HEAVY NAPHTHENIC DISTILLATE, PETROLEUM CAS:64742-52-5 RTECS #:PY8035000 Fraction by Wt: 100% Other REC Limits: NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST) ========== Hazards Identification =============== LD50 LC50 Mixture:TLV 10 MG/M3 OIL MIST Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT TENDS TO REMOVE SKIN OILS AND MAY CAUSE SKIN IRRITATION, EXPOSURE TO FUMES OR MISTS MAY CAUSE MUCOUS MEMBRANE IRRITATION. Effects of Overexposure: EYES/SKIN: IRRITATION AND DRYNESS ON PROLONGED CONTACT, INHALATION: FUMES OR MISTS MAY CAUSE MUCOUS MEMBRANE IRRITATION. Medical Cond Aggravated by Exposure: NONE. First Aid:EYES: FLUSH WITH PLENTY OF WATER. IF IRRITATION PERSISTS, SEE DOCTOR. SKIN: WIPE OFF AND WASH WITH SOAP AND WATER. INHA LATION: REMOVE FROM EXPOSURE TO FRESH AIR. INGESTION: GIVE WATER. DO NOT INDUCE V OMITING, SEE DOCTOR. --IF PRODUCT IS INJECTED UNDER THE SKIN, SEE DOCTOR IMMEDIATELY REGARDLESS OF APPEARANCE OR SIZE. THIS IS A SERIOUS MEDICAL EMERGENCY--Flash Point Method:COC Flash Point:>360F,>182C Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. Fire Fighting Procedures: WEAR FIRE FIGHTING PROT ECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

======= Accidental Release Measures ==========

Spill Release Procedures:SCRAPE UP GREASE. WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT. ABSORB IN INERT MATERIAL AND PLACE IN APPROPIATE DISPOSAL CONTAINER AND COVER. WASH AREA

============ Handling and Storage =============
Handling and Storage Precautions:HANDLE AND STORE USING METHODS GENERALLY ADVOCATED FOR PETROLEUM PRODUCTS. DO NOT STORE OR MIX WITH OXIDIZING MATERIALS. AVOID EXCESSIVE HEAT OR FLAME Other Precautions:AVOID REPEATED CONTACT WITH SKIN. AVOID CONTACT WITH EYES AND INHALATION OF FUMES, VAPORS OR MISTS. DO NOT INGEST.
====== Exposure Controls/Personal Protection ========
Respirato ry Protection:NONE NORMALLY NEEDED. RESPIRATORY PROTECTION RECOMMENDED IF FUMING OR MISTING. Ventilation:GENERAL (MECHANICAL) VENTILATION. USE LOCAL EXHAUST WHEN HANDLING HOT FUMES. Protective Gloves:NITRILE, PVA. Eye Protection:SAFETY GLASSES. Other Protective Equipment:OIL RESISTANT APRON. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health NONE.
======== Physical/Chemical Properties ===========
HCC:V6 Boiling Pt:B.P. Text:>550F,>288C Melt/Freeze Pt:M.P/F.P Text:200F,93C Vapor Pres:10 Spec Gravity:0.91 Evaporation Rate & Description of the company o

WITH SOAP AND WATER.