

STEPAN COMPANY -- STEPANFOAM G-302-R -- 9330-00-180-6162

=====
Product Identification
=====

Product ID:STEPANFOAM G-302-R

MSDS Date:12/06/1990

FSC:9330

NIIN:00-180-6162

Kit Part:Y

MSDS Number: BRPBM

=== Responsible Party ===

Company Name:STEPAN COMPANY

Address:22 W FRONTAGE ROAD

City:NORTHFIELD

State:IL

ZIP:60093-3407

Country:US

Info Phone Num:312-446-7500

Emergency Phone Num:312-446-7500

CAGE:87

570

=== Contractor Identification ===

Company Name:STEPAN COMPANY

Address:EDENS EXPY WINNETKA RD

Box:City:WINNETKA

State:IL

ZIP:60093

Country:US

Phone:800-228-5635, CHEMTREC 800-424-9300

CAGE:87570

=====
Composition/Information on Ingredients
=====

Ingred Name:NON HAZARDOUS INGREDIENT

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:N

O IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES-CONTACT WITH EYES IS PAINFUL AND IRRITATING. SKIN-PROLONGED OR REPEATED CONTACT WITH SKIN CAUSES IRRITATION. INHALATION-MIS CAUSED BY MANUFACTURING OPERATIONS IRRITATES NASAL PASSAGE.

Explanation of Carcinogenicity:NOT IDENTIFIED AS A CARCINOGEN BY OSHA, IARC OR NTP.

Effects of Overexposure:CHRONIC EFFECTS & MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE TO THIS PRODUCT HAS NOT BEEN ESTABLISHED, UNNECESSARY EXPOSUR

E TO THIS PRODUCT OE ANY CHEMICAL SHOULD BE AVOIDED.

Medical Cond Aggravated by Exposure:NOT ESTABLISHED.

=====
===== First Aid Measures =====

First Aid:EYES-FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SKIN-WASH OFF SKIN WITH WATER. REMOVE CONTAMINATED CLOTHING AND CLEAN BEFORE REUSE. INHALATION- IF VAPORS OR MIST CAUSE IRRITATION OR DISTRESS, REMOVE TO FRESH AIR. GIVE OXYGEN OR APPLY ARTIFICIAL RESPIRATION, IF NEEDED
. INGESTION-IF SWALLOWED,
CONSULT A PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:>230F,>110C

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM, OR WATER FOG. CLASS BC, ABC EXTINGUISHER.

Fire Fighting Procedures:SELF-CONTAINED POSITIVE PRESSURE BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.

Unusual Fire/Explosion Hazard:NONE KNOWN.

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN ALL SPILLS AND LEAKS TO PREVENT DISCHARGE INTO THE ENVIRONMENT. VENTILATE AREA. SMALL: SOAK UP WITH ABSORBENT, SHOVEL INTO WASTE CONTAINER, FLUSH AREA WITH WATER. LARGE: RECOVER LIQUID FOR REPROCESSING OR DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A DRY, WELL VENTILATED AREA AT ABOUT 65-85 DEG. F. RELEASE PRESS

URE CAREFULLY BEFORE OPENING
CONTAINERS.

Other Precautions:SPILLED MATERIAL IS SLIPPERY. WASH THOROUGHLY AFTER
HANDLING. IF INGESTED, CALL A PHYSICIAN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VAPORS ARE PRESENT, USE NIOSH OR MSHA
APPROVED RESPIRATOR FOR ORGANIC VAPORS, AIR-LINE RESPIRATOR, OR
SELF-CONTAINED BREATHING APPARATUS.

Ventilation:USE ADEQUATE VENTILATION.

Protective Gloves:USE IMPERVIOUS GLOVES.

Eye Protection:WEAR
FULL FACE SHIELD/GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT REPEATED
OR PROLONGED CONTACT.

Work Hygienic Practices:EYE WASH STATION AND SAFETY SHOWER SHOULD BE
NEAR WORK AREA.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>212F,>100C

Vapor Density: