

MINNESOTA MINING & MFG CO ELECTRICAL PRODUCTS,(3M) -- SCOTCH A-2 CABLE
PREPARATION KIT -- 5975-01-015-2758

===== Product Identification =====

Product ID:SCOTCH A-2 CABLE PREPARATION KIT

MSDS Date:01/16/1996

FSC:5975

NIIN:01-015-2758

Kit Part:Y

MSDS Number: BRQFP

=== Responsible Party ===

Company Name:MINNESOTA MINING & MFG CO ELECTRICAL PRODUCTS,(3M)

Address:3M AUSTIN CTR

Box:2963

City:AUSTIN

Stat

e:TX

ZIP:78769-2963

Country:US

Info Phone Num:512-984-5670

Emergency Phone Num:512-984-5670

CAGE:75037

=== Contractor Identification ===

Company Name:BECKER JOHN A CO

Address:1341 EAST 4TH ST

Box:City:DAYTON

State:OH

ZIP:45402-2235

Country:US

Phone:513-226-1341

CAGE:12497

Company Name:MINNESOTA MINING AND MFG CO ELECTRICAL PRODUCTS DIV

Address:3M AUSTIN CTR

Box:City:AUSTIN

State:TX

ZIP:78769-2963

Country:US

Phone:512-984-1800

CAGE:75037

Company Name:MINNESOTA MINING AND MFG CO FEDERAL SYSTEMS DE

PT
Address:1101 15TH ST N W
Box:City:WASHINGTON
State:DC
ZIP:20005-5002
Country:US
Phone:202-331-6900
CAGE:9D466

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATES
CAS:64771-72-8
Fraction by Wt: 80-95%
Other REC Limits:300 PPM (MFR)

Ingred Name:D-LIMONENE
CAS:5989-27-5
Fraction by Wt: 5.0-20%
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLATILE ORGANIC CONTENT: 740.0 GRAMS/LITER.
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

=====
=====
Hazards Identification
=====

LD50 LC50 Mixture:NOT GIVEN FOR PRODUCT
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE CONTACT CAUSES MILD
IRRITATION/REDNESS/ SWELLING/PAIN/TEARING. SKIN CONTACT CAUSES
MODERATE IRRITATION/REDNESS/ SWELLING/ITCHING/DRYNESS. INHALATION
CAUSES IRRITATION OF THE UPPER RESPIRATORY TRACT/SORENESS OF NOSE
AND THROAT/COUGH
NING/SNEEZING.INGESTION CAUSES IRRITATION OF GI
TISSUES/PAIN/VOMITING/ABDOMINAL PAIN
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.
Effects of Overexposure:EYE IRRITATION/REDNESS/SWELLING/PAIN/ TEARING.
SKIN IRRITATION/REDNESS/SWELLING/ITCHING/DRYNESS. UPPER RESPIRATORY
TRACT IRRITATION/SORENESS OF NOSE AND THROAT/COUGHING/SNEEZING. GI
TRACT IRRITATION/ PAIN ABDOMINAL

TENDERNESS/NAUSEA/BLOOD

INVOMITUS/BLOOD IN FECES. ASPIRATION PNEUMONITIS/COUGHING/DIFFICULT BREATHING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION ASAP. INHALATION: MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION. SKIN: IMMEDIATELY REMOVE CONTAMINATED CLOTHI NG AND WASH WITH SOAP AND W

ATER. GET MEDICAL

ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GIVE VICTIM A GLASS OF WATER. NEVER GIVE ANYTHING BY MOUTH IF UNCONSCIOUS. CALL PHYSICIAN OR POISON CONTROL.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:144F,62C

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS AND FULL P ROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR ALL REQUIRED PROTECTIVE GEAR, SCBA PP MODE. SWEEP SPILLED PADS INTO CLOSABLE CONTAINER. VENTILATE AREA & ALLOW VAPORS TO DISSIPATE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER IN WELL-VENTI LATED

AREA. KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM HEAT, SPARKS, OPEN FLMAES AND OTHER SOURCES OF IGNITION.

Other Precautions:COMBUSTIBLE LIQUID AND VAPOR. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. WASH EXPOSED AREAS THOROUGHLY WITH SOAP AND WATER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID PROLONGED BREATHING OF VAPORS.

Ventilation:USE WITH APPROPRIATE LOCAL EXHAUST VENTILATION.

Protective Gloves:NITRILE RU

BBER, POLYETHYLENE, VITON

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

KEY1:V4. THIS IS A KIT.

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:380

F,193C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Decomp Temp:Decomp Text:NOT GIVEN

Vapor Pres:< 1.0

Vapor Density:>1

Spec Gravity:0.76

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:NIL

Appearance and Odor:CLEAR LIQUID, CITRUS-LIKE ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:CARBO

N MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no man

ner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.