

VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC. -- CAM 2 80 W 90 GO -- 9150-01-313-2191

===== Product Identification =====

Product ID:CAM 2 80 W 90 GO

MSDS Date:04/24/1990

FSC:9150

NIIN:01-313-2191

MSDS Number: BSDTS

=== Responsible Party ===

Company Name:VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC.

Address:200 E MAIN ST

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Info Phone Num:606-

264-7000

Emergency Phone Num:800-ASHLAND/800-274-5263

CAGE:72527

=== Contractor Identification ===

Company Name:BUDGET OIL CO

CAGE:8P476

Company Name:VALVOLINE OIL CO

Address:3499 BLAZER PKY

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Phone:606-357-7206 / 800-274-5263

CAGE:72527

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM OIL

Fraction by Wt: 85- 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MI

ST)

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS UNKNOWN.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE AND CHRONIC- TOXICOLOGICAL
TESTING INDICATES THAT SIMILAR PRODUCTS ARE NOT HAZARDOUS AS
DEFINED BY OSHA (29 CFR 1910.1200).

Effects of Overexposure:MAY CAUSE EYE, SKIN, RESPIRATORY TRACT
IRRITATION.

Medical Cond Aggravated
by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALATION:REMOVE TO
FRESH AIR. PROVIDE CPR IF NEEDED. EYES:FLUSH WITH WATER FOR 15
MINUTES, HOLDING EYELIDS OPEN. SKIN:REMOVE EXCESS. WASH SKIN WITH
SOAP & WATER . INGESTION:DO NOT INDUCE VOMITING. KEEP PERSON WARM &
QUIET. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:>300F,>14
9C

Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
WATER/FOAM MAY CAUSE FROTHING. COOL FIRE EXPOSED CONTAINERS WITH
WATER SPRAY.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. DO NOT SPRAY WATER
INTO CONTAINERS OF HOT, BURNING LIQUID.

Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE DUE TO PRESSURE
BUILD UP.

===== Accidental Release Measures =====

Spill Rele

ase Procedures:ABSORB SPILLS WITH NON-FLAMMABLE ABSORBENT
MATERIAL SUCH AS EARTH, SAND OR VERMICULITE. SWEEP UP AND TRANSFER
TO A CONTAINER FOR PROPER DISPOSAL. CLEAN AREA WITH APPROPRIATE
CLEANER.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY PLACE AWAY FROM STRONG
OXIDANTS. DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER
(EVEN EMPTY).

Other Precautions:DO NOT GET IN E

YES, ON SKIN OR ON CLOTHING. WASH
THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

Ventilation:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

Protective Gloves:NOT NORMALLY REQUIRED.

Eye Protection:NOT NORMALLY REQUIRED.

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS AND LEGS.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCE

DURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Vapor Density:>1

Spec Gravity:0.902

Evaporation Rate & Reference: