

FARWEST PAINT MFG CO -- EXTERIOR TRIM ENAMEL GREEN -- 8010-01-334-0907

===== Product Identification =====

Product ID:EXTERIOR TRIM ENAMEL GREEN

MSDS Date:03/23/1992

FSC:8010

NIIN:01-334-0907

MSDS Number: BSFWQ

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:20

6-941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:TEXANOL (ESTER ALCOHOL)

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 4.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC: 62 G/L

RTECS #:9999999VO

Other REC Limits:NONE SP

ECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: PROLONGED INHALATION IN
CONFINED AREAS MAY LEAD TO MUCUS MEMBRANE IRRITATION, DIZZINESS,
HEADACHE. SKIN: IRRITATION. EYES: IRRITATION. INGESTION: AMOUNTS
INGESTED INCIDENTAL TO CONSUMER & INDUSTRIAL HANDLING AREN'T
LIKELY TO INJURE, HOWEVER, INGESTI
ON OF LARGER AMOUNTS COULD CAUSE
SERIOUS INJURY.
Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH
SAFE HANDLING INSTRUCTIONS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS
DEVELOP, GET MEDICAL ATTENTION AT ONCE. SKIN: WASH OFF QUICKLY WITH
PLENTY OF WATER, THEN SOAP & WATER. REMOVE & WASH CONTAMINATED
CLOTHING BEF ORE REUSE. EYES: FLUSH IMMEDIATLEY WITHLARGE AMOUN
TS
OF WATER, ESPECIALLY UNDER LIDS, FOR AT LEAST 15 MINUTES. GET
MEDICAL ATTENTION. INGESTION: IF SWALLOWED, GET MEDICAL ATTENTION
IMMEDIATELY.

===== Fire Fighting Measures =====

Extinguishing Media:FOAM, DRY CHEMICAL, WATER FOG OR WATER
Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:WILL NOT BURN, CLOSED CONTAINERS MAY
BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

=====

===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND
ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED
WITH ABSORBENT MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID TEMPERATURES BELOW 40F. KEEP
FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND
APPROPRIATELY LABELED.
Other Precautions:USE ONLY WITH ADEQUATE VENTILATI

ON. AVOID BREATHING
VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW
APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC
VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION
AGAINST MATERIALS.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection

:SAFETY GLASSES W/UNPERF SIDE SHIELDS

Other Protective Equipment:EYE WASH - SAFETY SHOWERS - GOGGLES

Work Hygienic Practices:KEEP WORK AREA CLEAN & FREE FROM SPILLS/LEAKS.

ALWAYS WASH HANDS THOROUGHLY BEFORE EATING, SMOKING, OR DRINKING.

Supplemental Safety and Health

REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:23.8

Vapor Density:> AIR

pH:7-8

Evaporation Rate & Reference

:SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR; COLOR OF TINT

Percent Volatiles by Volume:7.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS AND/OR HYDROFLUORIC ACID

Stability Condition to Avoid:ELEVATED TEMPERATURES, CONTACT WITH
OXIDIZING AGENTS

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

Conditions to Avoid Polymerization:ELEVATED TEM

PERATURES, CONTACT WITH

OXIDIZING AGENTS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE & FEDERAL
REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to

be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.